

Triton from AML



The Next Generation is Here

SUMMIT Enterprise Class Radio

Rugged, Bright-White Backlit Display

Wear-Resistant Keypad



Built-In Terminal Emulation Clients

The Triton comes with built-in TE clients for VT100/220, TN5250 and TN3270.

Multiple Barcode Scanning Options

Choose options such as Auto-Ranging 1D Laser or 2D Imaging.

Optional "Pistol-Grip" Handle

The Triton can be configured with an optional handle for scan-intensive environments.

Just like all AML products, the AML Triton is Made in the USA. Since 1983, AML has engineered, manufactured, and supported our products in Euless, TX.



Physical Specs

Dimensions (without handle)	225 mm L x 89 mm W x 57 mm D (8.9" L x 3.5" W x 2.3" D)
Dimensions (with handle)	225 mm L x 89 mm W x 208 mm D (8.9" L x 3.5" W x 8.2" D)
Weight (without handle)	482g / 17 oz.
Weight (with handle)	709g / 25 oz.
Display	160 x 160 pixel Grayscale LCD with LED Bright White Backlight
Battery	Rechargeable 7.2V Lithium-Ion 2600 mAh, 19.2 watt-hours
Keypad	55-key alphanumeric or 35-key numeric
Pistol-Grip	Optional (Use M7501-XXXX-XX Part number)

Performance Specs

Processor	Samsung® S3C2410 @ 202 MHz
Operating Platform	AML Embedded Linux® OS; Linux® Kernel 2.6.39
Memory (RAM/ROM)	32 MB SDRAM; 16 MB Non-volatile NOR Flash
Integrated Scanning Options	Standard 1D Laser; Lorax "Near/Far" Laser; 2D Imager
Development Environment	AML M7220 SDK for Linux® supporting C and C++; GNU GCC 3.3.5 for ARM-Linux®; Fully Open Sourced Licensing

Wireless Data Communicatons

WLAN IEEE 802.11b/g/n (Summit SDC-MSD40NBT)



Security Wireless Equivalent Privacy (WEP);
Wi-Fi Protected Access (WPA);
IEEE 802.11i (WPA2)

Encryption WEP;
TKIP;
AES

Antenna Internal Dual-band Diversity

Wired Data Communications

I/O USB Type B (Slave);
Serial RS-232 (max. rate 115200 baud)

Software Tools

Terminal Emulation	VT100/102; VT220; TN5250; SSH
Utilities	Calculator; Bar Code Data Viewer; Linux Console;
Servers	TELNET; FTP; SSH/SFTP; HTTP

Optional Peripherals & Accessories

Triton communication and charging cradle (Red)
Single slot communication and charging cradle
Four slot terminal charger
Four slot battery charger
Vehicle mount terminal charger
Vehicle mount cradle (non-charging)
Holster with adjustable belt

Environmental Specs

Drop Specifications	5' (1.5M) to concrete
Operating Temp	-10° to 50°C / 14° to 122°F
Storage Temp	-25° to 50°C / -13° to 122°F
Humidity	5% to 90% RH, non-condensing
Electrostatic Discharge (EDS)	15kVDC air; 4kVDC contact, all sides
Sealing	IP51 (dust, drip waterproof)

Regulatory Specs

EMI/RFI	FCC Part 15 Class A
Laser Safety (if equipped)	CDRH Class II; IEC Class 2
Restrictions of Hazardous Material	EU RoHS Compliant / Pb Free

Linux® is the registered trademark of Linus Torvalds in the U.S. and other countries.

Specifications are subject to change without notice. All names and products are the trademarks or registered trademarks of their respective organizations.



Corporate Headquarters
2190 Regal Parkway
Euless, Texas 76040

Sales & Customer Service
Tel: 800-648-4452
Fax: 817-685-6232
Email: sales@amltd.com

www.amltd.com
www.amlkiosks.com
Local: 817-571-9015
Fax: 817-571-6176

Technical Support
Tel: 877-842-3990
Fax: 817-685-6232
Email: support@amltd.com

MADE IN USA
SINCE 1983 ★ ★ ★ ★ ★



© 2014 American Microsystems, Ltd.