



### **Overview**

- These multi-agency approved multi-output power supply/chargers convert a 115VAC/60Hz input into one (1) Class 2 Rated 12VDC or 24VDC power limited outputs.

#### **AL300ULX**

- Grey enclosure.

#### **AL300ULXR**

- Red enclosure.

### **Specifications**

- |  |  |
|--|--|
| <ul style="list-style-type: none"> <li>• 12VDC or 24VDC selectable output.</li> <li>• 2.5 amp supply current.</li> <li>• Class 2 Rated power limited output.</li> <li>• Input 115VAC / 60Hz, 1.45 amp.</li> <li>• Input fuse rated @ 3.5 amp/250V.</li> <li>• Filtered and electronically regulated output.</li> <li>• Short circuit and thermal overload protection.</li> <li>• Built-in charger for sealed lead acid or gel type batteries.</li> <li>• Maximum charge current .7 amp.</li> <li>• Automatic switch over to stand-by battery when AC fails (zero voltage drop).</li> <li>• AC fail supervision (form "C" contacts).</li> </ul> | <ul style="list-style-type: none"> <li>• Low battery supervision (form "C" contacts).</li> <li>• Battery presence supervision (form "C" contacts).</li> <li>• AC input and DC output LED indicators.</li> <li>• Enclosure:                     <ul style="list-style-type: none"> <li>- Combination knockouts are 1/2" and 3/4"</li> <li>- Accommodates up to two (2) 12VDC/7AH batteries.</li> </ul> </li> <li>• Product weight:                     <ul style="list-style-type: none"> <li>- AL300ULX: 7.7 lbs.</li> <li>- AL300ULXR: 7.3 lbs.</li> </ul> </li> <li>• Shipping weight:                     <ul style="list-style-type: none"> <li>- AL300ULX: 8.7 lbs.</li> <li>- AL300ULXR: 8.3 lbs.</li> </ul> </li> </ul> |
|--|--|

### **Agency Approvals**



- |         |   |
|---------|---|
| UL 294  | UL Listed for Access Control System Units.                                |
| UL 603  | UL Listed Standard for Power Supplies for Use with Burglar-Alarm Systems. |
| UL 1069 | UL Listed Hospital Signaling and Nurse Call Equipment.                    |
| UL 1481 | UL Listed Standard for Safety for Fire Protective Signaling Systems.      |



- CUL Listed - CSA Standard C22.2 No.205-M1983, Signal Equipment.



- MEA - NYC Department of Buildings Approved.



- CSFM - California State Fire Marshal Approved.

# Enclosure Dimensions

13"H x 13.5"W x 3.25"D

