

ALTV244UL, ALTV244ULCB Data Sheet

Rev. DSALTV244UL - D26E

Overview

• These Altronix AC Wall Mount CCTV Power Supplies provide 24VAC or 28VAC distributed via four (4) fuse or Class 2 Rated PTC protected power limited outputs for powering CCTV Cameras, heaters and other video accessories.

ALTV244UL

• Four (4) fused protected outputs. *ALTV244UL3*

ALTV244UL w/3-wire Line Cord.

ALTV244ULCB

• Four (4) Class 2 Rated PTC protected power limited outputs.

ALTV244ULCB3

Enclosure Dimensions 8.5"H x 7.5"W x 3.5"D

ALTV244ULCB w/3-wire Line Cord.

Specifications

- Input 115VAC, 50/60Hz, .9 amp.
- 24VAC @ 3.5 amp (85VA) or 28VAC @ 3 amp (85VA) supply current.
- Main fuse rated @ 5 amp/250V.
- Output ratings:
 - Fuses are rated @ 3.5 amp.
 - PTCs are rated @ 2.5 amp.
- Power ON/OFF switch.
- Surge suppression.
- AC power LED.
- Spare fuse(s) provided (all models w/primary and/or secondary fuses).
- Unit maintains camera synchronization.
- Ease of installation saves time and eliminates costly labor.

2.135° — 0.525° — 0.5

Agency Approvals



UL Listed for Commercial CCTV Equipment (UL 2044).



CUL Listed - CSA Standard C22.2 No.1-98, Audio, Video and Similar Equipment.



Canadian Standard Association



European Conformity