



Premium License-exempt Broadband Wireless Solutions

Feature Highlights

- Premium 5 GHz and 900 MHz PtMP solution
- Wide range of subscriber units supporting various applications and customer requirements
- QoS for data, voice and video applications
- Coverage range of up to 30 km Line of Sight (LOS)
- Capacity of up to 32 Mbps per sector
- 900 MHz with Near/None-Line-Of-Sight (NLOS) support, and excellent propagation capabilities
- Optimized uplink/downlink configuration to support business applications such as public safety and video surveillance
- Secure connectivity - FIPS-140-2* and HW-based FIPS-197 and AES 128
- TDD OFDM NLOS technology
- Configurable MIR/CIR per SU per direction
- Scalable license-based pay-as-you-grow configurations

* Certification in future release

BreezeACCESS[®] VL

Alvarion's BreezeACCESS VL is a flexible and field proven Point-to-Multipoint (PtMP) solution providing broadband wireless outdoor connectivity for a variety of applications in urban and rural deployments. Available in a range of frequencies in the 5 GHz and 900 MHz bands, this widely deployed platform offers a carrier-class outdoor link with enhanced security and capacity as well as top QoS for data, voice and video services. Enhanced uplink/downlink configuration offers better support of business applications including public safety and video surveillance.

BreezeACCESS VL supports a wide range of subscriber units, providing an optimized solution for the performance and cost requirements of various markets and customers. It enables operators, municipalities, enterprises and communities around the world to quickly and cost-effectively benefit from an array of top quality broadband services.



Unit	Unit Type	Feature Highlights	Deployment Options	Benefits
AU (Access Unit)	Chassis-based base station 	<ul style="list-style-type: none"> Carrier grade chassis 1 to 6 sectors per chassis Outdoor unit (ODU) for each sector Mix and match support for different bands Optional redundant power supply Total net capacity > 192 Mbps (32 x 6 sectors) 	<p>Multi-sector: AUS–BS</p> <ul style="list-style-type: none"> Entry level price Supports up to 25 SUs per sector Upgradable to full AU-BS <hr/> <p>Multi-sector: AU-BS</p> <ul style="list-style-type: none"> Supports up to 512 SUs per sector 	<ul style="list-style-type: none"> Pay-as-you-grow support Optimized configuration for vertical applications Supports any SU model in the same sector Superior NLOS performance for public safety applications in urban deployments
	Standalone base station 	<ul style="list-style-type: none"> Single sector AU comprised of an indoor unit (IDU) and outdoor unit (ODU) Optional all-outdoor or DC solution 	<p>Single-sector: AUS–SA</p> <ul style="list-style-type: none"> Entry level price Supports up to 25 SUs per sector Upgradable to full AU-SA <hr/> <p>Single-sector: AU-SA</p> <ul style="list-style-type: none"> Supports up to 512 SUs per sector 	
SU (Subscriber Unit) Comprised of an indoor unit (IDU) and outdoor unit (ODU). The IDU connects to the network via a standard Ethernet 10/100BaseT (RJ-45) interface and to the ODU via a CAT-5 cable.	SU-31, SU-6, SU-54 	<ul style="list-style-type: none"> Net aggregated throughput: <ul style="list-style-type: none"> SU-3: 3 Mbps SU-6: 6 Mbps SU-54: 32 Mbps Different part numbers for each frequency (0.9, 4.9, 5.2, 5.3, 5.4, 5.8 GHz) Quick installation using LEDs for fast alignment Supports 2 different services per SU (2 priority levels) Coverage range of up to 30 km (LOS) 	<p>Data, voice and video applications</p> <ul style="list-style-type: none"> Extended range Pay-as-you-grow upgrade options: <ul style="list-style-type: none"> SU-3 SU6 SU-3 SU82 SU-6 SU-Video SU-6 SU54 SU-Video SU-54 	<ul style="list-style-type: none"> Pay-as-you-grow support Optimized configuration for vertical applications Supports any SU model in the same sector
	SU-Lite 	<ul style="list-style-type: none"> Net aggregated throughput: <ul style="list-style-type: none"> SU-3L: 3 Mbps SU-6L: 6 Mbps SU-12L: 12 Mbps Single part number for the entire 5 GHz band Coverage range of up to 12 km (FCC LOS) 	<ul style="list-style-type: none"> Primarily residential data and voice applications Pay-as-you-grow upgrade options: <ul style="list-style-type: none"> SU-3L SU-6L SU-6L SU-12L 	<ul style="list-style-type: none"> Cost-effective solution for residential markets All VL-SU models can be deployed in the same sector Extended coverage over the entire 5 GHz band
	SU-Video 	<ul style="list-style-type: none"> Fixed asymmetric throughput: 8 Mbps uplink and 12 Mbps downlink Available in 5.4 GHz and 5.8 GHz Quick installation using LEDs for fast alignment Supports 2 different services per SU (2 priority levels) Coverage range of up to 30 km (LOS) 		<ul style="list-style-type: none"> Optimized bandwidth support for video applications

Star Management Suite

- All AUs and SUs are managed by AlvariStar NMS and AlvariCraft configuration tool
- All AU types are interoperable with all SU types
- All SU types can be deployed in the same sector

1. In VL900 - SU3 only
2. Only in VL900

System Advantages

- **Powerful Access:** Proven robust system enabling best-of-class service delivery, including long range and high-capacity service. The Access Unit (AU) automatically selects algorithm for best possible service, rapid antenna alignment and SLA enforcement.
- **Quality Connectivity:** Optimized bandwidth allocation, including over-the-air and traffic prioritization, to best fit the needs of a wide variety of applications such as data, voice and video streaming and to provide cost-effective quality connectivity.
- **Flexibility:** Subscriber units can be located exactly where required and transferred when necessary, since the system is free of wired infrastructure restraints and ensures full tactical communications in every possible configuration.
- **Quick Installation:** Subscriber units can be easily deployed using the SNR alignment LED bar, enabling operators to minimize OPEX and expedite deployment rate.
- **Compelling Business Case:** Helps reduce CAPEX and OPEX by supporting maximized efficiency and the need for less equipment with scalable pay-as-you-grow support.
- **Maximizes Modularity:** Near/NLOS support, high bandwidth capacity, increased coverage, multi-subscriber profiles in same sector and network.
- **Reliability and Availability:** Ruggedized, carrier-class outdoor solution operating over an extended temperature range.
- **Security:** Built-in encryption and a host of secure management and authentication functions.
- **Complete Offering:** Seamless integration with BreezeACCESS Wi2 for urban WiFi services.

The BreezeACCESS VL Product Range



Specifications

Radio

Frequency

902-927 MHz, 4.9-5.1 GHz,
5.15-5.35 GHz, 5.47-5.725 GHz,
5.725-5.875 GHz
5.15-5.875 GHz (SU-L)

Radio access method

Time Division Duplex TDD

Channel

AU/SU: 5 MHz (900 MHz), 10 MHz,
20 MHz
SU-L: 20 MHz, 10 MHz

Central frequency resolution

1 MHz (900 MHz), 5 MHz, 10 MHz

Max input power (at ant. port)

-48 dBm typical

Max output power (at antenna port)

AU: -10 dBm to 21 dBm, 1 dB steps
AU (900 MHz): -10 dBm to 27 dBm,
1 dB steps

SU: -10 dBm to 21 dBm,
automatically adjusted by ATPC
SU (900 MHz): -10 dBm to 27 dBm,
automatically adjusted by ATPC
SU-L: -9 dBm to 18 dBm, 3 dB steps
(Wall/pole mount with tilting
option)

Modulation scheme (adaptive)

OFDM: BPSK, QPSK, QAM 16,
QAM 64

Antenna port (AU-E)

N-Type 50 ohm

Subscriber integrated antenna

20 dBi (19 dBi in 4.9-5.1 GHz band),
14° H/V, integrated flat panel
17 dBi, 24°AZ x 18°EL, integrated flat
panel (SU-L)

AU antennas

60°: 16dBi, sector 60° vertical
90°: 16dBi, sector 90° vertical
120°: 15dBi, sector 120° vertical,
360°: 8dBi, Omni horizontal

Headquarters

International Corporate HQ
corporate-sales@alvarion.com

North America HQ
n.america-sales@alvarion.com

Sales Contacts

Australia:
anz-sales@alvarion.com

Asia Pacific:
ap-sales@alvarion.com

Brazil:
brazil-sales@alvarion.com

Canada:
canada-sales@alvarion.com

Caribbean:
caribbean-sales@alvarion.com

China:
cn-sales@alvarion.com

Czech Republic:
czech-sales@alvarion.com

France:
france-sales@alvarion.com

Germany:
germany-sales@alvarion.com

Italy:
italy-sales@alvarion.com

Ireland:
uk-sales@alvarion.com

Japan:
jp-sales@alvarion.com

Latin America:
lasales@alvarion.com

Mexico:
mexico-sales@alvarion.com

Nigeria:
nigeria-sales@alvarion.com

Philippines:
ph-sales@alvarion.com

Poland:
poland-sales@alvarion.com

Portugal:
sales-portugal@alvarion.com

Romania:
romania-sales@alvarion.com

Russia:
info@alvarion.ru

Singapore:
asean-sales@alvarion.com

South Africa:
africa-sales@alvarion.com

Spain:
spain-sales@alvarion.com

U.K.:
uk-sales@alvarion.com

Uruguay:
uruguay-sales@alvarion.com

For the latest contact information
in your area, please visit:
www.alvarion.com



© Copyright 2011 Alvarion Ltd. All rights reserved.
Alvarion® its logo and all names, product and service
names referenced herein are either registered trademarks,
trademarks, tradenames or service marks of Alvarion Ltd. in
certain jurisdictions.
All other names are or may be the trademarks of their
respective owners. The content herein is subject to change
without further notice.
Any purchase orders submitted and actual supply of products
and/or grant of licenses are subject to Alvarion's General
Term and Conditions and/or any other effective agreement
between the parties.

213544 rev.u

Specifications (Continued)

Electrical Characteristics

Power consumption

SU/ AU-SA:	25W
AU-BS:	30W (module plus outdoor unit)
SU-L:	Typical 10W, maximum 40W
BS-PS-AC-VL (AC power supply):	240W, full chassis (1PS, 6 AU)
BS-PS-DC-VL (DC power supply):	240W, full chassis (1PS, 6 AU)

Input power

SU / AU-SA:	AC input 100-240 VAC, 50-60 Hz
AU-BS:	AC input 100-240 VAC, 50-60 Hz
SU-L:	AC Input 85-265 VAC, 50-60 Hz DC output 55 VDC, 1A MAX 54 VDC from indoor to outdoor 3.3 VDC, 54V from power supply in backplane
BS-PS-AC-VL (AC power supply):	AC input 85-265 VAC, 47-65 Hz DC output 54V, 3.3V
BS-PS-DC-VL (DC power supply):	DC input -48 VDC nominal (-34 to -72), 10 A max. DC output 54V, 3.3V

Connectors

ODU

SU / AU-SA:
Ethernet: 10/100BaseT RJ-45
Radio: 10/100BaseT Ethernet RJ-45
AC IN: 10/100BaseT Ethernet RJ-45

SU-L:

Ethernet: 10/100 BaseT RJ-45
Radio: 10/100 BaseT Ethernet RJ-45
AC IN: 3-pin AC power plug

AU-BS:

Ethernet: sealing assembly
Radio: 10/100BaseT Ethernet RJ-45

IDU

SU / SU-L / AU-SA:
Indoor: 3-pin AC power plug
10/100Base RJ-45 (waterproof)

AU-BS:

BS-PS-AC-VL (AC power supply):
AC IN: 3-pin power plug
BS-PS-DC-VL (DC power supply):
-48 VDC: 3-pin DC D-Type 3 power
pin plug Amphenol

Physical and Environmental

Dimensions

SU ODU with integrated antenna:	30.5 x 30.5 x 6.2 cm (0.55 kg) / 12 x 12 x 2.4 in (1.21 lb)
SU ODU without integrated antenna:	30.6 x 12 x 4.7 cm (1.85 kg) / 12 x 4.7 x 1.8 in (4.07 lb)
SU-L outdoor unit:	195 x 190 x 74 mm (1.47 kg) / 7.6 x 7.4 x 2.9 in (3.24 lb)
SU-L indoor unit:	140 x 66 x 35 mm (0.3 kg) / 5.5 x 2.6 x 1.3 in (0.66 lb)

Operating temperature

SU/AU outdoor units:	-40°C to 55°C
SU/AU indoor units:	0°C to 40°C
SU-L outdoor unit:	-40°C to 55°C
SU-L indoor unit:	0°C to 40°C

Operating humidity

SU/AU outdoor units:	5%-95% non condensing, weather protected
SU/AU indoor units:	5%-95% non condensing
SU-L outdoor unit:	Maximum 95% non condensing

Standard Compliance

EMC

FCC Part 15 class B, EN55022 class B,
EN 301 489-1/4

Safety

EN 60950-1, UL 60950-1

Environmental

EN 300 019 part 2-3 class 3.2E for
indoor units
EN 300 019 part 2-4 class 4.1E for
outdoor units IP-65, SU integral
antenna IP-65

Storage

EN 300 019-2-1 class 1.2E

Hazardous substances

RoHS compliant

Transportation

EN 300 019-2-2 class 2.3

Lightning protection

EN 61000-4-5, class 3 (2kV)

Radio

EN 301 893 (V 1.5.1)
EN 302 502 (V 1.2.1)
FCC part 15, FCC P.90,
IC RSS-210 (Canada)

Configuration and Management

Local and remote management

Monitor via Telnet, SNMP and
configuration upload/download
Web and SSH V2 (only in SU-L)

Remote management access

From wired LAN, wireless link

Management access protection

Multilevel password
Configuration of remote direction
(from Ethernet only, wireless only,
or both sides)
Configuration of IP addresses of
authorized stations

Software upgrade

Via TFTP and FTP

Configuration up/download

Via TFTP and FTP

SNMP agents

SNMP v1 client, MIB II, Bridge MIB,
Private BreezeACCESS VL MIB

Data Communications

VLAN and QoS support

QinQ 802.1ad¹, 802.1Q
WLP over the air traffic prioritization
MIR/CIR per SU per direction (UL/DL)
Concatenation, burst mode, small
packet optimization to support voice
Advanced Automatic Transmit Power
Control (ATPC)

Traffic prioritization

Layer 2: Based on IEEE 802.1p
Layer 3: IP ToS according to RFC791
and DSCP according to RFC2474
Layer 4: UDP/TCP port range

Security

WEP 128-bit authentication, AES 128,
WEP 128, certified built-in encryption
FIPS-197 mode and FIPS-140-2^{1,2}

Note: Not all options are available in all regions and some features require software
licensing key. Please contact your local representative for further information.

1. Not supported currently in SU-L
2. Certification in future release

About Alvarion

Alvarion (NASDAQ:ALVR) is a global 4G communications leader with the industry's most extensive customer base, including hundreds of commercial 4G deployments. Alvarion's industry leading network solutions for broadband wireless technologies WiMAX, TD-LTE and WiFi, enable broadband applications for service providers and enterprises covering a variety of industries such as mobile broadband, residential and business broadband, utilities, municipalities and public safety agencies. Through an open network strategy, superior IP and OFDMA know-how, and ability to deploy large scale end-to-end turnkey networks, Alvarion is delivering the true 4G broadband experience today (www.alvarion.com).