

## TP-1610 16 E1/T1 cPCI VoIP Communication Board



- High channel density
- Concurrent toll quality voice and fax support
- Carrier grade applications
- Reduced system cost and increased reliability
- Fast time-to-market
- Flexible and easy migration to VoIP Networks
- Extensive VoIP experience

The **TP-1610** cPCI VoIP communication board, based on dual AudioCodes' TPM-1100 PMC Modules, is an ideal building block for deploying high-density, high-availability Voice over IP (VoIP) systems. The TP-1610 is suitable for VoIP gateways, IP-enabled call centers, large Telcos and next generation DLCs. Offering integrated voice gateway functionality capable of delivering up to 480 simultaneous calls, the TP-1610 supports all necessary functions for voice and fax streaming over IP networks.

### DELIVER FEATURE-RICH SOLUTIONS

The TP-1610 supports a broad selection of voice processing related algorithms, including G.711, G.723.1 and G.729AB Vocoders, G.168-compliant echo cancellation, T.38 real-time Fax over IP, and a wide selection of In-band and Out-band tone detection and generation. In addition, signaling protocols supported include ISDN PRI, SIGTRAN (M2UA, M3UA, IUA) and CAS.

### COMPLY WITH INDUSTRY STANDARDS

The TP-1610 board complies with industry standard network control protocols including MGCP, MEGACO (H.248), SIP, H.323 as well as AudioCodes' proprietary TPNC. These allow for the implementation of a distributed gateway architecture that separates call processing functions from media streaming functions, resulting in better redundancy, scalability and higher system availability.

### PROTECT CUSTOMER INVESTMENT

The TP-1610 is based on the VolPerfect™ architecture, AudioCodes' underlying, best-of-breed, core media gateway technology for all of its products. The TP-1610 supports AudioCodes' API, which enables software download, provisioning and control. It was designed to maintain essential API backward compatibility in order to protect customers' investment in the development of products based on former generations.

### ENABLE FAST & EASY INTEGRATION

Enabling accelerated design cycles with high density and reduced costs, the TP-1610 is an ideal building block for scalable, reliable VoIP solutions. With the TP-1610's comprehensive feature set, customers can quickly design a wide range of solutions for migration to VoIP networks.

### TP-1610 FEATURES

- Up to 480 voice/fax independent multiple LBR channels
- VoIP packet streaming (RTP/RTCP) per RFC 3550/3551
- Standard control: MGCP (RFC 2705), MEGACO (H.248), SIP/H.323
- Real-time Fax over IP/T.38
- On-board announcement support towards PSTN/TDM and IP
- Tone detection and generation (MF, DTMF, RFC 2833)
- PSTN Signaling: CAS, ISDN PRI, V5.2 (AN), and SS7
- SIGTRAN IUA, M2UA, M3UA over SCTP
- cPSB PICMG 2.16 compliant Ethernet on the backplane

# AudioCodes Enabling Technology Products

## TP-1610

### SPECIFICATIONS

Software Specifications	
Capacity	60, 120, 240 or 480 independent digital voice, fax and data ports
Voice Compression	G.711, G.723.1, G.729A/B, G.726/G.727, NetCoder® MS-GSM, GSM-FR Additional coders supported – contact AudioCodes for further information
Echo Cancellation	G.168 compliant 32, 64*, 128* msec echo tail
Gain Control	Programmable
Fax Relay	Real-time fax over IP/T.38 compliant, automatic fallback to G.711 and VBD for up to super G-3 fax machines
ASR - 3 <sup>rd</sup> party	Host-based Architecture – Media Stream over PCI
Recognition Engines	Distributed Architecture – Media Stream over VoIP RTP
In-band/Out-band Signaling	Packet side or PSTN side, DTMF and tone detection and generation
IVR Support	On-board announcement storage – 10 Mb Recorded prompts – 20 minutes of G.711, 200 minutes of G.723
VoIP Standards Compliance	RTP/RTCP per RFC 3550/3551 DTMF over RTP per RFC 2833
Control Protocols	Media Gateway on a blade mode: <ul style="list-style-type: none"><li>• Controlled by either MGCP or MEGACO</li><li>• PCI used for power only</li></ul> SIP, H.323 TPNCP – AudioCodes' proprietary VoIP API Library
Management Interfaces	SNMP V2v: Standard MIB-2, RTP MIB, DS1 MIB, AudioCodes proprietary MIB On-board Embedded Web Server
Operating System	• Windows™ 2000, XP, 2003 • Linux™ • Solaris™ on Intel™/Sparc™
Signaling	
PSTN	<b>CAS</b> T1 robbed bit, MFC/R2 numerous country variants <b>CCS</b> ISDN PRI: numerous country variants including ETSI EURO ISDN, ANSI NI2, DMS, 5ESS, Japan INS1500 V5.2 AN (Contact AudioCodes)
SIGTRAN	IUA over SCTP per RFC 3057/2960 SS7 MTP2 link termination M2UA and M3UA over SCTP
Hardware Specifications	
Ethernet	Dual redundant 100 BASE-T ports
Hot Swap	Full hot swap supported per PICMG 2.1
Physical Interfaces	Form factor – 6U PICMG 2.0 single cPCI slot TDM Interface – H.110 CT Bus Telephony – two 50-pin Telco connectors on rear panel Ethernet – cPSB PICMG 2.16 on the backplane, Dual RJ-45 on rear panel
Power	40.7W, 3A at 5V, 7.8A at 3.3V

\* With reduced channel capacity

### APPLICATIONS

- Next Generation Switches
- IP Services Platforms
- VoIP Access Gateways
- Trunking Gateways
- Cable Telephony Gateways
- IP Enabled Contact Centers

### ABOUT AUDIOCODES

AudioCodes Ltd. (NASDAQ: AUDC) enables the new voice infrastructure by providing innovative, reliable and cost-effective Voice over Packet technology and Voice Network products to OEMs, network equipment providers and system integrators. AudioCodes provides its customers and partners with a diverse range of flexible, comprehensive media gateway and media processing technologies, based on VoIPerfect™ – AudioCodes' underlying, best-of-breed, core media gateway architecture. The company is a market leader in voice compression technology and is a key originator of the ITU G.723.1 standard for the emerging Voice over IP market. AudioCodes voice network products feature media gateway and media server platforms for packet-based applications in the converged, wireline, wireless, broadband access, and enhanced voice services markets. AudioCodes enabling technology products include VoIP and CTI communication boards, VoIP media gateway processors and modules, and CPE devices. AudioCodes' headquarters and R&D facilities are located in Israel with an R&D extension in the U.S. Other AudioCodes' offices are located in Europe, the Far East, and Latin America.

#### International Headquarters

1 Hayarden Street, Airport City  
Lod, Israel 70151  
Tel: +972-3-976-4000  
Fax: +972-3-976-4040

#### US Headquarters

2099 Gateway Place, Suite 500  
San Jose, CA 95110  
Tel: +1-408-441-1175  
Fax: +1-408-451-9520

**info@audiocodes.com**  
**www.audiocodes.com**

© 2005 AudioCodes Ltd. All rights reserved. AC, Ardito, AudioCodes, AudioCodes logo, AudioCoded, IPmedia, Mediant, MediaPack, MP-MLQ, NetCoder, Stretto, TrunkPack, VoicePacketizer and VoIPerfect are trademarks or registered trademarks of AudioCodes Ltd. All other marks are the property of their respective owners. The information and specifications in this document and the product(s) are subject to change without notice.

Ref # LTRT-00220 08/05 V.7

