

# C3255

## Checkweigher



NTEP CC 04-088

- **Capacity**– 30 lb (15 kg), 60 lb (30 kg), 150 lb (60 kg), 300 lb (150 kg)
- **Stainless Steel Construction**– Wipe-down environment friendly
- **LCD Display**– Bright, large and visible
- **Power Options**– Battery and AC power
- **Preset Targets**– Includes 10 preset
- **Checkweighing Features**– Checkweighing bar graph, push button target setting, simple weight display, over/under/accept indicators, and audible alarm for target
- **Approvals**– NTEP

VALUE IN  
WEIGHING

# C3255 Checkweigher

## Features

**Display Type**– 7 segment LCD with annunciators and bar graph. Large 1.2" digits.

**Battery Operation**– Uses 6 “C” cell batteries (not included) allowing remote operation and portability. The battery supports over 120 hours of continuous operation.

**Ten Preset Targets**– Allows quick selection of the items to be weighed. Setting new targets is quick and simple via the keyboard.

**Unit Switching**– Accessed through the “mode” key. Either lbs, kg or oz may be selected.

**Count Function**– A simple and accurate feature is available under the “mode” switch

**Target Graph**– In the checkweigher mode the graph indicates over, under or accept with a full visual representation of the weight in relation to the target

**Folding Column**– The display unit folds down for storage and shipping

**Selectable Calibration Settings**– Choose from full, 1/2, and 1/4 capacity

**Key Functions**– On/off, mode, net/gross, zero, tare, call, 0-9

## Specifications

### Capacity / Resolution (NTEP)

nmax	lb	nmax	kg	nmax	oz
6000	12 x 0.002 lb	6000	6 x 0.001 kg	3840	192 x 0.05 oz
6000	30 x 0.005 lb	6000	12 x 0.002 kg	4800	480 x 0.1 oz
6000	60 x 0.01 lb	6000	30 x 0.005 kg	4800	960 x 0.2 oz
6000	120 x 0.02 lb	6000	60 x 0.01 kg	3840	1920 x 0.5 oz
6000	300 x 0.05 lb	6000	120 x 0.02 kg	4800	4800 x 1 oz
3000	15 x 0.005 lb	3000	6 x 0.002 kg	2400	240 x 0.1 oz
3000	30 x 0.01 lb	3000	15 x 0.005 kg	2400	480 x 0.2 oz
3000	60 x 0.02 lb	3000	30 x 0.01 kg	1920	960 x 0.5 oz
3000	150 x 0.05 lb	3000	60 x 0.02 kg	2400	2400 x 1 oz

**Scale Dimensions**– 19" H x 13.5" W x 19.75" D  
483 mm (H) x 343 mm (W) x 502 mm (D)

**Platter Size**– 13.5" W x 17.4" D  
342 mm (W) 442 mm (D)

**Operating Temp**– 41° F - 95° F (5° C - 35° C)

**Power Supply**– 15V, 300mA, AC adapter (included)

**Packaging Dimensions**– 26" L x 20" W x 12" H  
660 mm (L) x 508 mm (W) x 305 mm (H)

**Shipping Weight**– 33 lb (15 kg)

### Certifications–

NTEP CC# 04-088

Full FCC compliance

UL/CUL power adapter



Model C3255 Battery Compartment



a division of Avery Weigh-Tronix, LLC

### Brecknell

1000 Armstrong Dr., Fairmont, MN 56031  
Toll free: 800-637-0529, Tel: 507-238-8702  
Fax: 507-238-8271  
e-mail: sales@brecknellscales.com  
www.brecknellscales.com



### Brecknell

Foundry Lane, Smethwick  
West Midlands B66 2LP UK  
Tel: +44 (0) 845 246 6717  
Fax: +44 (0) 845 246 6718  
Email: sales@brecknellscales.co.uk  
www.brecknellscales.co.uk

