

# PS-USB



## Portable Shipping Scale



- **Capacity—**  
15 kg x 0.005 kg / 30 lb x 0.01 lb  
30 kg x 0.01 kg / 70 lb x 0.02 lb  
60 kg x 0.02 kg / 150 lb x 0.05 lb
- **Units—** kg, lb, lb:oz\* (\*non-NTEP)
- **Display—** 6½ digits 25 mm / 1" high, seven segments LCD with blue backlight
- **Construction—** Heavy duty cast aluminum base with stainless steel platter
- **Power—** 6VDC 500mA adapter with center positive or four AA batteries
- **RS-232 and USB Interface**
- **Emulation Protocols:** Standard NCI default with field configurable settings of NCI, 8213, 3835 and Autosend. Interfaces with software programs such as UPS™ Worldship Online.
- **Platform Dimension—**  
355 mm (W) x 305 mm (L) / 14" W x 12" L
- **Product Dimension—**  
355 (W) x 411 mm (L) x 80 mm (H)  
14" W x 16" L x 3.15" H

# PS-USB Portable Shipping Scale

## Features

PS-USB scales are particularly suited to shipping and warehouse applications and general purpose weighing. These are very affordable scales with high accuracy.

The triple power modes (battery, AC adapter and USB) enable portability or permanent installation.

The PS-USB features RS-232/USB interface that can transmit and receive using a demand type protocol.

Comes with adjustable feet and leveling bubble for precise weighing.



Removable stainless steel platter



Durable cast aluminum upper load cell supporter and cast aluminum base

## Specifications

### Capacity:

15 kg x 0.005 kg / 30 lb x 0.01 lb

30 kg x 0.01 kg / 70 lb x 0.02 lb

60 kg x 0.02 kg / 150 lb x 0.05 lb

### Platform Dimension:

355 mm (W) x 305 mm (L) / 14" W x 12" L

**Product Weight:** 4.8 kg / 10.5 lb

**Display:** 6½ digits 25 mm / 1" high, seven segments LCD with blue backlight

**RS-232/USB:** Bi-directional full duplex (USB and RS-232 cable included)

**Other Functions:** Weighing, counting, check weighing, percent weighing, accumulation

**Keyboard:** Hold/setup, print/func, acc/total, unit/data, tare/preset, on/off/zero

**Units:** kg, lb, lb:oz

### Power:

6VDC 500mA adapter (AWT05-507975 USA - included) with center positive

Four AA batteries (not included)

USB (VCP) cable (included)

### Optional Power Supplies:

AWT05-507841: UK power adapter

AWT05-507842: EU power adapter

**Battery Life:** 20 hours

**Operating Temperature:** -10° C to 40° C / 14° F to 104° F

### Packaging Dimension:

505 mm (L) x 465 mm (W) x 150 mm (H)

20" L x 18" W x 6" H

**Shipping Weight:** 6.3 kg / 14 lb

**Certifications:** CE, WEE directive, UL/CE, BS approved power adapter

### Part Number:

816965006540: 15 kg / 30 lb

816965006533: 30 kg / 70 lb

816965006526: 60 kg / 150 lb



a division of Avery Weigh-Tronix, LLC

### Brecknell

1000 Armstrong Dr., Fairmont, MN 56031  
Toll free: 800-637-0529, Tel: 507-238-8702  
Fax: 507-238-8271  
e-mail: sales@brecknellscales.com  
www.brecknellscales.com



### Brecknell

Foundry Lane, Smethwick  
West Midlands B66 2LP UK  
Tel: +44 (0) 845 246 6717  
Fax: +44 (0) 845 246 6718  
Email: sales@brecknellscales.co.uk  
www.brecknellscales.co.uk

