



## ***Shock, Water and Dust Resistant Enterprise PDA***

***Expansion capabilities via CF Card and  
SDIO slots***




***Large and high resolution VGA LCD for superb  
display clarity***



- ***Withstands a drop from 3.3 feet (1m); IP54 rated for dust and water resistance***
- ***Large 3.7-inch transfective VGA LCD (landscape or portrait mode)***
- ***Standard large capacity battery for up to 27 hours of continuous use***
- ***Compact Flash and SDIO slots for flexible expansion possibilities***
- ***Auto-recovery tool to automatically back up and restore user data in case of accidental data corruption***
- ***Microsoft®Windows Mobile™2003 Second Edition***
- ***Standard large capacity battery without spoiling ease of handling and flat back***



## GENERAL GUIDE / OPTIONS



## SPECIFICATIONS

<b>CPU</b>	Intel®PXA270 Application Processor (Max. 416 MHz)
<b>OS</b>	Microsoft®Windows Mobile™2003 Second Edition Software for Pocket PC
<b>Memory</b>	
<b>RAM</b>	64 MB
<b>F-ROM</b>	64 MB (user area approx. 20MB)
<b>Display</b>	
<b>Type</b>	3.7-inch transfective TFT color LCD 65,536 colors
<b>Resolution</b>	480 x 640 dots
<b>Backlight</b>	LED
<b>Indicator</b>	2-color LED x 2
<b>Input/Switch</b>	
<b>Keyboard</b>	Touchpanel Software keyboard Program keys (x 4), Action key, UP/DOWN keys, Cursor key Power switch, Reset switch, Battery cover lock switches (x 2)
<b>Switch</b>	
<b>Interface</b>	
<b>Infrared</b>	IrDA 1.3 compatible Max. 4 Mbps
<b>Serial</b>	26-pin interface (supports serial RS-232C and USB)
<b>SDIO Slot</b>	SDIO, SD, MMC cards are supported.
<b>CF Slot</b>	CompactFlash card Type I/Type II (3.3V)
<b>Audio</b>	Speaker (monaural), Microphone (monaural), Headphone jack (stereo)

<b>Power</b>	
<b>Operation</b>	Lithium-ion battery pack (HA-C21BAT) 2,300 mAh
<b>Operating period</b>	<b>IT-10M20</b> Approx. 27 hours calculation : display =1:10
<b>Memory backup</b>	NiMH battery (rechargeable) on board
<b>Memory backup period</b>	Approx. 30 minutes. (Assuming NiMH battery is fully charged.)
<b>Environment</b>	
<b>Drop durability</b>	From 1.0 m in height onto concrete floor*
<b>Operating temperature</b>	32°F to 104°F / 0C to +40C
<b>Storage temperature</b>	-4°F to 140°F / -20C to +60C
<b>Operating humidity</b>	10% to 85%RH (no condensation)
<b>Storage humidity</b>	10% to 90%RH (no condensation)
<b>Dust/Water-splash proof</b>	IP54
<b>Dimensions and weight</b>	
<b>Weight</b>	Approx. 10.23 oz / 0.64 lb / 290 g
<b>Dimensions</b>	Approx. 5.51"(D) x 3.15"(W) x 0.98"(H) / 140 (D) x 80 (W) x 25 (H) mm
<b>Application development tool</b>	eMbedded Visual C++ 4.0
<b>Compliance</b>	
<b>Safety</b>	EN60950 (for IT-10M20BR only), UL60950-2000
<b>EMC</b>	EN55022/EN55024, FCC Part 15B
<b>RF type approval</b>	EN300328/EN301489/EN50361/EN50371, FCC Part 15C and SAR, IC RS-210

\* : exclude when a card is installed.

- CASIO is a registered trademark of CASIO Computer Co., Ltd. in Japan.
- Microsoft, Windows and Windows Mobile are registered trademarks and trademark respectively of Microsoft Corporation in the USA and/or other countries.
- The BLUETOOTH registered trademark is owned by Bluetooth SIG, Inc., U.S.A. and licensed to CASIO Computer Co., Ltd.
- Other product names or company names in this catalogue are either trademarks or registered trademarks of their respective owners.
- Displays shown in this catalogue are photographic images.
- This catalogue is current as of December 2004.
- Specifications and designs are subject to change without notice.

**CASIO**  
CASIO INC.