

Advanced Performance Line

Fingerprint keyboards with integrated optical fingerprint sensor and optional smart card reader for quick, easy and secure logon

FTSC technology

Personal ID Keyboard G81-12000/12100



General

These keyboards are equipped with an integrated fingerprint sensor as well as with an optional smart card reader. The smart card offers additional safety functions.

Smart card terminal

- 1 smart card terminal compliant with PC/SC
- Push-pull card reader with springloaded contacts
- MTBF 200,000 read cycles
- Electrical characteristics in accordance with ISO 7816/3 GSM 11.11
- Contact positioning in accordance with ISO 7816/2

Asynchronous protocols T=0, T=1 With GemPC410 also S=8, S=9 and S=10

Fingerprint sensor

- Principle of operation: optical
- Resolution: 250 dpi
- Operating voltage: 5 V ± 5%
- Interface : Parallel port, in EPP mode

Interfaces to the PC

The keyboard cable is equipped with max. 3 connectors

- Keyboard: PS/2 connector
- Smart card reader:9-pin sub-D for RS 232
- Fingerprint reader:
- 25-pin sub-D for parallel port

 Additional connector for printer
 (pass through)

Power Supply

The keyboard, including the integrated equipment, typ. has a current requirement of 180mA. It is supplied through the PS/2 interface. For PCs with a PS/2 port that cannot provide this amount of power, a Cherry Power Pack (see Accessories) can be supplied.

Temperature range: Storage temperature: -20 °C to +60 °C Operating temperature: 0 °C to +50 °C

Dimensions: 12000 series: (L x W x H) 470 x 220 x 62 mm 12100 series: (L x W x H) 470 x 220 x 62 mm



Network logon

Software

BioCard or BioLogon

for operating system logon



Software updates can be found in the internet at: http://www.identix.com

Driver updates can be downloaded from our homepage at: http://support.cherry.de

(1) International layouts

BE	=	Belgian	
СН	=	Swiss	
DE	=	German	
DK	=	Danish	
ES	=	Spanish	
FR	=	French	
GB	=	English (UK)	
EU	=	English (US) with €	
SL	=	SI/HR/YU/BiH	
IT	=	Italian	
NO	=	Norwegian	
SF	=	Swedish/Finnish	
US	=	English (US)	

Other versions available on request.

Stock codes

G 81-12100 LXD ⁽¹⁾	G 81-12100 LXD ⁽¹⁾ Standard without smart card reader + pass through	
G 81-12100 LVD ⁽¹⁾	Standard without smart card reader	Bio Logon
G 81-12000 LWC ⁽¹⁾	Standard smart card reader and pass through	Bio Card + smart card
G 81-12000 LTC ⁽¹⁾	Standard smart card reader	Bio Card + smart card
G 81-12016 LWB ⁽¹⁾	Smart card reader Gemplus Gem PC 410 and pass through	Bio Card + smart card

FCC Part 15
Subpart B
Class B

Other approvals available on request.

68