

FingerTIP ID Keyboard G83-14401 /-14501



G83-14400

Models may vary from the image shown

- USB keyboard with fingerprint sensor and optional PC/SC smart card reader
- Capacitive fingerprint sensor TCS1 from UPEK with TouchChip® technology 256 x 360 pixel
- Smartcard reader CardMan 3121 compatible
- Compatible with UPEK BSAPI 3.6
- Encrypted fingerprint data
- Template on device possible
- Supports Windows Biometric Framework
- Free demo software can be downloaded from:
<http://www.upek.com/support/downloads/windows7/legacy/>

Technical Data

Delivery volume

- 1 FingerTIP ID keyboard
- 1 printed manual
- 1 CD with Smartcard Reader Drivers

Approvals

- FCC, GS, CE, GOST-R, UL, WHQL

System requirements

- USB interface
- Windows XP, XP x64, 2003, 2003 x64, Vista, Vista x64, Windows 7, Windows 7 x64, 2008, 2008 x64, Linux, MAC OS

Technical Data

- **Number of buttons:**
104 = International layout with Windows™ keys
- **Cable length:**
approx. 1.75 m
approx. 5.74 ft
- **Weight:**
approx. 1190 g (keyboard)
approx. 2.62 lbs (keyboard)
approx. 1500 g (with packaging)
approx. 3.30 lbs (with packaging)
- **Dimensions:**
approx. 455 x 195 x 54 mm (keyboard)
approx. 17.9' x 7.68' x 2.13' inches (keyboard)
approx. 493 x 255 x 59 mm (with packaging)
approx. 19.4' x 10' x 2.32' inches (with packaging)
- **Current consumption:**
max 150 mA
- **Interface:**
USB, bus powered
- **Smart card interface:**
 - Reads and writes all ISO 7816 cards
 - Supports T=0, T=1, I²C (S=8), 2-wire (S=10), 3-wire (S=9)
- **Smart card speed:**
412,903 bps
- **Clock frequency smart card:**
4.8 MHz
- **Card connection unit:**
Approx. 100,000 insertions
- **Sensor resolution:**
508 dpi
- **Operating life of individual keys:**
> 20 million operations
- **Storage temperature:**
-20°C to 60°C
-4°F to 140°F
- **Operating temperature:**
0°C to 50°C
32°F to 122°F

Technical Data

- **Packaging units:**
40 keyboards per master carton
2 master cartons per pallet

- **Warranty:**
2 years

Models:

Order number	Housing color	Smartcard Reader
G83-14401LPBEU-2	Black	Yes
G83-14501LPBEU-2	Black	No

(Possible color and country/layouts versions available on request)



G83-14501



G83-14401

Models may vary from the Image shown

ZF Electronics Corporation
11200 88th Avenue
Pleasant Prairie, WI 53158
USA
Phone: 262.942.6500
Internet: www.cherrycorp.com

Sales: 262.942.6562
E-Mail: CEP_sales@zf.com
Fax: 262.942.6566

The manufacturer accepts no liability for errors or non-availability, and reserves the right to change specifications without prior notice. Technical data relates to product specifications only. Features may differ from those described. Only drawings combined with product specifications shall be deemed binding.

© 2008 ZF Electronics Corporation, Last update: September 23, 2010_V02

