

# 1600 series

## Pocket-Size Scanner



		1660	1661	1664
RF Communication	Module	Bluetooth® Class 3 ( 2.4 GHz ) Version 2.0		Bluetooth® Class 2 ( 2.4 GHz ) Version 2.1 +EDR
	Coverage	10 m / 33 ft. line of sight		20 m / 66 ft. line of sight
	Standard profile	SPP, HID		
Performance	Category	Bluetooth® linear imager scanner		Bluetooth® 2D imager scanner
	Optical sensor	2500 pixels		752 x 480 pixels
	Light source	Red LED 625 nm		625 ± 5 nm LEDs ( 2x )
	Resolution	3 mil		3 mil - 1D barcode / 5 mil - 2D barcode
	Depth of field ( depends on barcode resolution )	3.5 to 38 cm / 1.4 to 15 in.		Code 39 3 mil : 6.9 to 10.7 cm / 2.7 to 4.2 in. Code 39 5 mil : 3.6 to 18.5 cm / 1.4 to 7.3 in. UPCA 13 mil : 4.0 to 30.5 cm / 1.6 to 12 in. PDF417 5 mil : 7.1 to 11.4 cm / 2.8 to 4.5 in. PDF417 6.67 mil : 4.8 to 17.5 cm / 1.9 to 6.9 in.
	Scanning angle	Pitch ± 70° Skew ± 70°		Pitch ± 60° Skew ± 60°
	PCS	Minimum 30%		
	Scan rate	100 scans / second		60 scans / second
	Barcodes supported	Codabar, Code 39, Code 93, Code 128, GS1 DataBar ( RSS ), Industrial 2 of 5, Interleave 2 of 5, ISBT-128, Italian and French Pharmacodes., Matrix 2 of 5, MSI, Plessey, Telepen, UPC-A, UPC-E, EAN-8, EAN-13, GS1-128 ( EAN-128 )		1D: All major codes* <sup>1</sup> 2D: PDF417, MicroPDF417, Composite, RSS, TLC-39, Datamatrix, QR code, Micro QR code, Aztec, MaxiCode Postal Codes: US PostNet, US Planet, UK Postal, Australian Postal, Japan Postal Dutch Postal ( KIX )
	Programmable features	Data editing, interface selection, symbology configuration		
Language support	US and UK English, French, Italian, Belgian, Norwegian, Swedish, Spanish, Portuguese, German, Japanese, Turkish and Hungarian			
Physical	Weight ( including battery )	50 g / 1.76 oz.	69 g / 2.43 oz.	106 g / 3.7 oz.
	Size LxWxH	9.5 x 3.5 x 2 cm / 3.7 x 1.4 x 0.8 in.		11.3 x 4.5 x 3.0 cm / 4.4 x 1.8 x 1.2 in.
	Color	Grey		Black
	Button	Power and scan keys		
	Memory	256 K	512 K	4 MB
Electrical	Working hours	30 hours based on 1 scan / 5 seconds	40 hours based on 1 scan / 5 seconds	24 hours based on 1 scan / 5 seconds
	Power Supply	Two AAA batteries		Li-ion 3.7V, 850 mAh
	Power consumption Standby / Operating	15 mA / 245 mA @ 3V	17 mA / 190 mA @3.7V	20 mA / 180 mA @ 3.7V
User Environment	Temperature	Operating : 0 °C to 50°C / 32°F to 122°F / Storage : -20°C to 60°C / -4°F to 140°F( w/o battery )		
	Humidity ( non-condensing )	Operating : 10% to 90% / Storage: 5% to 95%		
	Impact resistance	--	0.9 m / 3.0 ft. multiple drops onto concrete	1.5 m / 4.9 ft. multiple drops onto concrete
	Ingress protection	--		IP42
	Electrostatic discharge	± 8 kV contact / ± 15 kV air		
EMC regulation	BSMI, CE, C-tick, FCC, NCC, IC, TELEC, SRMC, KC		BSMI, CE, C-tick, FCC, NCC, IC, TELEC, SRMC	
Configuration	Setup option includes Windows®- based ScanMaster software			
Accessories	3610 Bluetooth® transponder, protective cover		3610 Bluetooth® transponder, Micro USB cable, battery charger, protective cover	
Warranty	1 year			

1. All of the barcodes that 1600 series 1D scanner can read except French Pharmacode, Plessey, and Telepen.

ACCESSORIES



3610 Bluetooth® Transponder



Battery Charger



1600H



3610H

Antimicrobial Protection Series



**HEADQUARTERS**  
CipherLab Co., Ltd.  
12F, 333 Dunhua S. Rd., Sec.2  
Taipei, Taiwan 10669  
Tel +886 2 8647 1166  
Fax +886 2 8732 3300  
www.cipherlab.com

**CipherLab China**  
J Room, 4F, No.728 West Yan'an  
Road, Changning District, Shanghai  
China 200050  
Tel +86 21 3368 0288  
Fax +86 21 3368 0286

**CipherLab USA**  
2552 Summit Avenue  
Plano, Texas USA 75074  
Tel +1 469 241 9779  
Toll Free 888 300 9779  
Fax +1 469 241 0697

**CipherLab Central Europe**  
Willicher Damm 145  
41066 Mönchengladbach  
Germany  
Tel +49 2161 56230 0  
Fax +49 2161 56230 22