




computing without boundaries



## DLI 8300 rugged tablet

field service • fleet management  
first responders • retail  
warehouse & logistics



Intel® Atom processor

8.4" outdoor screen

barcode scanner

mobile payment

color camera

GPS, WLAN, WWAN, WPAN



The DLI 8300 rugged tablet is the ideal rugged device for use in a wide variety of industrial and harsh environment applications including:

- Field Service - dispatch operations, route planning, work order management
- Mobile Payment - in-home repairs, up-sells, extended warranties & services
- First Responders - command and control, CAD, e-ticketing, and evidence gathering
- Fleet Management - asset tracking, geofencing, delivery verification & signature capture, real-time vehicle diagnostics

**In the field. On the road.  
At the jobsite or in the office.  
Everywhere business gets done.**

**As feature-rich as it is rugged, the DLI 8300 fits perfectly into any mobile computing environment.** Thanks to its long list of integrated features, the DLI 8300 Rugged Tablet shatters the boundaries between hand held and vehicle mounted devices by combining a compact, ergonomic design with a level of functionality previously unavailable in a rugged tablet.

Built around an industrial-class Intel® Atom processor, an 8.4" outdoor readable touchscreen (optional), and housed in an impact-resistant IP54 sealed casing, the DLI 8300 is rugged to its core. Equally at home in field service, logistics, transportation, and public safety environments, the 8300 was designed with productivity in mind. Multiple, integrated communication options including cellular, WiFi, Bluetooth, and GPS, as well as a wide variety of input and capture options including an integrated imager, on-board RFID, magstripe, color camera, and integrated biometric reader round out the DLI 8300's expansive feature set.

Adding to the DLI 8300's long list of innovative features is a revolutionary JBus interface, allowing the device to operate as a vehicle diagnostics tool in addition to its core mobile computing and wireless communications functionality. Give DLI a call today at (800) 526-1299 for more information.



www.dataitd.com



dust



water



drop



vibration

extreme  
temps

wireless

**Intel® Atom processor • 8.4" indoor/outdoor touchscreen**  
**Barcode scanner • Mobile Payment • Biometrics • VoIP**  
**GPS • Color Camera • WLAN, WWAN, WPAN**

## System

- **Casing** - Impact-resistant ABS+PC polymer, IP54 rated, multiple 4ft drops to bare concrete
- **Processor** - Intel® Atom Industrial Version Z530 1.60Ghz
- **Chipset** - Intel® System Controller Hub US15W, L2 Cache: 512KB, FSB: 533Mhz
- **Display** - 8.4 inch, 350 NIT indoor/outdoor readable, 600 x 800 or 1024 x 768 resolution, Contrast Ratio: 400:1
- **Touchscreen** - Digitizer or Resistive (standard or polarized), Industrial rated @ 3 million touches in a single location
- **Video** - 256MB RAM
- **Audio** - Intel High Definition Audio; dual integrated speakers  
- Integrated microphone, 3.5mm mic/headset jack
- **Memory** - 2GB DDR2 SODIMM 533Mhz
- **Storage** - HDD: 1.8" 60GB or 80GB Shock Mounted  
- SSD: 8GB, 16GB, 32GB, 64MB Industrial
- **Operating System** - Vista® Business, XP® Pro, XP® Tablet, Windows® Embedded Standard, Windows® 7, Linux 2.6 (Ubuntu)
- **Ports** - (2) USB 2.0, (1) RS232 (optional), (2) RF pass-thru, (1) Ethernet  
- all ports IP67 rated w/ sealed locking connectors
- **Keys** - (6) user-programmable
- **Biometric** - Access Control / Mouse Function
- **Barcode scanner** - Integrated Adaptus® Imager JPOS-Compliant (optional) or Motorola® Lorax Auto Ranging Scanner (optional)
- **RFID** - integrated 13.56 MHz ISO 14443 A&B, ISO 15693 reader (optional)
- **3-in-1 Module** - Mini Magstripe, 13.56Mhz RFID reader and Adaptus® Imager, (optional module)
- **Smart Card Reader** - Integrated PCMCIA Type II slot with On-board Flash, ISO 7816 Class A and AB smart card compatible (optional)

*Information in this document is subject to change without notice.*

## Environmental

- **Temperature** - Operating -4°F to +140°F (-20°C to 60°C)  
- Storage -7°F to 149°F (-22°C to 65°C)
- **Impact** - Multiple 4ft drops to bare concrete
- **Vibration** - 5~500Hz 1G PTP, MIL STD. 810F 514.5C-3 Highway truck vibration exposure
- **Shock** - Operating - 20G (11ms), Non Operating - 40G (11ms), Crash - 75G (11ms)
- **EMI/EMC** - FCC Class B, CE
- **Water/Dust** - IP54, Dust - limited ingress, Water - Protected against sprays from all directions - limited ingress permitted

## Physical

- **Dimensions** - H - 9.5" (241mm), W - 10.23" (259mm), D - 1.83" (46mm)
- **Weight** - 3.7 lbs. (with 2 batteries)
- **Warranty** - Standard One Year. Available No-Fault Service Coverage
- **GPS** - SiRFstarIII chipset with Internal Geohelix Antenna (optional)  
- External Antenna (optional)
- **Camera** - Color 2 Mega Pixel, Autofocus, UVC Compliant (optional)
- **WiFi** - 802.11b/g Wifi Radio (Cisco CCX 5) Standard  
- 802.11a/g/b/n Wifi Radio (Cisco CCX 5) (Optional)
- **WWAN** - (2) User-accessible, sealed PCMCIA cellular card slots including support for external antenna; Cellular carriers include Verizon®, Sprint®, AT&T/Cingular®, T-Mobile®
- **Bluetooth** - Class 2 radio (optional)
- **Voice Communications** - VoIP, Integrated microphone; Integrated 2.5mm headset/mic jack, Bluetooth® headset/mic (optional)
- **Power** - Battery Packs: Internal 1950mAh Lithium Ion Battery, External 2600mAh Lithium Ion Battery (5~6Hrs) of usage. \*Depending on configuration and application.

## Accessories

- **Vehicle Cradle** - Secure locking mechanism w/configurable port replicator, (3) RS232, (3) USB port, (1) 10/100 Ethernet port, External cellular and GPS antenna passive connection; J1708 / J1939, CANbus; Optional 10v~60v DC integrated Power Regulating Converter
- Desktop cradle w/built-in battery charger; Ruggedized Vinyl carrying case; 3-bay battery charger (toaster); 3 battery charging "spider" cable; Cigarette Lighter Power Adapter, Handle, Handstrap



Schedule  
Contract GS-35f-0219V



## computing without boundaries

shipping: 703 data ltd parkway laporte, indiana 46350 • mail: p.o. box 761 laporte, indiana 46352  
toll free: 800.526.1299 • fax: 219.362.1937 • [www.data ltd.com](http://www.data ltd.com)