

## LP3™

### High-Volume Portable Label Printer

The LP3™ is a 76.2 mm (3 in) direct thermal portable label printer that delivers greater paper capacity, long battery life and a range of wireless connectivity options for the retail and manufacturing marketplace. And of course, it packs the legendary reliability Datamax-O'Neil by Honeywell is known for across the globe – ensuring your operation runs smoothly.

LP3 prints 25.4 mm (1 in) to 76.2 mm (3 in) labels and can accommodate a wide variety of labels and paper, including the heavy stock necessary for hang tags and specialty label needs.

The retail floor is no place for downtime. Continuously reloading supplies or receiving a flashing low-battery light in the middle of a markdown can slow down your operations. Compared to other mobile printers on the market, the LP3 offers superior media capacity and battery power longevity. And with its fast and easy side-loading design, this means fewer interruptions and increased productivity on the floor.



*Offering greater media capacity and battery endurance, LP3 has the capability of help you eliminate downtime and increase efficiencies.*

### FEATURES & BENEFITS



Longer battery life with two standard 7.2V Lithium-ion rechargeable batteries.




An ergonomic design allows storefront workers to carry the printer or fit it easily in a shopping cart.



The LP3 features a label presenter for quick-and-easy peel-and-apply operations.



Experience quick-and-easy media loading by simply sliding the roll into the printer, securing the end-cap and you're ready to go.



LP3 provides greater media capacity and accommodates a wide variety of labels and paper.

# Technical Specifications

## PHYSICAL CHARACTERISTIC

**Dimensions (HxWxD):** 199.6 mm x 157.5 mm x 131.3 mm (7.86 x 6.2 x 5.17 in)  
**Weight:** Printer only: 1.13 kg (39.9 oz),  
With batteries & paper roll: 1.8 kg (63.5 oz)  
**Drop Specification:** 1.22 m (4 ft)

## USER ENVIRONMENT

**Operating Temperature:** 0°C to 45°C  
(-4°F to 113°F)  
**Storage Temperature:** -40°C to 70°C  
(-40°F to 158°F)  
**Charging Temperature:** 5°C to 40°C  
(41°F to 104°F)  
**Relative Humidity:** 10% to 90% non-condensing  
**ESD Protection:** 8 kV Air, 4 kV contact

## PRINT TECHNOLOGY

**Printhead:** Direct thermal, 8 dots per mm  
(203 dots per inch)  
**Print Width:** 72.1 mm (2.84 in)  
**Print Mechanism Speed:** 51 mm per second  
(2 in per second)

## POWER SOURCE

**Batteries:** (2) 7.2V Lithium-ion (Li-ion), 2200 mAh  
(for a total of 4400 mAh)  
**DC Inputs (for Charging Only):** 12-15V, built-in  
spike and surge protection  
**Endurance:** 802.11b/g: prints approx. 8,760,  
50.8 mm (2 in) x 28.575 mm (1.125 in) labels on a  
single battery charge (36.5 hours)  
**Bluetooth®:** Prints approx. 13,392, 50.8 mm (2 in)  
x 28.6 mm (1.13 in) labels on a single battery  
charge (55.8 hours)  
**Recharging:** 4-5 hours from AC adapter or 12V  
auto power adapter

## COMMUNICATION

**Serial:** RS-232; up to 460.8 kbps  
**USB:** 2.0 (full speed)  
**802.11 b/g:** Frequency band: 2.4 to 2.4897 GHz,  
Data rates: Standard 802.11b/g rates, network  
standard: IEEE 802.11b/g, wireless access modes:  
Infrastructure and ad hoc

## Security Protocols:

	WPA	WPA2
<b>Modes</b>	PSK/Enterprise	
<b>Security/Encryption</b>	TKIP/RC4	CCMP/AES
<b>Authentication</b>	EAP-FAST, EAP-PEAP, EAP-TTLS	

**Network Support:** DHCP, TCP, UDP, BOOTP,  
remote-management support, (compatible with  
the remote-management software and other  
remote-management systems)  
**Bluetooth®:** Network Environment: Ad hoc or  
piconet, Supported Versions: v1.2 (compatible  
with v1.1 devices)

## MEDIA

**Type:** Labels: 19 mm (0.75 in) to 76.2 mm (3.0 in)  
lined labels w/Q-mark or gap sensing,  
synthetic media, UV-coated media, 50.8 mm (2 in)  
hang tags  
**Maximum Roll Capacity:** 88.9 mm (3.5 in) O.D.;  
25.4 mm (1.0 in) I.D. core  
**Roll Width:** 25.4 mm (1.0 in) to 76.2 mm (3.0 in)  
**Thickness:**  
Minimum: 0.05 mm (0.002 in)  
Maximum: 0.18 mm (0.007 in)  
*For optimum print quality and printer  
performance, use certified Honeywell  
media supplies.*

## AGENCY APPROVAL

*Contact your Honeywell sales representative for  
the most recent list of agency approvals.*

## BARCODES/FONTS/GRAPHICS

**Memory:** 2MB RAM/4MB Flash  
**Standard Fonts:** 5.5CPI, 7.2CPI, 10.2 CPI,  
10.7CPI, 18.5CPI 20.4CPI, 22.6CPI & 34.0CPI  
(additional fonts available)  
**Optional Characters:** Arabic, Greek, Hebrew,  
OCRA, OCRB, Unicode subset including Latin &  
Thai, Asian (including Big 5, Simplified Chinese,  
Korean and Shift JIS) - additional international  
characters available

**Barcodes:** Linear: Codabar, Code 39, Code 93,  
Code 128, EAN-8, EAN13, Interleaved 2 of 5,  
MSI/Plessey, UCC/EAN-128, UPC-A, UPC-E,  
2D Symbologies: PDF417, AZTEC, QR, GS1,  
Datamatrix (available on wireless only)  
**Graphics:** Supports storage of graphics/logos in  
Flash memory and transient "print once" graphics

## SOFTWARE/FIRMWARE

**Protocol:** Line Printer Mode, Easy Print®  
**Device Management (for 802.11 models only):**  
Remote Management Software (RMS), Wavelink®  
Avalanche MC, Motorola MSP  
**Drivers:** Windows® CE and Desktop  
**Compatible Label Design Software:** NiceLabel,  
BarTender®, DP Designer  
**Software Development Kit:** C++, Visual Basic,  
Java, Microsoft Dynamics, Blackberry  
**Device Interface:** OPOS, JPOS

## OPTIONS

**Wireless Communication:** Bluetooth® or  
802.11b/g

## WARRANTY

**Standard Warranty:**  
**Printer:** 1 year\*  
**Printhead:** 1 year\* or 25,400,000 mm (1,000,000 in),  
whichever comes first  
**Extended Warranty:** Contact your Honeywell  
sales representative for extended warranty  
options available through Honeywell Repair  
Services

\* Covers platen roller, printhead and installed options

## Honeywell Scanning & Mobility

9680 Old Bailes Road  
Fort Mill, SC 29707  
800-582-4263  
www.honeywell.com