

1545C

Rear Mount

**3000 Series
15" CRT Touchmonitor**



SPECIFICATIONS

Model	1545C	
Case/Bezel color	Metal/black	
Display type	FST CRT	
Display size	15.0" diagonal	
Display area dimensions, nominal	Horizontal	10.6" (270 mm)
	Vertical	8.0" (202 mm)
Monitor dimensions	Width	17.1" (434 mm)
	Height	12.3" (313 mm)
	Depth	15.0" (381 mm)
Dimensional drawing number	MS500333 Rev A (available at www.elotouch.com)	
Highest recommended resolution	800 x 600 at 85 Hz	
Resolution presets	800 x 600 at 85 Hz	
	640 x 480 at 85 Hz	
Dot pitch, nominal	0.28 mm	
Video bandwidth	65 MHz	
Input frequency	Horizontal 30–55 kHz; vertical 50–160 Hz	
Input video format	Analog (no proprietary video card needed)	
Input video signal connector	Mini D-Sub 15-Pin (female)	
Power supply	100–240 VAC, 50/60 Hz	
Power dissipation	60 W typical, 70 W max.	
Temperature	Operating 5°C to 55°C; storage –20°C to 65°C	
Humidity	Operating 10% to 85%; storage 5% to 95%; noncondensing	
Weight (approx.)	Actual 36 lb (16.3 kg); shipping 44 lb (20 kg)	
Warranty	Monitor	2 years
	Touch technology	2 years iTouch
Other features	Digital on-screen display (OSD); ENERGY STAR; VESA DPMS/NUTEK; VESA DDC 1/2 B Plug and Play; ISO 9241/3	

ORDERING INFORMATION

Touch Technology	Touch Interface	Surface Treatment	Elo Part Number	Agency Approvals
iTouch	Serial	Antireflective	C11285-000	FCC/ICES-03: Class B, UL/cUL (*Recognized component), TÜV-Bauart, CE, VCCI, C-Tick, MPR II, DHHS, Demko
iTouch	USB	Antireflective	F45900-000	FCC/ICES-03: Class B, UL/cUL (*Recognized component), TÜV-Bauart, CE, VCCI, C-Tick, MPR II, DHHS, Demko

- Users should independently evaluate the suitability of the product for their application.
- All prices, models, and availability subject to change without notice.

- Stock quantities may be limited. Larger quantities are available within one week.
- For Product Agency Certifications refer to our Web site.

3000 Series
15" CRT Touchmonitor

