



3.5" Mini-Dome Cameras

Product Features:

- Digital Signal Processing
- Sony 1/3" Super HAD CCD
- High Performance Mini-Dome Cameras
- Excellent Low Light Sensitivity
- Auto Tracking White Balance
- Signal Noise Ratio of 48dB
- Reverse Power Input Safety Circuit Built-In
- 12VDC Power
- Includes Cable With BNC Connector for Video 12V for power
- Durable Housing
- Optional Mounting Brackets Available




Black & White/DSP Color
EL-MDB42-4 EL-MDC38-4 EL-MDC48-4



Camera Specifications

Model	BLACK & WHITE		COLOR	
	EL-MDB42-4	EL-MDB56-4	EL-MDC38-4	EL-MDC48-4
Image Sensor	Sony 1/3" Super HAD CCD			
Picture Elements	270K (EIA)	410K (EIA)	270K (NTSC)	410K (NTSC)
White Balance	Automatic White Balance			
Scanning System	525 Lines (EIA) 2:1 Interlace		525 Lines (NTSC) 2:1 Interlace	
Sync. System	Internal			
Scanning Frequency	(H)15.734KHz, (V)59.94Hz (EIA)		(H)15.734KHz, (V)59.94Hz (NTSC)	
Horizontal Resolution	420 TV Lines	560 TV Lines	380 TV Lines	480 TV Lines
S/N Ratio	48dB (AGC Off)			
Gamma Correction	0.45			
Video Output Signal	1.0Vp-p Composite			
Minimum Illumination	0.1 Lux at F1.6		0.5 Lux at F1.6	
AGC	Automatic			
Back Light Compensation	Automatic			
Automatic Electronic Shutter	1/60 - 100,000 (EIA)		1/60 - 10,000 (NTSC)	
Lens Type	4.3mm Fixed Board Lens (STD) – (Opt. 2.9, 6, 8, 12, & 16)			
Operating Temperature	14 ° F –122 ° F (-10 ° C – +50 ° C)			
Humidity	Within 90% RH			
Output Terminal	1M BNC/DC Cable (2.1mm)			
Power Source	12 VDC 110mA		12 VDC 130mA	
Dimensions (mm)	110mm(W) X 76.5mm(H)			
Weight	270g			



Presented by: