

iSOLATE100M Intrinsically Safe PS2/Serial Interface Isolator for location in the hazardous area



Galvanic isolation for keyboards, pointing devices, barcode scanners and other RS232/RS485 serial interfaces suitable for location in the hazardous area

**ATEX II 2 G EEx m [Ia] IIC T4
II D T75°C IP67**

-30°C to +60°C (-22°F to +140°F)

IP67

Overview

The iSOLATE100M is an ATEX certified intrinsically safe PS2 and serial interface suitable for hazardous area mounting. The device allows connection of hazardous area peripherals such as pointing devices, keyboards and scanners to PC systems located in a safe area. The iSOLATE100M is designed for use with Extronics own range of keyboards and pointing devices such as trackball, trackpad or finger mouse but can be used with other manufacturers compatible equipment.

Features and Benefits

Multiple Applications

The unit is simple to operate and is available in a variety of configurations as specified in the ordering data below.

No High Integrity Earth Required

With both galvanic and optical isolation for the power and the interfaces no high integrity earth is required or consideration about potential differences occurring meaning low simple and trouble free installation.

Long Distance Connection


Keyboard or pointing device may be up to 20 metres away from the PC in the hazardous area using a PS2 cable or up to 70 metres using a CAT6 STP cable

Location

Suitable for location in zone 1 hazardous area

Specification

Certificate Number	TUV 04 ATEX 2645
Certification Type	ATEX II 2 G EEx m [Ia] IIC T4 II D T75°C IP67
Dimensions	105 x 166 x 44 mm (w x h x d) plus connection enclosures 4.13 x 6.54 x 1.73 inches
IP Rating	IP67
Ambient Temperature	-30°C to +60°C (-22°F to +140°F)
Weight	1.6Kg (3.53lbs)
Relative humidity	0 to 75%, non-condensing
Housing	Aluminium. Terminal Enclosures GRP.
Electrical Connection	Exe / Ex I Rated Terminal enclosures
Power Supply	Powered from PC PS2 port or separate 5 VDC supply
Mounting	Surface using two brackets supplied
Interfaces	2 x PS2, One can be configured for single direction RS232 (Rx from hazardous to safe area) Optional keyboard/mouse wedge for safe area



Ordering Information

iSOLATE100M

Please Specify [#1] - Type of configuration

Intrinsically Safe Keyboard Interface two PS/2 safe area to two PS/2 hazardous area
 Intrinsically Safe Keyboard Interface PS/2 Keyboard Wedge
 Intrinsically Safe Keyboard Interface PS/2 and RS232
 Intrinsically Safe Keyboard Interface PS/2 and RS485

Accessories

PS/2 to USB converter
 Keyboard/Mouse Extender

iSOLATE100M-[#1]-[#2]-[#3]

EX01
 EX02
 EX03
 EX04

USBCONV1
 CE120