

GVision 10.4" LCD Monitor

10.4" SVGA Display for high-end applications

- Product Specifications -

		JIPS-DA
LCD Display		10.4" TFT active matrix panel
Display Size		210.432(H)x157.824(V) mm
Pixel Pitch		0.2055(H)x0.2055(V) mm
Max. Resolution		SVGA 800 X 600
Contrast Ratio		300:1 (typical)
Brightness		230 cd/m ² (typical)
Response Time		50 ms
Display Color		262K
Viewing Angle	L/R	+55°~-55° (typical) = 110 degrees total
	U/D	+35°~-15° (typical) = 50 degrees total
PC Interface	Video	RGB analog 0.7V peak to peak
	Sync.	TTL positive or negative
Display Mode		VGA 720x400 (70 Hz)
		VGA 640x480 (60/66/70/72/75/85 Hz)
		SVGA 800x600 (60/70/72/75/85 Hz)
Signal Connector		D-sub 15 pin
Front Control		Power on/off with LED, Menu/Select, Adjustment (+,-)
Plug & Play		DDC1/2B compatible
Speaker		1W/per channel driver
Dimensions (inches)		10.8 x 9.25 x 1.75
Power Adapter		Input AC 90~264V, 50~60Hz; Output DC 12V / 3.5A
Operating Conditions	Temperature	5°C-35°C (41°F-95°F)
	Humidity	20%-80% (no condensation)
	Altitude	To 10,000 feet
Storage Conditions	Temperature	-20°C-60°C (-4°F-140°F)
	Humidity	10%-90% (no condensation)
Options:	Mechanical	Wall mount, robotic arm, pole mount kit.
	Touchscreen	Resistive, Capacitive, Surface Acoustic Wave
	Video-in	Model # J1PS-DW

* Specifications are subject to change without notice.



Catch the wave of the future - Now!



GVision-USA Inc.

20532 Crescent Bay Drive, Suite 104, Lake Forest, CA 92630

www.gvision-usa.com

TEL: 949.586.3338 FAX: 949.586.3398