

S410

SEMI RUGGED 14" LAPTOP

- 14 inch HD or FHD display
- Optional Intel® Core™ i7 2.6GHz processor
- Optional 1000 NIT Lumibond 2.0™ sunlight readable touchscreen
- MIL-STD 810G and IP51 certified¹
- Optional NVIDIA® GeForce® 4GB graphics card
- Certified to withstand a 3 foot drop
- Certified for -5.8°F low temperature



Speed for Multi-Tasking

Intel Skylake Core i7, i5, & i3 processors give the S410 best-in-class performance for data-intensive multi-tasking. This latest generation offers faster boot up and faster performance while using less power.



Purpose Built Configuration

The S410's no-compromise set of integrated features, configurable options and complete accessory ecosystem provide you with a truly "purpose-built" tool for more successful implementations. This includes second battery, second LAN, PowerShare USB 2.0, discrete GPS and vehicle mounting capability.




Multi-Level Security

S410 is the first to use Intel's TPM 2.0 for powerful anti-tampering protection. Combined with fingerprint scanner, smart card reader, optional Absolute™ DDS and additional Microsoft security features, the S410 offers extensive protection for your data and device.




Sunlight Readable Display.

The S410 semi-rugged laptop offers an advanced, Lumibond 2.0 multi-touch display with up to 1000 NITs of brightness. By bonding Gorilla® Glass with the touch panel and LCD, we've created a single pane with amazing durability, readability and responsiveness .



Amazing Graphics.

The S410 offers FHD display along with an optional NVIDIA® GeForce® GTX 950M 4GB graphics card. Combined, these features produce extreme clarity and contrast for amazing graphics performance.



Extreme Temperature Range

Being able to work in any environment is critical, even freezing cold or extreme heat. The S410 is certified to perform when you need it, even in temperatures as cold as -5.8°F and as hot as 140°F.

GETAC S410

Specifications



Getac

GetacSales_US@getac.com
www.getac.com
949.681.2900

Getac, Inc.
400 Exchange, Ste 100
Irvine, CA 92602

| | | | |
|-------------------------|--|---|--|
| Ruggedness | Semi-Rugged MIL-STD 810G certified (vibration, temperature, shock, altitude and humidity) IP51 certified 3 foot drop - 26 faces (non-operational) Covered ports | Customizable Bay (One option only) | Optional PCMCIA Type II Optional ExpressCard34/54 Optional DVD super multi drive Optional 2nd battery |
| Operating System | Windows® 10 Professional Windows 7 Professional | Expansion Slot | SD Card Reader Optional smart card reader |
| CPU | Intel® Core™ i7-6600U vPro™ 2.6GHz processor with Turbo Boost Technology up to 3.4GHz 4MB Intel® Smart Cache Intel Core i7-6500U 2.5GHz processor with Turbo Boost Technology up to 3.1GHz; 4MB Intel Smart Cache Intel Core i5-6300U vPro 2.4GHz processor with Turbo Boost Technology up to 3.0GHz 3MB Intel® Smart Cache Intel Core i5-6200U 2.3GHz processor with Turbo Boost Technology up to 2.8GHz 3MB Intel® Smart Cache Intel Core i3-6100U 2.3GHz processor 3MB Intel® Smart Cache | Security | Intel vPro™ Technology (per CPU options) TPM 2.0 Cable lock slot Optional smart card reader Optional contactless Smart card reader (RFID) NIST BIOS compliant Optional fingerprint reader Optional Absolute™ DDS software |
| Memory | 4GB DDR3L expandable to 16GB | Communications | 10/100/1000 base-T Ethernet Intel Dual Band Wireless-AC 8260, 802.11ac Bluetooth (v4.2 class 1) Optional dedicated GPS Optional 4G Gobi LTE mobile broadband XLTE Ready ² |
| Storage | SATA 500GB HDD [†] ; Optional SATA 1TB HDD; Optional SATA 128GB / 256GB / 512GB SSD Optional 2nd Storage (onboard) 128GB or 256GB SSD | Power | AC adapter (65W, 100-240VAC, 50/60Hz or 120W, 100-240VAC, 50/60Hz with NVIDIA configs.) Li-Ion battery (11.1V, 4200mAh) Optional Media Bay 2nd battery (11.1V, 4200mAh) Optional bridge battery |
| VGA Controller | Intel HD Graphics 520 Optional NVIDIA® GeForce® GTX 950M 4GB discrete graphics | Dimensions and Weight | 13.8" x 11.5" x 1.4" (350 x 293 x 34.9 mm) ^{††} 4.9 lbs (2.2kg) |
| Display | 14" HD widescreen (1366 x 768) TFT LCD Optional 1000 NITS LumiBond® sunlight readable display with multi-touch technology Optional Full HD 14" TFT LCD (1920 x 1080) 800 NITs LumiBond sunlight readable display with multi-touch technology | Temperature | Operating: -5.8°F to 140°F / -21°C to 60°C / Storage: -60°F to 160°F / -51°C to 71°C Humidity: 95% RH , non-condensing |
| Webcam | Optional integrated FHD webcam (1920x1080) | I/O Interfaces | DC in x 1 USB 3.0 (9-pin) x 3 USB 2.0 (4-pin) x 1 Network (RJ-45) x 1 Headphone-out / microphone-in combo x 1 HDMI x 1 Optional Serial port (RS-232: 9-pin, D-sub) x 1 Optional VGA port (15-pin, D-sub) x 1 Docking connector (16-pin) x 1 Optional RF antenna pass-through for GPS, WLAN and WWAN |
| Keyboard | Splash-resistant membrane keyboard Optional splash-resistant LED backlit | Warranty | 3 Year limited warranty standard ^{‡w} |

Standard and optional features vary depending on purchased configuration. Specifications subject to change without notice.

¹ MIL-STD 810G certified for vibration, temperature, shock, altitude, humidity and 3 ft drop.

² Data plan required. Cellular data is available in the US on Verizon Wireless and AT&T networks. LTE is available in select markets. Check with your carrier for details. 4G LTE configuration must be ordered at time of purchase.

³ Computers configured with a 32-bit operating system can address up to 3GB of system memory. Only computers configured with a 64-bit operating system can address 4 GB or more of system memory.

[†] For storage, 1GB = 1 billion bytes; actual formatted capacity less.

^{††} Dimensions and Weight vary by configuration and manufacturing process.

[‡] 3 year limited warranty standard. For warranty terms and conditions visit www.getac.com

Copyright 2016, Getac, All Rights Reserved. Getac and the Getac logo are either registered trademarks or trademarks of Getac Technology Corporation in the United States and/or other countries. Microsoft and Windows are registered trademarks of Microsoft Corporation in the United States and in other countries. All other trademarks are the property of their respective owners.

V3M04Y16