

Portable Tablet T510K



Rugged Mobile Computing Solutions



The T510K portable tablet gives you the power of desktop computing in a slim, rugged design with a large 10 inch display and 23-key Keypad. On-the-go data collection is easy with 2D barcode imaging, camera, and RFID. Staying connected is easy with 802.11 b/g/n, Bluetooth and Gobi 3000 module. Dual hot swappable batteries give you up to 9 hours of use in the field or in the warehouse. The T510K weighs only 2.42 lbs, with an IP54 rating and is also shock and vibration tested.

All Glacier portable tablets are meant to run 24/7 in a variety of environments.

Affordable rugged computing for mobile professionals.

- INTEL® ATOM™ Z530P 1.6GHZ PROCESSOR, 533MHZ FSB
- 802.11 b/g/n
- GOBI 3000 3G MODULE
- BLUETOOTH 2.1 +EDR
- CAMERA
- 2D BARCODE SCANNER
- RFID 13.56MHZ
- ULTRA LOW POWER CONSUMPTION
- 9 HOURS BATTERY LIFE



INTEGRATED 802.11 & BLUETOOTH



IP54




DROP TESTED



TOUCHSCREEN INTERFACE

 Find us on Facebook

 Visit us on LinkedIn

Rugged Mobile Computers
Copyright Glacier Computer 2011

Glacier T510K Hardware Specifications

Operating System

Windows® XP
Windows® 7

Processor

Intel® Atom Z530P 1.6GHz CPU, FSB
533MHz

Chipset

Intel® System Controller Hub US15WPT

Memory

2GB DDR2-667 SDRAM

Storage

32GB SSD
64GB SSD (optional)

Display

10.4" (1024x768) XGA TFT Active Matrix
LED Backlight
800 NIT Sunlight Readable (optional)
Resistive Touchscreen

Camera

2M w/Auto Focus

Wireless/Communications

Wi-Fi 802.11 b/g/n
Bluetooth 2.1 +EDR
Gobi 3000 3G Module

Barcode Scanner

2D Scanner

RFID

HF 13.56MHz, ISO
15693/14443A/14443B

Function Keys

10 x Number Keys (0-9)
Enter Key
4-ways Arrow
4x Function Keys
ESC Key
Backspace Key
Dot (.) Key
Brightness Control Key

Keypad

23-Key

I/O Ports

USB 2.0 Port
SD/SDHC Slot
SIM Socket

Audio

Azalia HD DT
Audio-out Jack
Integrated Mic & 1.5W Speaker

Battery

1880mAh 3-Cell, 2500mAh 4-Cell
Hot Swappable
Operating Time 9 Hours

AC Adaptor

AC Power Input: 100V-240VAC
Adaptor Output: 19VDC, 3.4A, 65W

Dimension & Weight

8.07 x 11.57 x 0.98in/205 x 294 x
25mm
2.42lb/1.1kg

Temperature & Humidity

Operating Temperature -20C° to
+45°C, -4°F to +113°
Storage Humidity 5% ~ 95% non-
condensing

Environment

IP54 Rating
4 ft/122cm Drop to Wood

Vibration

3Grms/5 ~ 500Hz/ random operation

Shock

40G Peak Acceleration
(11 ms duration))

Certifications

CE/FCC Class B,

Optional Features

Docking Station
800 NIT Sunlight Readable Display
64 GB SSD

Desktop Cradle

3x USB, 1x LAN, 1x DC Jack

Warranty

1 Year

Specifications are subject to change.



Glacier Computer LLC

10 Northern Blvd., Amherst, NH 03031 Tele: 603-882-1560

www.glaciercomputer.com