

Transaction Team™ 3100 Series Interactive Transaction Terminal



Features

Pressure-Sensitive Screen Technology - "Electronic ink" mirrors pen-and-paper experience, generating exact signature reproduction. Enables touch-screen PIN entry.

Large Backlit LCD Screen - Easy to read, displays store logo, ads, line items, and/or interactive survey; split screen capabilities.

Passive Pen Technology - Low maintenance - no expensive electronic pen replacement.

Fully Programmable Display - Allows customization of both text and graphics.

Integrated 3 track MSR (Standard) - Eliminates the need for additional hardware. Saves space and money.

Screen Protector System (TT3101 Standard) - Additional benefit of screen protection from abuse and water penetration.

Secure ISA Expansion Bus (Standard) - Allows for the addition of future peripherals.

Pin Secure - Secure for debit transactions using DUKPT or Master/Session key management.

RS-232, IBM RS-485 Connectivity - Multiple connectivity options to fit multiple operating environments with cable strain relief.

Durable - Rugged, long-lasting functionality. Hard coated silica/mylar touch screen. Chip resistant, flame retardant plastics.

Continuing our commitment to innovative consumer activated e-transaction systems, the Transaction Team (TT)3100 Series streamlines point-of-transaction and back office operations, reduces costs, and improves customer service. This user-friendly, interactive device combines a split screen display, MSR, and signature capture capabilities, all in a single unit. The TT3100 Series supports both RS-232 and IBM RS-485 connectivity, automatically auto-configures to the correct protocol, and allows auxiliary RS-232 peripheral devices to pass data to the host transparently.

The TT3100 Series boasts a 4.5 x 3.3 inch (11.4 x 8.4 cm) LCD window – so large that it displays line item detail while simultaneously pointing to transaction promotions. The TT3100 is fully programmable for both text and graphics, and the easy-to-read backlit screen will display logos and ads and will administer customer surveys.

The TT3100 Series is PIN secure, using either DUKPT or Master/Session key management. If there is an interruption of power to the unit, battery backup protects valuable data from being lost. Because the TT3100 Series utilizes passive pen technology, the unit is virtually maintenance-free – there's never a need for expensive electronic pen replacement.

The TT3101 model offers an added benefit of a Screen Protector System with field-replaceable overlays. This feature extends the life of the display screen and offers protection from an occasional light exposure to water.

Ideal for the retail, hospitality, financial services, security, and ID markets, the TT3100 Series integrates easily with any PC or point-of-transaction system running on open operating systems, such as Microsoft® MS-DOS®, Windows® 3.x, Windows 95®, Windows 98®, Windows 2000®, and Windows NT® version 3.51 and higher. Customer applications are developed using an included TT3100 Series Software Suite.

Upgrade your image.

Display/Signature Window

Signature Window:	Resistive, transparent, pressure-sensitive touch screen
LCD Size:	4.45 x 3.3 in. (11.3 x 8.4 cm) (Active area)
LCD Resolution:	320 x 240 dot
Touch Pad Resolution:	903 x 1238 ppi

Mechanical/Electrical

RS-232:	Using HDB15-DB9 cable and AC power adapter
RS-232 Pass-Through:	Using HDB15-DB9 host/DB9 Aux. Y cable with AC power adapter
RS-485:	Using HDB15-SDL cable using 9A, 9B, 4B connectors

Memory

ROM:	512KB
RAM:	512KB

Dimensions (reference)

Width:	7.09 in. (18 cm)
Length:	8.97 in. (22.8 cm)
Height:	2.79 in. (7.1 cm)
Weight:	1 lb., 11 oz. (756 g)

Power Requirements

Current Draw:	370 mA @ 12VDC
Source:	12V AC adapter, European and host-powered options also available

Optional TT3100 Series Software Suite

Operating Systems:	Microsoft® MS-DOS®, Windows® 3.x, Windows 95®, Windows 98®, Windows 2000®, Windows NT® 3.51 or higher
Formats Supported:	BMP, SIG, DIB, CGM, EPS, PCL, TIFF, TXT, NLC, WMF, PCX, and PLS
Object Tools:	Support for VBX, ActiveX, and VB add-in
Signature Processing:	Compression
Security:	Secure key injection, tamper-resistant security, inherently secure microcontroller
Onboard Encryption:	PIN Encryption, Master/Session key, DUKPT

Approvals and Certifications

Agency Conformance:	FCC Class A, CE, UL
----------------------------	---------------------

IBM is a registered trademark of International Business Machines, Inc.

Microsoft® MS-DOS®, Windows® 3.x, Windows 95®, Windows 98®, Windows 2000®, and Windows NT® are registered trademarks or trademarks of Microsoft Corporation in the United States and/or other countries.



Complies with EMC 89/336/EEC

Worldwide Offices

Offices Serving North America
Skaneateles Falls, NY
Tel: +1 315 685 8945
or, in North America: +1 800 782 4263
sales@hhp.com
Charlotte, NC
Tel: +1 704 998 3998
or, in North America: +1 800 782 4263
sales@hhp.com

Offices Serving Europe, Middle East, and Africa
Europe
Tel: +31 (0) 40 29 01 600
euro_sales@hhp.com
United Kingdom
Tel: +44 (0) 1 925 240055
euro_sales@hhp.com
Ireland
Tel: +353 (0) 502 44007
euro_sales@hhp.com

France
Tel: +33 (0) 1 461 04111
euro_sales@hhp.com
Germany
Tel: +49 (0) 7 477 151377
euro_sales@hhp.com
Spain
Tel: +34 93 228 76 68
euro_sales@hhp.com

Offices Serving Asia and the Pacific Rim
Hong Kong
Tel: +852 2511 3050/2511 3132
asia_sales@hhp.com
Japan
Tel: +813 52127392
asia_sales@hhp.com

Offices Serving Latin America
Naples, Florida
Tel: +1 239 263 7600
la-sales@hhp.com
S. o Paulo
Tel: +55 11 5016 3454
la-sales@hhp.com
Rio De Janiero
Tel: +55 21 2494 7060
la-sales@hhp.com

Web Site Address www.hhp.com

Hand Held Products, Inc. d/b/a HHP (IHHP)® 1999-2002. All rights reserved. Printed in the U.S.A.

Due to HHP's continuing product improvement programs, specifications and features herein are subject to change without notice.