

VALUETEAM™ 3080B

Entry Level Hand Held CCD Scanner



Features

Hardware - Rugged ABS plastic case protects from ESD, shocks, and damage. Side trigger for ergonomic operation. Compact size fits on crowded countertops.

Software - Universal Interface, all in one model.

Flash Memory - Upgrading memory in the field extends the useful life of the product.

Windows®-Compatible - HHP SET™, a Windows® utility, is capable of performing on-screen configurations, program upgrades, and on-line diagnoses.

The VALUETEAM™ 3080B scanner offers the excellent scanning performance you expect from HHP, at an attractive, entry level price. It connects to the most often used terminals and PCs for point-of-sale or general purpose applications.

The VT3080B reads from contact to 2 inches (5.1 cm) from the bar code, has Flash Memory, is compact in size, and is comfortable to use.

HHP sets high standards for scanner durability. The VT3080B has been designed to take the punishment of daily use. VALUETEAM CCD scanners also excel in reading real world bar codes; those that are damaged, smudged or dirty, or printed on low resolution printers.

When you need value, but still want HHP performance, choose the VALUETEAM 3080B.

Applications

- Retail Point of Sale
- Office Automation
- Factory Automation

To learn how the VT3080B can work for you, contact us at any of the locations listed on the back or visit us at www.hhp.com.

Upgrade your image.



VALUETEAM 3080B Specifications

Performance

Reading Distance:	Contact to 5.1cm (2")
Reading Width:	8 cm (3.1")
Resolution:	4 mil. minimum "X" dimension
Scan Speed:	100 scans per second
Light Source:	660 nm visible LED
Sensor:	2048 pixel CCD

Mechanical/Electrical

Weight:	225g including main cable
Plastic Material:	ABS
Input Voltage:	5 VDC +-5%
Current Draw:	105mA Scanning 40mA Standby .2mA Low Power Standby in PC Wedge or Wand Emulation modes only

Environmental

Operating	
Temperature:	0-40 degrees C
Humidity:	20 - 85%, non condensing relative humidity
Storage	
Temperature:	-10 to 55 degrees C
Humidity:	15 - 90 %, non condensing
ESD Protection:	Functional after 5kV contact, and 10kV air discharge
Mechanical Shock:	Functional after 6 drops from 3.3 ft. (1 m)

Interfaces

Host Interfaces:	IBM® PC/XT, PC/AT, PS/2® keyboard wedge Generic PC/AT and PS/2 keyboard direct link Apple® MAC® and Power MAC™ ADB keyboard wedge and direct link Standard TTL RS-232 Standard TTL RS-232 serial wedge Pseudo (inverted) RS-232 serial interface Wand emulation USB keyboard direct link
Symbology Support:	Code 128/EAN 128, UPC-A, UPC-E, EAN-13, AN-8, Codabar/ NW-7, Code 39/ Code 32, Code 2 of 5, Code 93, Code 11, MSI/ Plessey, UK/Plessey
Data Editing:	Can insert characters in up to 4 positions
Data Checking:	Checks for code length and character/position
Warranty	1 year factory warranty
Agency	FCC Class A, CE

Apple is a registered trademark of Apple Computer, Inc.

IBM is a registered trademark of International Business Machines, Inc.

Windows is a registered trademark of Microsoft Corporation in the United States and/or other countries.



Complies with EMC 89/336/EEC

Worldwide Offices

Offices Serving North America
Skaneateles Falls, NY
Tel: +1 315 685 8945
or, in North America: +1 800 782 4263
sales@hhp.com
Charlotte, NC
Tel: +1 704 998 3998
or, in North America: +1 800 782 4263
sales@hhp.com

Offices Serving Europe, Middle East, and Africa
Europe
Tel: +31 (0) 40 29 01 600
euro_sales@hhp.com
United Kingdom
Tel: +44 (0) 1 925 240055
euro_sales@hhp.com

France
Tel: +33 (0) 1 461 04111
euro_sales@hhp.com
Germany
Tel: +49 (0) 7 477 151377
euro_sales@hhp.com
Spain
Tel: +34 93 228 76 68
euro_sales@hhp.com

Offices Serving Asia and the Pacific Rim
Hong Kong
Tel: +852 2511 3050
asia_sales@hhp.com
Japan
Tel: +813 5842 6325
asia_sales@hhp.com

Offices Serving Latin America
Naples, Florida
Tel: +1 239 263 7600
la-sales@hhp.com
São Paulo
Tel: +55 11 5016 3454
la-sales@hhp.com
Rio De Janeiro
Tel: +55 21 2494 7060
la-sales@hhp.com

Web Site Address www.hhp.com

Hand Held Products, Inc. d/b/a HHP ("HHP") ©1999-2003. All rights reserved. Printed in the U.S.A.

Due to HHP's continuing product improvement programs, specifications and features herein are subject to change without notice.