

LOW-LIGHT

HI-SPEED

SMART

RELIABLE

IQeye511

NETWORK CAMERAS



Resolution On-Demand™

The IQeye511 delivers high-speed IP video and enhanced low-light performance in an attractive, low-profile package. Users can select the resolution they want, when they want it, from CCTV up to HDTV or even megapixel.

The IQeye511 includes our IQfocus™ utility, making it easy to install and support. Its industrial design and time-tested operating system ensures reliable operation in even the most demanding environments.

Every feature-rich IQeye is flexible and can be custom tailored for your application. Its rugged package is ideal for the professional installation where plastic, consumer-grade products fall short.

From small systems using IQrecorder™ on-camera NVR software to enterprise-wide NVR/DVR systems,* the IQeye511 lets you capture all the details.

www.iqeye.com

*For a complete list of compatible NVR/DVR systems, please visit www.iqeye.com.

IQinvision 

When you can't afford to miss a thing.

IQeye511 - Resolution On-Demand™

IQrecorder™

Available with every IQeye, IQrecorder enables you to record and playback crisp, clear IQeye Resolution™ images using affordable network storage *with no client software*.

IQauthenticate™

Every IQeye is also available with on-camera, digital authentication that protects images right in the camera. IQauthenticate addresses the image manipulation problem *at the source* ensuring your evidence has not been compromised.

IQfocus™

The IQfocus utility lets you use popular hand-held CCTV monitors and eliminates the hassles of focusing cameras over slow networks.







High Resolution



IQeye Resolution

- **1.3 Mpix resolution (1280x1024)**
- **Improved 0.2 lux low-light performance**
- **30+ ips @ D1 / 20 ips @ HDTV**
- **IEEE 802.3af - Power-Over-Ethernet**
- **LIGHTGRABBER™ low light technology**
- **Digital PTZ with no moving parts**
- **Multi-zone motion detection**
- **Digital image cropping**
- **Privacy zones**
- **Advanced bandwidth management tools**
- **Proven network reliability**
- **User-selectable exposure window**
- **AC/DC or IEEE 802.3af**
- **< 2.5 watts, AC or DC**

CAMERA MODEL	LENS OPTIONS	POWER SUPPLY	ENCLOSURE TYPE
 IQ511 Camera - 1.3 MP Camera, 15ips, 0.2 lux	NL - No Lens V3 - Wide Varifocal Lens V4 - Telephoto Varifocal Lens W1 - Ultra Wide Varifocal Lens	NP - No Power Supply P1 - 110VAC PS P2 - 220VAC PS PE - IEEE 802.3af PoE Module	NE - No Enclosure
 IQ511 Indoor Dome 5"- 1.3 MP Camera, 15ips, 0.2 lux	V3 - Wide Varifocal Lens	NP - No Power Supply P1 - 110VAC PS P2 - 220VAC PS PE - IEEE 802.3af PoE Module	D1 - Interior In-Ceiling Dome D2 - Interior Pendant Dome D3 - Interior Pendant Dome with Wall Mount
 IQ511 Vandal Dome 4"- 1.3 MP Camera, 15ips, 0.2 lux	B1 - Wide Varifocal Lens	NP - No Power Supply P1 - 110VAC PS P2 - 220VAC PS PE - IEEE 802.3af PoE Module	DV - Interior/Exterior Vandal Dome
 IQ511 Outdoor Housing 9.5"- 1.3 MP Camera, 15ips, 0.2 lux	NL - No Lens V3 - Wide Varifocal Lens V4 - Telephoto Varifocal Lens	NP - No Power Supply	X2 - Outdoor Housing, IP 65/NEMA 4
Part Number Example - IQ511NLPENE - 1.3 MP Camera, 15ips, 0.2 lux, No Lens, IEEE 802.3af PoE module, No Enclosure			

Camera dimensions (without lens) approx. 2.9"(7.4cm)H x 3.5"(8.9cm)W x 1.7"(4.3cm)D
 Camera weight (without lens) 6oz (160g)
 For shipping weight information, please contact IQinVision.

©2007 IQinVision, Inc., IQinVision, IQeye logo are registered trademarks, and IQeye, IQpoet, IQauthenticate, IQrecorder, Resolution-On-Demand, IQeye Resolution and LIGHTGRABBER are trademarks of IQinVision. All other brands, trademarks and/or registered trademarks are property of their respective holders. 0107

When you can't afford to miss a thing.

IQinvision 
www.iqeye.com

3005 S. El Camino Real
 San Clemente, CA 92672 USA
 phone +1.949.369.8100
 fax +1.949.369.8105