

SurgeGate Series AC Protection



M4T—PREMIER SERIES 4-OUTLET AC SURGEGATE WITH TELEPHONE PROTECTION



Features

- AC protection for telecom systems
- SurgeGate Plus Circuitry
- Expandable protection using SurgeGate Modules
- Four switched AC power outlets
- Diagnostic indicator lights (four)
- Eight foot power cord with right angle plug
- EMI/RFI noise filtration
- Mounting brackets included
- Telephone protection for one voice or DSL line
- RJ-11/45 Jacks

Technical Specifications

Designs and specifications are subject to change without notice due to product improvement.

PRODUCT SPECIFICATIONS:

Agency Approval	UL 1363, 1449
LED Indicators	4
Grounding Requirements	Uses Electrical AC Ground
Ground Impedance	N/A
Width	4.25"
Height	9.5"
Depth	1.5"
Weight	2.0 lbs
Product Warranty	Lifetime
Connected Equipment Warranty	Up to \$50,000



For up-to-date
warranty information
see our web site:
www.itwlinx.com



AC SURGE PROTECTION:

SurgeGate Plus Circuitry	Yes
Thermal Fusing	Yes
Catastrophic Surge Circuit	Yes
Over/Undervoltage Voltage Protection	Yes
Overvoltage Voltage Shutoff	147V $\pm$ 8V
Undervoltage Voltage Shutoff	87V $\pm$ 8V
Single Pulse Energy Dissipation	1650 Joules
Peak Impulse Current	52,000 A
EMI/RFI Noise Filtration	50db (99.7%)
Line Voltage	120V (50/60Hz)
Initial Clamping Level	200V Peak, 141 Rms
UL 1449 Rating	330V
Protection Modes	L-N, L-G, N-G
Maximum Current Rating	15A (1800W)
Response Time	1–5 Nanoseconds
Plug Configuration	Right Angle
Number of Outlets	4
Switched Outlets	4
Cord Length	8'

SIGNAL LINE SURGE PROTECTION: TELCO CIRCUIT PROTECTION

Signal Perfect Circuitry	Yes
Fuseless/Auto-Resetable	Yes
Clamping Level	260V
Response Time	1–5 Nanoseconds
Capacitance	50pF
Suppression Modes	Metallic & Longitudinal
Wires Protected	2-wires, 1-pair (pins 4, 5)
Termination Type	RJ-11/45

COAX CIRCUIT PROTECTION

Signal Perfect Circuitry	N/A
Fuseless/Auto-Resetable	N/A
Response Time	N/A
Termination	N/A
Antenna/Cable Lines Protected	N/A
Antenna/Cable Clamping Level	N/A
Antenna/Cable Attenuation	N/A
Satellite Lines Protected	N/A
Satellite Clamping Level	N/A
Satellite Attenuation	N/A

LAN CIRCUIT PROTECTION

Signal Perfect Circuitry	N/A
Fuseless/Auto-Resetable	N/A
Performance Rating	N/A
Clamping Level	N/A
Response Time	N/A
Wires Protected	N/A
Termination Type	N/A



More information is available in the Technical Reference section of this catalog, turn to page 86.

Applications:

- Telephone Systems
- Workstations
- Printers
- Fax Machines
- Copiers
- TVs / VCRs
- Cameras
- Access Controls
- Alarms

Ordering Information

ITW Linx Part Number	Description
M4T	4-outlet AC surge protector, with SurgeGate Plus circuitry and modular mounting capabilities. Plus protection for one telephone or DSL line.