



**Infinite
Peripherals®**

DPP-450

General Specifications

Mobilize Your Enterprise™

4" thermal mobile printer, battery operated.
Bluetooth® option available.
Prints paper and labels, includes label gap sensor and label peeler.
LCD display. Compact form factor, integrated belt clip.

**Headquarters/
Main Warehouse**
2312 Touhy Avenue
Elk Grove Village, IL 60007

Office (847) 818-1260
Fax (847) 818-1287
Toll-Free (800) 278-7860
Email info@ipcprint.com

**Mobility Sales/
Technical Support Center**
1641 McGaw Avenue
Irvine, CA 92614

Office (949) 222-0300
Fax (949) 222-0375
Toll-Free (866) 278-7860
Email info@ipcprint.com

Standard Features



Li-ion
Battery

Optional Features



Bluetooth®



PRINTING SPECIFICATIONS

Printing Method	Line thermal dot printing
Printing Speed	150mms/s (1200 dots/sec)
Print Width	104mm / 832 dots per line
Resolution	203dpi (8x8 dots/mm)
Dot Pitch	Horizontal - 0.125 mm (8 dots/mm) Vertical - 0.125 mm (8 dots/mm)
Resident Fonts	Font A: 12 x 24 dots (48 char. per line) Font B: 9 x 16 dots (64 char. per line)
Loadable Fonts	Font C: 12 x 24 dots (48 char. per line) Font D: 9 x 16 dots (64 char. per line)
Logo Registration	1 black and white size: 832 x 248 dots
Input Buffer	128 KB (131072 bytes)
Resident Barcodes	1D - EAN13, EAN8, UPC-A, UPC-E, Codebar, Code39, Code128 2D - PDF417, QR Code
Communications	RS232 C - max. 115200 bps. USB v 1.1, compatible with 2.0 Bluetooth
Emulation	ESC/POS/LABEL (Continuous paper mode, Black Mark mode)
Thermal Paper	115 mm / Ø 45 mm, thickness 60 Qm Label Paper Roll: 115 mm / Ø 45 mm
Reliability	Printing head: 50km (printing rate 25% max)

ELECTRICAL

Power Supply	Rechargeable Li-ion battery (7.4 V / 2000 mAh) Battery capacity: per charge (~30,000 lines) AC adapter - DC 24V, 5A AC 100 - 240 V, 50/60 Hz
---------------------	---

MECHANICAL

Dimensions	136mm (W) x 123mm (D) x 51mm (H)
Weight	785 grams (without paper) 990 grams (with paper)

ENVIRONMENT

Operating Environment	Operating temperature 0°C to +45°C 32°F to 113°F Operating humidity 35 to 85% RH Storage temperature -20°C to +60°C -4°F to 140°F Storage humidity 10 to 90% RH
------------------------------	--

COMPATIBILITY

iOS Support	iOS6 and higher
Android™ Support	Android OS 2.1 and higher

Specifications subject to change without notice.
Android is a trademark of Google Inc.
The Bluetooth® word mark and logos are registered trademarks owned by Bluetooth SIG, Inc.

COMPATIBLE WITH

Infinea Tab® 4



Infinea Tab® M



Linea Pro® 5