

Intermec

Product Profile

- Full omni-directional 2D Image Reader with image capture technology
- Captures data at a high-speed 30 frames per second
- Reads all popular 2D and linear symbologies
- Free Quick*View software and Visual*Menu configuration utility makes initial setup a snap!



ScanImage™ 1470B IMAGER

Intermec is proud to offer the ScanImage 1470B imager. Strides beyond our previous imager offerings, the ScanImage 1470B comes packed with powerful features.

Rightly suited for a wide spectrum of industries, the ScanImage 1470B imager is ideal for warehouse and distribution, retail, packaging, printed circuit board manufacturing and healthcare/clinical applications—essentially anywhere omni-directional and/or 2D imaging is required. The ScanImage 1470B seizes data at a high-speed 30 frames per second. A scanning range of up to 9 inches on linear bar codes, ergonomic design, and a new intuitive, bright, sharp scan line make the ScanImage 1470B extremely user friendly.

What's more, exceptional durability combined with low power consumption

makes the ScanImage 1470B an excellent choice for portable data collection in warehouse, manufacturing, and distribution applications.

Setting up the ScanImage 1470B is a snap with Visual*Menu – a software utility for quick and easy configuration. There's no need to page through thick manuals to turn on/off features required for your application. With a point and click you can instantaneously configure your imager to meet the needs of your application. Even better, every ScanImage 1470B imager comes with Quick*View and Visual*Menu configuration software free of charge.

Ease, comfort and performance, the ScanImage 1470B is the easy choice for your imaging solution.

Intermec

Physical Characteristics**Length:** 6.1 in. (15.4 cm)**Height:** 5.6 in. (14.2 cm)**Width:** 2.5 in. (6.4 cm)**Weight:** 7 oz. (198 g)**Power****Supply:** 4 to 9 volts**Power Management:** Low, Medium, High Power Modes**Connectivity**

RS-232, Keyboard Wedge, Intermec 10-pin Wand em for (T242x and 97xx), Intermec 700, Intermec T241x (16-pin)

Bar Code Symbologies**Linear:** Code 39, Code 128, Codabar, UPC, EAN, Interleaved 2 of 5, Code 93, Codablock**2 Dimensional:** Data Matrix, PDF417, Micro PDF417, Maxicode, Aztec, Aztec Mesa, QR Code, Code 49, UCC Composite, RSS**Postal:** POSTNET (US), BPO4 State, Canadian 4 State, Japanese Post, KIX (Dutch Post), Planet Code**OCR Fonts:** OCR-A, OCR-B, U.S. Currency**Scanning Performance****Scan rate:** 30 frames per second**Scan range:** 5 mil linear: 2.75 - 3.75 in (7.0 - 9.5 cm)

10 mil linear: 2.1 - 9.5 in (5.3 - 24.1 cm)

10 mil Data Matrix: 2.2 - 3.8 in (5.6 - 9.6 cm)

Scan angles: $\pm 45^\circ$ **Rotational Sensitivity:** 360°**PCR:** down to 30% on 6.6 mil Data Matrix**Accessories**

BATTPACK1 Rechargeable Battery Pack (US)

BATTPACK1 Rechargeable Battery Pack (Europe)

BATTPACKU1 Rechargeable Battery Pack (UK)

067056 Wall/Countertop Holder, Black
069443 Scanner Stand**Environment****Operating Temperature:** -0 C to 50 C**Storage Temperature:** -40 C to 70 C**Humidity:** 95% Relative Humidity, non-condensing at 50 C**Shock and Vibration Protection:** 10**Rain and Dust Resistance:** Windblown rain and dust**Drop Survival:** 10 drops to concrete from 5 ft.**Regulatory Approvals**

UL Listed, Compliant with all European Directives, CE marked.

Intermec reserves the right to make changes without notice to any products herein for any reason at any time, including but not limited to improving the reliability, form, fit, function or design. Please contact Intermec for current price list and availability.

North America**Corporate Headquarters**
6001 36th Avenue West
Everett, Washington 98203
tel: 425.348.2600
fax: 425.355.9551**Systems & Solutions**
550 2nd Street S.E.
Cedar Rapids, Iowa 52401
tel: 319.369.3100
fax: 319.369.3453**Media Supplies**
9290 Le Saint Drive
Fairfield, Ohio 45014
tel: 513.874.5882
fax: 513.874.8487**Europe/
Middle East & Africa
Headquarters**Sovereign House
Vestern Road
Reading, Berkshire RG1 8BT
United Kingdom
tel: +44.118.987.9400
fax: +44.118.987.9401**Asia****Hong Kong**
2602 Convention Plaza
Office Tower
1 Harbor Road
Wanchai, Hong Kong
tel: 852.2574.9777
fax: 852.2574.9725**Singapore**25-16 International Plaza
10 Anson Road, 079903
tel: 65.324.8391
fax: 65.324.8393**Australia**Level 7, 200 Pacific Highway
Crows Nest NSW 2065
Australia
tel: 61.2.9492.4400
fax: 61.2.9954.6300**South America & Mexico
Latin America Headquarters**17921 B Skypark Circle
Irvine, California 92614
tel: 949.442.9393
fax: 949.757.1687**Mexico**Tamulipas 141, Primero Piso
06140 Mexico, D.F.
tel: 525.55.211.1919
fax: 525.55.211.8121**Worldwide
Fax Document
Retrieval Service**800.755.5505
(North America Only)
tel: 650.556.8447**Internet**

www.intermec.com

Sales800.347.2636
(toll free in N.A.)
tel: 425.348.2726**Service and Support**800.755.5505
(toll free in N.A.)
tel: 425.356.1799

Copyright © 2002 Intermec Technologies Corporation. All rights reserved. Intermec is a registered trademark of Intermec Technologies Corporation. All other trademarks are the property of their respective owners. Printed in the U.S.A. 611112-01B 06/02

In a continuing effort to improve our products, Intermec Technologies Corporation reserves the right to change specifications and features without prior notice.