



Intermec

Product Profile

- Compact, industrial design
- Robust data collection
- 2.4 GHz or 802.11b 11 Mbps radios for wireless models
- Industry standard development and connectivity tools
- Flexible application environments



2480 SERIES STATIONARY COMPUTER

The 2480 Series Stationary Terminal delivers timely, accurate data for mission critical manufacturing systems. With a compact metal case, environmental sealing and power protection, the reliable 248X handles the most punishing industrial plants. It's ideal for work in process tracking, labor collection, and time and attendance applications.

The 2480 Series Stationary Terminal includes two ports for bar code input devices and a serial port to connect a printer or scale. An optional integrated badge scanner, digital input/output and two additional serial ports accommodate the most demanding data collection requirements.

Choose Ethernet, wireless or serial connections to host computers. With the 2.4 GHz and 802.11b wireless models, you can easily change configurations of manufacturing work cells. The 2480 Series supports client/server and terminal emulation host environments. It's also compatible with Intermec CrossBar® networks.

The 2480 Series Stationary Terminal is programmable using industry standard, Microsoft® C/C++ or EZbuilder, Intermec's rapid application development tool. Using standard tools you can dramatically reduce development time and cost for creating shop floor solutions.

A large, stylized outline of the Intermec logo at the bottom of the page, spanning across the width of the document.

Physical Characteristics

Height: 24.4 cm (9.6")
 Length: 27.2 cm (10.7"); 28.7 cm (11.3")
 with badge scanner
 Depth: 9.9 cm (3.9")
 Weight: 4.3 kg (9.5 lbs)

Environment

Operating temperature: -20° to 50°C
 (-4° to 122°F)
Storage temperature: -20° to 60°C
 (-4° to 140°F)
Humidity: Non-condensing (0 to 95% RH)
Sealing: Die cast aluminum case.
 NEMA5/IP53 sealing for dust, moisture
 and splashing.

Power

Operating: 95 - 250 volts AC, 50/60 Hz
Power protection: Handles 1 second
 dropouts
Memory Backup: Rechargeable NiCad
 battery pack

Memory

RAM: 1MB Total
Non-volatile memory: 2MB; option for
 2MB additional, 4MB total
Extended Memory: 2MB Flash; 2MB or
 4MB SRAM

Displays

CGA compatible LCD with backlight
2480/85: 4 lines by 40 characters per line
2481/86: 12 lines by 40 characters per line
 Display up to 24 lines

Keyboards

Alphanumeric: 59 key elastomeric; PC
 style QWERTY layout; 5 shiftable function
 keys
Oversized function/numeric: 35 key
 elastomeric; 10 separate function keys
Time and Attendance: 35 key membrane,
 10 separate function keys
Terminal Emulation: templates for IBM
 5250, IBM 3270 and ANSI/VT

Input Ports

2 bar code input ports
Digital input/output: 4 optically isolated
 sense inputs; 4 two form C output relays,
 dry contacts
 External speaker connection

Bar Code Symbologies

Code 39, 2 of 5, Interleaved 2 of 5,
 Codabar, UPC/EAN, Code 128, Code 11,
 Code 93 and 93i, Plessey, MSI, Code 16K,
 PDF-417 supported using tethered
 scanner

Wired Data Communication

2480/81:
Ethernet: 10BaseT
Serial Ports: RS-232, RS-232/422/485

Integrated RF Module

2485/86 Models
Frequency Band: 2.4 GHz frequency band,
 actual frequencies in use vary by country
WLI Forum OpenAir

Type: Frequency Hopping Spread
 Spectrum

Data Rate: 1.6 Mbps, .8 Mbps fallback
Range*: From 1500+ ft (450+ m) to 500 ft
 (150 m) depending on environment

IEEE 802.11b Wi-Fi Certified

Type: Direct Sequence Spread Spectrum
Data Rate: 11/5.5/2/1 Mbps with Auto
 fallback for increased range

Range* at 1 Mbps: From 1750 ft (533 m)
 to 165 ft (50 m) depending on environ-
 ment

Range* at 11 Mbps: From 525 ft (160 m)
 to 80 ft (24 m) depending on environ-
 ment

Security: Wired Equivalent Privacy (WEP) -
 64 or 128 bit encryption

* Unlimited range with roaming

Host Support Direct Connect

Host Environment: IBM AS/400, S/390,
 Digital, HP, UNIX with Telnet Services
Connectivity: Ethernet, 2.4 GHz wireless,
 serial
Communication: TCP/IP, XMODEM/
 YMODEM
Terminal Emulation: TN 5250, TN 3270,
 VT/ANSI

Host Support via DCS 300 Server

Host Environment: IBM AS/400, S/390,
 Digital, HP, UNIX
Connectivity: 10/100 Mbps Ethernet,
 Token Ring, Twinax, Coax, SDLC
Communications: TCP/IP, SNA, TCP/IP
 socket pass through
Terminal Emulation: IBM SNA 5250, 3270,
 ANSI/VT 100, 220, 320, and Screen
 Mapping
Web-based: dcBrowser™ for HTML
 applications

Language Support

English, German, French, Italian, Spanish,
 Portuguese, Chinese, Japanese, Korean
 and Thai. Localized fonts, keypads and
 Getting Started Guide.
 Supports additional single and double
 byte fonts.

Badge Scanner

- Visible light badge scanner
- Infrared light badge scanner

Accessories

Wall or desk mount brackets,
 Programmer's Software Kit (PSK),
 EZBuilder™ Rapid Application Develop-
 ment software, Adapter for third serial
 port (9 pin RS-232)

Regulatory Approvals

UL Listed, UL 1950 and C22.2 No. 950, TUV
 Rheinland GS, EN 60950, FCC Part 15,
 Canada, RSS210 and ICES 003 Class B, EN
 55022/CISPR 22, Class B, ETS 300 826, ETS
 300 328, Compliant with European
 Directives CE Marked

North

America
 Corporate Headquarters
 6001 36th Avenue West
 Everett, Washington 98203
 tel: 425.348.2600
 fax: 425.355.9551

Systems & Solutions

550 2nd Street S.E.
 Cedar Rapids, Iowa 52401
 tel: 319.369.3100
 fax: 319.369.3453

Media Supplies

9290 Le Saint Drive
 Fairfield, Ohio 45014
 tel: 513.874.5882
 fax: 513.874.8487

Europe/

Middle East & Africa
 Headquarters
 Sovereign House
 Vastern Road
 Reading, Berkshire RG1 8BT
 United Kingdom
 tel: +44.118.987.9400
 fax: +44.118.987.9401

Asia

Hong Kong
 2602 Convention Plaza
 Office Tower
 1 Harbor Road
 Wanchai, Hong Kong
 tel: 852.2574.9777
 fax: 852.2574.9725

Singapore

25-16 International Plaza
 10 Anson Road, 079903
 tel: 65.324.8391
 fax: 65.324.8393

Australia

Level 7, 200 Pacific Highway
 Crows Nest NSW 2065
 Australia
 tel: 61.2.9492.4400
 fax: 61.2.9954.6300

South America & Mexico

Latin America Headquarters
 17921 B Skypark Circle
 Irvine, California 92614
 tel: 949.442.9393
 fax: 949.757.1687

Mexico

Tamulipas 141, Primero Piso
 06140 Mexico, D.F.
 tel: 525.55.211.1919
 fax: 525.55.211.8121

Worldwide

**Fax Document
 Retrieval Service**
 800.755.5505
 (North America Only)
 tel: 650.556.8447

Internet

www.intermec.com

Sales

800.347.2636
 (toll free in N.A.)
 tel: 425.348.2726

Service and Support

800.755.5505
 (toll free in N.A.)
 tel: 425.356.1799

Copyright © 2002 Intermec
 Technologies Corporation. All
 rights reserved. Intermec is a
 registered trademark of Intermec
 Technologies Corporation. All
 other trademarks are the
 property of their respective
 owners. Printed in the U.S.A.
 608322-01D 04/02

In a continuing effort to improve
 our products, Intermec
 Technologies Corporation
 reserves the right to change
 specifications and features
 without prior notice.