

Duo-Touch® II



Duo-Touch® II

The Smallest, Lightest Rugged Tablet PC

RELIABLE

Providing for computing anywhere, anytime

- Meets or exceeds MIL-STD 810F and MIL-STD-3009
- ASTM 4169-99 truck assurance Level II, Schedule B
- Sealed against water and dust intrusion (IP54)
- Hazardous Location (HazLoc) Certification (UL1604)
- Magnesium alloy casing and impact absorbing exoskeleton

INNOVATIVE

For today and for the future

- DynaVue™ outdoor-readable display
- Intel® Core™ Duo Processor U2500 at 1.2 GHz
- Dual-mode active and passive touch screen
- 512MB to 2GB DDRII SRAM 533MHz
- Optional integrated fingerprint scanner

SERVICES

We know the road

- Standard 3 yr limited warranty
- Expanded service options available

WIRELESS

Upgradable, modular design for unparalleled performance and flexibility

- PC Radio card slot with optional sealed cover
- 802.11 a/g/n WLAN
- Bluetooth® 2.0
- Up to 3 RF modems and GPS at the same time
- Various combinations available depending on specific requirements

ERGONOMIC

Designed for rugged mobility

- One handed operation
- Under 2 kg (4.1lbs)
- Intuitive design for easy operation

GENERAL DYNAMICS
Itronix

General Dynamics Itronix® brings the wireless performance and capabilities of its rugged notebooks to a mid-sized Tablet PC!

The Duo-Touch® II is the next generation Tablet PC by General Dynamics Itronix that provides the versatility of tablet computing for challenging work environments demanding rugged computers. Lightweight and ergonomic – enabling one-handed operation – the Duo-Touch II includes both an active digitizer and passive touch screen, and boasts the ruggedness and weatherization you've come to expect from General Dynamics Itronix. Designed for integrated wireless technologies, including EDGE / GPRS / UMTS / HSDPA / HSUPA, EV-DO, 802.11 a/g/n, Class II Bluetooth and GPS, the Duo-Touch II is ready for any wireless network. The Duo-Touch II also features unparalleled outdoor viewability with our new patent-pending DynaVue™ touchscreen technology.

The Duo-Touch II offers the performance and flexibility needed to keep field-deployed, mission-critical workers productive. General Dynamics Itronix took the best aspects of Tablet PC technology and improved on them for high-performance mobile applications. The Duo-Touch II is ideal for industrial, public safety and military applications and is backed by our comprehensive "total solution" services. Whether your mobile workers are new to wireless computing or you are looking to enhance your existing mobile computing line-up, the Duo-Touch II will provide years of reliable performance at the stroke of a pen or touch of a finger.



Product specifications

Compact Size:

- Length: 10.6" (27.0 cm)
- Width: 7.2" (18.4 cm)
- Depth: 1.65" (4.2 cm)

Weight:

- 4.1 lbs (less than 2.0 KG)

Processor/Memory:

- Intel® Core™ Duo Processor U2500 at 1.2 GHz with 2MB L2 Cache
- 512MB to 2GB DDRII SDRAM 533 MHz

Storage:

- Shock mounted 2.5" 80 GB and 120 GB hard disk drive with heater
- Optional 16 GB or 32 GB Solid State Hard Disk Drives

Power:

- Smart 3900 mAh (40.0W) Lithium-Ion main battery pack
- 3900 mAh (40.0W) Lithium-Ion expansion battery pack option

Display:

- 8.4" SVGA TFT Transmissive display with DynaVue™ Patent-Pending technology for optimum outdoor viewability
- DynaVue™ exceeds the minimum contrast ratio as required for bright sunlight per MIL-STD-3009

Pointing Device:

- Digitizer control panel touchscreen and passive touchscreen standard

Operating System:

- Microsoft® Windows XP Tablet PC Edition 2005
- Microsoft® Windows Vista™

Interfaces:

- (1) PC Card slot for Type I or II card with 32 bit Card Bus 2.1 Interface
- (1) Compact Flash slot for Type I or II card
- Built-in RJ-11 and RJ-45 jacks for integrated fax/modem and Ethernet
- (2) USB 2.0 connectors
- 26-pin docking connector
- External speaker and microphone jacks
- Connector for expansion battery

Audio:

- Internal microphone and speaker
- PCI Audio with AC-97 compliance

Integrated Wireline Communications:

- 56 Kbps V.92 fax/modem
- 10/100/1000 Mbit Base-T Ethernet LAN

Optional Integrated Wireless Communications:

- 802.11 a/g/n WLAN
- Bluetooth® 2.0
- GPS
- Sealed, rugged PC Card slot cover for user installed radios
- Up to 3 RF modems and GPS can be integrated at one time

Hot Keys:

- Enter
- Up/Down Arrows
- Escape
- Security (Secure Attention Sequence)
- Rotate Display Image (landscape/portrait)
- Function Key
- Suspend/Power on/off
- WLAN/Bluetooth on/off
- On/off switch for all radio's

Options:

- Desk Mount with 15-pin external video (CRT) port, (2) USB ports, and expansion Battery Charger
- 12 / 24VDC vehicle power supply
- Vehicle dock with serial, USB, and external monitor connections
- Fingerprint Scanner

- Hand strap
- Carry cases for system and accessories with handle and optional shoulder straps
- Backlit keyboard

Environmental:

- Die-cast magnesium for structural components
- Operating temperature -20° to 60° C (-4° to 140° F)
- Storage temperature -55° to 75° C (-67° to 167° F)
- Optional Compliance with UL 1604 Class I, Division 2, Group A, B, C and D for Hazardous Locations
- Meets or exceeds MIL-STD 810F
- ASTM 4169-99 truck assurance Level II, Schedule B
- Sealed against water and dust intrusion (IP54)
- Magnesium alloy casing and impact absorbing exoskeleton
- Boot Temperature: -20° C with Hard Drive Heater
- CE Mark

Warranty

- 3 yr limited
- Extended service and maintenance options available

GENERAL DYNAMICS Itronix

North America Head Office: 12825 E. Mirabeau Parkway • Spokane Valley, WA 99216 • Tel: +1-800-441-1309, +1-509-624-6600 • Fax: +1-509-626-4203 • Email: sales@gd-itronix.com • www.gd-itronix.com

EMEA Head Office: Earlplace Business Park, Fletchamstead Highway, Coventry, CV4 9UR UK • Tel: +44(0) 24 7671 4800 • Fax: +44(0) 24 7671 5677 • Email: sales@gd-itronix.eu • www.gd-itronix.eu

Germany: Tel: +49 211 5 23 91 459 • Fax: +49 211 5 23 91 200 • Email: sales@gd-itronix.eu • www.gd-itronix.eu

France: Parc d'Affaires Silic, 74 Rue d'Arcueil, BP 10405, 94573 RUNGIS Cedex, France • Tel: +33(0) 1 46 87 80 09 • Fax: +33(0) 1 45 60 55 95 • Email: sales@gd-itronix.eu • www.gd-itronix.eu

Canada: 2783 Thamesgate Dr., Mississauga, Ontario, L4T 1G5, Canada • Tel: +1-800-571-5434 • +1-905-672-7007 • Fax: 1-905-672-3999 • Email: sales@gd-itronix.com • www.gd-itronix.com

Asia: 5th Floor-2, No. 80, Chung-Hsiao East Road Sec. 2, Taipei 100, Taiwan • Tel: +866 2 2393 0660 • Fax: +886 2 2395 5256 • Email: sales@gd-itronix.com

© 2008 General Dynamics. All rights reserved. General Dynamics reserves the right to make changes to its products and specifications at any time and without notice. All trademarks indicated as such herein are trademarks of General Dynamics. All other product and service names are the property of their respective owners. © Reg. U.S. Pat. and Tm. Off. V.4 02/08 4T