

MP-4000 TH

MINIPRINTER



Bematech



» DETAIL



APPLICATIONS

- General receipt printing
- Restaurants
- Gas Pumps
- Fast food systems
- Banks
- Drugstores

FEATURES

- Very high printing speed - up to 250 mm/s
- Variable paper width (58 to 82.5 mm) and large receipt paper roll - up to 102 mm
- Easy and fast paper loading
- Small footprint and modern design
- Exclusive ERS and MCS Systems
- Fiscal ready

Solutions for your point of sale



CD-145 + FIT + S-500 + MP-4000



SB-9010 + BR-500 + MP-4000



MP-4000 + TM-100 + SB-7050



» MORE ADVANTAGES

- High performance, flexibility and ease of operation are some of the features that make the Bematech MP-4000 TH thermal receipt printer the ultimate Point of Sale printing solution when top image quality, high speed, reliability and reduced printing costs are needed.



SPECIFICATIONS

Printing	Method: Direct thermal line printing	
	Printing Speed: 250 mm/s	
	Paper Feed Speed: 59 lps	
	Dot Density: 8 dots/mm (203 dpi x 203 dpi)	
	Printing Width: Paper Width (mm)	Printing Width (mm)
	58	48 (384 dots)
76	72 (576 dots)	
80	76 (608 dots)	
82.5	80 (640 dots)	
Characters per Line: 24, 32, 48 e 64		
Characters Set: CODE 437, CODE 850, CODE 858 and CODE 860		
Features	Bar Codes: EAN-8, EAN-13, CODE 39, CODE 93, CODE 128, ITF, CODABAR, UPC-A, UPC-E, ISBN, MSI, PLESSEY, PDF-417	
	Cash Drawer Driver: 01 driver (RJ-12 connector)	
	Metal Tear Off	
	Automatic Cutter - partial and full cutting - (optional)	
	Drop in and easy paper loading	
	Downloadable firmware	
	Bit Map Image Buffer, download logos and code pages	
	Buzzer under software application control	
	Selectable font styles (Normal, Double High, Double Wide, Double High & Wide, Emphasized, Bold, UnderScore, Italic, Inverted, LandScape)	
	Communication Interfaces*: Serial (RS-232C), Parallel (IEEE1284), USB 2.0, Ethernet, WiFi	
Power Supply: 24VDC ± 10%, 2A (external power supply)		
Sensors: Head Up Sensor, End of Paper Sensor, Near End Paper Sensor, Top Cover Sensor		
Media	Type: Single-ply thermal paper roll	
	Width: 58 to 82.5 mm	
	Diameter: Up to 102 mm (4 inches)	
	Thickness: 56 to 107 microns	
Reliability	Printer Head Service Lifetime: 200 km	
	Cutter Lifetime: 2 million cuts	
Environment	Operating temperature: 0 a 50 °C	
	Operating Humidity: 10 a 90% RH (non condensing)	
Physical	Height: 146 mm	
	Width: 150 mm	
	Depth: 218 mm	
	Mass: 1.2 kg	
Drivers	Windows 95 / 98 / ME™, NT 4.0™, Windows 2000™, Windows XP™, Linux CUPST™	
	Configuration and remote management software applicative	
Accessories	* Power Supply, Communication Cable, Paper Roll	
	* Please contact Bematech for the availability of interfaces and accessories.	

(* Please contact Bematech for the availability of interfaces and accessories.

All constant information may be altered without previous notice, consult the sales executive. All constant brands and trademarks in the catalog are property of their respective owners.



Bematech

bematech.com