

# Magellan® 8200Ω

With OmegaTek™ Productivity Technology



## Features:

- OmegaTek™ Productivity Technology
- Enhanced All-Weights™ Platter
- Aggressive & ergonomic 5-sided scanning
- Multiple interface solution supports all popular host interfaces
- FirstStrike™ Advanced Decoding Software
- Flash memory for easy, low cost upgrades
- Powered auxiliary RS-232 port for easy integration of a handheld scanner
- Host Download
- Diagnostic Reporting
- Optional Productivity Index Reporting™ (PIR)
- RSS Decoding
- Optional EAS functionality
- Sunrise 2005 Compliant



## Mechanical

### Length & Weight

Model	Scanner/Scale	Length	Weight
8200Ω	short scanner	13.9" / 35.3 cm	13.0 lb / 5.9 kg
8201Ω	medium scanner	15.7" / 39.9 cm	15.0 lb / 6.9 kg
8202Ω	med. scanner/scale	15.7" / 39.9 cm	18.0 lb / 8.2 kg
8203Ω	long scanner	20.0" / 50.8 cm	15.0 lb / 6.9 kg
8204Ω	long scanner/scale	20.0" / 50.8 cm	20.0 lb / 9.1 kg

Width: 11.5" / 29.2 cm

Depth (below counter): 4.0" / 10.0 cm

Height (above counter): 51" / 131 cm

### Scale Capacities

Capacity: 30.0 lb / 9.99 kg or 15 kg (host dependent)

Minimum Increment: 0.01 lb / 0.005 kg

Vibration Immunity: 4 programmable filter settings

Maximum Static Weight: 150 lb / 68 kg

Adjustments Required: Calibration only

## Optical

Scan Lines: 48

Motor Speed: 6,000 rpm

Scan Rate: 4,800 lines/sec.

Scan Zone: 360°

Sides Read: 5

Read Height: 6.0" / 15.2 cm

## Environmental

### Temperature Rating:

Operating: 50° to 104° F / 10° to 40° C

Storage: -40° to 158° F / -40° to 70° C

Humidity: 5 to 95% NC

## Decoding Capability

The Magellan® 8200Ω autodiscriminates between the following supported symbologies:

- UPC Versions A & E
- UPC Supplementals (Bookland & Coupon Code)
- UPC Add-ons (sub 2 or P2, sub 5 or P5 & CI2B)
- Reduced Space Symbology (RSS-14, expanded & stacked)
- EAN 8, 13
- JAN 8, 13
- EAN/JAN two label
- UCC/EAN 128
- Code 39 (with full ASCII)
- Code 128
- Code 93
- Interleaved 2 of 5
- Italian Pharmacode
- Codabar/NW7
- MSI/Plessey

## Electrical

### AC Power requirements:

100-250 VAC, 50-60 Hz

11 Watts (nominal)

14 Watts (maximum)

4 Watts (sleep mode)

## Communications

**Host:** All Magellan® 8200Ω models support IBM 46XX, RS-232, and IBM USB. There is an optional Keyboard Wedge for the scanner-only version.

### Other:

Powered RS-232 auxiliary port

Scale host port

Remote scale display port

EAS interlock port

## Safety & Regulatory

**Electrical:** IRAM (Argentina), AS/NZS 60950 (Australia);

CSA-C22.2 No. 60950 (Canada); EN60 950 (TÜV Europe);

PSE Mark (Japan); UL 60950 (USA)

**Emissions:** FCC part 15, Class B (USA); AS/NZS 3548 (Australia/New Zealand); EN 55022-B (Europe); CISPR 22-B, VCCI-B (Japan)

**Laser Safety:** Class IIa Laser Product

 (CAUTION: Laser Light – do not stare into beam); IEC 825 Class 1, EN60 825 Class (Europe)

**Restriction of Hazardous Substances:** Complies to EU RoHS



**Weights and Measures:** Argentina; Australia; Brazil; Canada; 90/384/EEC (Europe); Mexico; New Zealand; USA (NIST Handbook 44)

**Contact your PSC representative** for certification schedule and additional listings.

## Other

**EAS Compatibility:** Integrated EAS hardware will work with Counterpoint IV, V, VI, and VII models available from Checkpoint® Systems.

**Good Read** acknowledgement with Sensormatic®.

PSC Inc.

959 Terry Street

Eugene OR 97402-9150 USA

Tel: 800 695 5700 or 541 683 5700

Fax: 541 345 7140

[www.psc.com](http://www.psc.com)



Copyright © PSC Inc. 2005-2006. All rights reserved. Protected to the fullest extent under U.S. and international laws. Copying or altering of this document is prohibited without express written consent from PSC. • PSC Inc. of Eugene, Oregon, USA is ISO registered by NQA. • The PSC logo, Magellan, and SurroundScan are registered trademarks of PSC Inc. • OmegaTek, All Weights, and FirstStrike are trademarks of PSC Inc. All other brand and product names are trademarks of their respective owners. • Additional information concerning this product or other PSC products and services can be found at the PSC web site, [www.psc.com](http://www.psc.com). • Product specifications are subject to change without notice.

