



XPBP04/XPBP09/ XPBP16/XPBP25

XProtect Basis+

MODELS

XPBP04 - XProtect Basis+ for 4 cameras

XPBP09 - XProtect Basis+ for 9 cameras

XPBP16 - XProtect Basis+ for 16 cameras

XPBP25 - XProtect Basis+ for 25 cameras

MINIMUM SYSTEM REQUIREMENTS

OS: Windows 2000, XP Pro, 2003

CPU: Single CPU, Intel recommended

RAM: Minimum 1 Gbyte

Network: Ethernet 100Mbit

Video card: AGP (min. 1024x768)

Video colors: True 24 bit

HDD: E-IDE (7200 rpm recommended)

*Refer to our website for the newest system performance parameters (frames per second).
http://www.panasonic.com/business/security/pc_recording.asp*

XProtect Basis+ offers you digital video solutions for networked surveillance.

XProtect Basis+ is perfect for a business that has a small to medium sized security installation. This solution is attractively priced with functionality to provide essential or expanded features best suited to your needs, for the most value in your surveillance investment. XProtect is a digital surveillance system with good management, flexible scheduling, and fast searching. Controlling up to 25 cameras per server, XProtect Basis+ interfaces with standard IP video and computer hardware – efficient and easy to install or add to later on.

The Administrator

In the Administrator module, you set up all your network cameras, video servers and users of the system. In the friendly interface you define how many camera views you want to see and their scheduling, archiving preferences, e-mail alerting, and user rights.

The Monitor

The Monitor lets you watch all live camera streams simultaneously from a central location for up to 25 cameras per server. The Viewer can play back recordings in views of 4 cameras at the same time.

The Remote Access Server

The built-in web server allows access to your surveillance system from remote locations using Microsoft Internet Explorer. You have full remote access to recorded images and live video in a single view or a quad view.

Panasonic ideas for life



XProtect Basis+ – Specifications

Video & Audio Recording

- Simultaneous video recording, viewing and playback of images
- XProtect Basis+ can be purchased for 4, 9, 16, or 25 cameras
- Offers simultaneous audio recording (one channel) and instant playback in real time
- Recording/viewing speed: 30+ frames per second per camera, only limited by hardware
- Recording quality: All resolutions depend entirely on the IP cameras and video server capabilities
- Recording technology: high speed database holding JPEG images and MPEG4 video streams
- Recording capacity for Basis+: 600,000 images per camera per day.
- Instant search on recordings based on date/time and activity/alarm (Video Motion Detection)
- Results can be generated as a JPEG image or as an AVI film.

Remote Access

- The built-in web server provides remote access to both live viewing and recordings
- From remote locations via the web interface you can view live images from up to four cameras simultaneously
- Playback and browse recordings from one camera via the web interface

Motion Detection

- Fully adjustable, built-in, real time Video Motion Detection
- VMD supports excluded zones
- Cameras can be set to speed up the number of frames when motion is detected or an event occurs
- Active alerting through email

PTZ Control

- Ability to preset 25 PTZ positions per camera
- PTZ zoom in to marked rectangle with certain PTZ cameras

Integration

- Integration with XProtect Transact for monitoring Point-Of-Sale or ATM transaction data together with time-linked video
- Supports camera control via external sensors



Recordings Viewer



Live Monitor

Panasonic ideas for life

DISTRIBUTED BY:

Panasonic System Solutions Company
Unit of Panasonic Corporation of North America
Security Systems

Executive Office: Three Panasonic Way, Secaucus, NJ 07094
(877) 733-3689

www.panasonic.com/security