



XPP01/XPP04/XPP09/ XPP16/XPP25/XPP36

XProtect Professional

MODELS

- XPP01** - XProtect Professional for 1 camera
- XPP04** - XProtect Professional for 4 cameras
- XPP09** - XProtect Professional for 9 cameras
- XPP16** - XProtect Professional for 16 cameras
- XPP25** - XProtect Professional for 25 cameras
- XPP36** - XProtect Professional for 36 cameras

MINIMUM SYSTEM REQUIREMENTS

- OS: Windows 2000 Pro, 2000 Server, XP Pro, 2003 Server
- CPU: Dual CPUs or single CPU with HT, Intel recommended
- RAM: Minimum 1 Gbyte
- Network: Ethernet 1 Gbit and over
- Video card: AGP (min. 1024x768)
- Video colors: True 24 bit
- HDD: E-IDE (7200 rpm recommended) or for best performance: Fast SCSI

Refer to our website for the newest system performance parameters (frames per second).
http://www.panasonic.com/business/security/pc_recording.asp

XProtect Professional offers you high performance IP video surveillance with advanced features.

XProtect Professional is the right product for medium to large installations wanting robust surveillance software with full functions for advanced management, flexible scheduling, fast searching and analysis. Controlling up to 36 cameras per server, XProtect Professional interfaces with standard IP video and computer hardware equipment – efficient to install and easily scalable for future expansion.

Three system components – all in one solution:

Administration

In the Administrator module, you set up all your network cameras, video servers and users of the system. In the friendly interface you define how many camera views you want to see and their scheduling, archiving preferences, e-mail or SMS alerting, and user rights.

Monitoring

The Monitor lets you watch all live camera streams simultaneously from a central location for up to 36 cameras per server. The Viewer recordings can be played back in views of up to 9 cameras at the same time.

Remote Access

XProtect Professional comes with a 4-channel Remote Client or an optional built-in web server for full remote access to alarm information, recorded images and live video.



Remote Client View of Recordings



Live Monitor

Panasonic ideas for life



XProtect Professional – Specifications

Video & Audio Recording

- Available in packages handling 1, 4, 9, 16, 25 or 36 cameras.
- Dual or triple computer monitor viewing support.
- Simultaneous video recording, viewing and playback of images.
- Multi-channel audio recording with instant playback.
- Recording technology: high speed database holding MJPEG & MPEG4 images.
- Support for MPEG4 IP cameras/video encoders.
- Daily archiving can be automatically moved to a network drive with images still available for playback.
- Recording/viewing speed: 30+ frames per second per camera, only limited by hardware.
- Recording quality: All resolutions depend entirely on IP cameras and video server capabilities.
- Recording capacity: 600,000 images per camera per day for unlimited number of days.
- Instant search on recordings based on date/time and activity/alarm (Video Motion Detection).
- On-the-fly configuration changes while recording.
- Event list on recordings
- Buttons to create manual events.

Pan/Tilt/Zoom Control

- Set up to 50 preset PTZ positions per camera.
- VMD sensitive PTZ patrolling among selected presets.
- PTZ go-to preset position on events.
- Remote PTZ camera control in the Remote Client or through the built-in web server.
- Pause PTZ patrolling when manually controlling PTZ.
- Combine PTZ patrolling and go-to-position on events.
- PTZ zoom in to marked rectangle.
- Joystick functionality for supported cameras.

Motion Detection

- Fully adjustable, built-in, real time Video Motion Detection.
- VMD supports excluded zones.
- Speed Up on Motion: cameras can be set to speed up the number of frames when motion is detected or an event occurs, like activation of an external sensor.
- Active alerting through sound, email and SMS.

Evidence Documentation

- Export images as single JPEGs, as a printed report with a single image, or as an AVI with audio as an option.
- Export images in the original database format for viewing with the recordings Viewer.
- Export audio recordings in WAV format.
- Choose to print documentation reports remotely or centrally.

Remote Access

- From remote locations via the Remote Client or the web interface, you can view live video in single, double or quad views, or browse and playback recorded images from up to 4 cameras simultaneously.
- A built-in web server that provides remote access to live cameras and recordings also allows advanced user profiles via the camera-to-user assignment function: The system administrator can set up separate users to view specific cameras for their locations only.
- Logging information shows which users have logged on through the web server interface, with which IP-address, and when.
- Control your PTZ cameras and view alarm summaries remotely.
- Activate output relays for remote control of gates, etc.
- With the Remote Client, you also get:
 - PTZ Point-and-Click control.
 - Improved video compression in streaming from server to client for better use of bandwidth.

Integration

- XProtect Professional offers integration with XProtect Transact for monitoring transaction events with Point-of-Sale or ATM data.
- XProtect Professional also offers integration with XProtect Matrix for instant transmission of live video to any network monitor.

Panasonic ideas for life

DISTRIBUTED BY:

Panasonic System Solutions Company
Unit of Panasonic Corporation of North America
Security Systems

Executive Office: Three Panasonic Way, Secaucus, NJ 07094
(877) 733-3689

www.panasonic.com/security