

CD-70 CUSTOMER DISPLAY

BRILLIANT COLORS DESERVE EXCLUSIVE HOUSING



The CD-70 is a 7" TFT-LCD display, which has a stylish, modern bezel free design. It can be applied as a second, customer-facing display in retail environments. Another adoption is to use it as main display for applications requiring a small monitors. Through the pole stand, the monitor is adjustable and can be fixed easily in the required position, which will convenient for the customers.

Via USB interface the video signal and the power (5V) is applied to the monitor. The power consumption of CD-70 is with 2.5W low, the TFT-LCD display is utilizes LED backlight.

The cost and space-saving display includes a VESA mount for flexible installation.

SPECIAL FEATURES

- Bezel free, spill and dust proof monitor with LED backlight
- Power supplied by USB connection (5V, 2.5W)
- ON / OFF switch
- VESA 75 x 75mm for flexible mounting options

CD-70

| Item | CD-70 | | | | | | | | | |
|----------------|---|--------------|------------|----------|--------------|--------------|--------------|-----------|-----------|-----------|
| LCD Display | Bezelfree 7" TFT-LCD, resolution 800 x 480, brightness 450cd/m ² , LED backlight | | | | | | | | | |
| Display Format | 16 : 9 | | | | | | | | | |
| MTBF | 35.000 hours | | | | | | | | | |
| Pixel Pitch | 0.1926mm (H) x 0.179mm (V) | | | | | | | | | |
| Active Area | 154.08mm (W) x 85.92mm (H) | | | | | | | | | |
| Viewing Angle | 140 (H) / 120 (V) | | | | | | | | | |
| Contrast Ratio | 1100 : 1 | | | | | | | | | |
| Display Colors | 16.7M | | | | | | | | | |
| Power Supply | No adaptor required, power via 5V USB interface | | | | | | | | | |
| Dimensions | 8.07in (W) x 0.91in (D) x 5.31in (H) w/o pole 20.87in (H) with pole (max.) | | | | | | | | | |
| Environment | <table border="0"> <tr> <td></td> <td>Operating:</td> <td>Storage:</td> </tr> <tr> <td>Temperature:</td> <td>32°F ~ 104°F</td> <td>14°F ~ 140°F</td> </tr> <tr> <td>Humidity:</td> <td>20% ~ 80%</td> <td>15% ~ 85%</td> </tr> </table> | | Operating: | Storage: | Temperature: | 32°F ~ 104°F | 14°F ~ 140°F | Humidity: | 20% ~ 80% | 15% ~ 85% |
| | Operating: | Storage: | | | | | | | | |
| Temperature: | 32°F ~ 104°F | 14°F ~ 140°F | | | | | | | | |
| Humidity: | 20% ~ 80% | 15% ~ 85% | | | | | | | | |
| Options | Various terminal mount or standalone possibilities | | | | | | | | | |

*Specification is subject to change without prior notice

