

Care.

Trust.

Responsibility.



## M2-POS

All-In-One Mobile POS

### Features At-A-Glance

Integrated Thermal Receipt Printer

Integrated 3 Track MSR

Integrated Barcode Scanner

Integrated IC Smart Card Reader



## Specifications

Item	M2-POS
Processor	Intel Xscale PXA 270 : 520MHz
Display	3.5" TFT LCD with touch screen, 260k color, (240 x 320)
System Memory	64MB NOR, 64MB NAND, 128MB SDRAM
Telecom Standards	Quad-band GSM / GPRS or CDMA
Communication	Wifi 802.11 b/g, Bluetooth 2.0 class 2 (profile: SPP)
Printer	2" thermal printer (3.14" per second)
MSR	1,2,3 track supported (bi-directional)
IC Card ***	IC card EMV2000 Level 1,2 certified (4 SAM slots)
Barcode Scanner ***	1D
Camera ***	2 Megapixel
Extension Slot	microSD card
Drop Test	4 ft
Operating Temperature	32° F ~ 40° F
Storage Temperature	-4° F ~ 122° F
Interface	Mini-USB 2.0
Battery	Rechargeable Li-ion battery 7.4V (1900mAh)
Cradle	RS232C * 2 ports, USB host & slave ports, mini-USB, battery slot charger
Dimensions	3" (W) x 8.7" (L) x 1.31" (H)
Weight	Standard model 0.90 lb without battery (Battery : 0.19 lb)
Other	Earphone jack & speaker

\*\*\* Optional Upgrade

## Features In Detail



### M2-POS Cradle



Cradle Ports:

- mini USB
- USB 1.1
- standard USB
- 2 Serial (RS232)



www.partnertechcorp.com

Partner Tech USA • 51 Parker • Irvine • CA • 92618 • Tel: (949) 598-1888 • Fax: (949) 598-0088

© 2010 Partner Tech USA. All rights reserved. Reproduction in whole or in part without written permission is prohibited. Features and specifications are subject to change without notice. All weights and measurements are approximate.