

Care.

Trust.

Responsibility.



MP-300

Mobile Printer

Features At-A-Glance

3.14" Paper Printer

Bluetooth Enabled

Quick Release Paper Cover

Leather Carrying Case



Specifications

Item	MP-300
Printing Speed	2.3" / second
Dot Density	203 DPI
Effective Printing	Width : 2.83" , 576 dots/line
System Memory	8 MB SDRAM, 4MB Flash
Character Per Line	Font A : 48 columns, Font B : 64 columns
Paper Width	3.14"
Paper Roll Diameter	Max Φ 45mm
Interface	Serial (RS-232C) / Bluetooth Class 2
Barcode	EAN-8, EAN-13, CODE39, ITF, UPC-A CODABAR, CODE93, CODE128, PDF417(2D)
Driver	Windows CE 4.2 & 5.0, Windows Mobile 5.0
Sensor	• Standard : paper end sensor, cover open sensor • Option : black mark sensor
Charger	Input : AC 100V ~ 240V, 50-60 Hz, Output : 8.4V, 0.8A
Battery	• 7.4V 1130 mAH Li-ion, 2 hr charging time • 40 - 50 minutes in continuous operation
Operating Temperature	41° F ~ 104° F
Storage Temperature	68° F ~ 104° F
Operating Humidity	35% ~ 80%
Storage Humidity	10% ~ 90%
Dimensions	5.9" (W) x 7.6" (D) x 5.8" (H)
Weight	1 lb. (0.77 lbs without battery and paper)
Accessories	Battery, RS-232 cable, charger, paper roll, CD, leather case
Certifications	• EMI & Safety : CE, FCC, CB, UL BSMI, CCC • RF : SRRC, FCC, ID, R & TTE, NCC

Features In Detail



MP-300 Carrying Case



MP-300 Open Cover



www.partnertechcorp.com

Partner Tech USA • 51 Parker • Irvine • CA • 92618 • Tel: (949) 598-1888 • Fax: (949) 598-0088

© 2010 Partner Tech USA. All rights reserved.
Reproduction in whole or in part without written permission is prohibited. Features and specifications are subject to change without notice. All weights and measurements are approximate.