

PAR//NER

CARE . TRUST . RESPONSIBILITY

Order Terminal OT-110

Order Taking with style



The functionality and stylish appearance of the OT-110 is ideally suited to the hospitality environment thanks to its compact size, lightweight design and durability. Orders can be transmitted directly from the OT-110 to the bar or kitchen via WiFi, allowing the employees to spend more time with guests and less time walking back and forth. The active WLAN roaming-function guarantees that there will be no break-off, if there are two or more Access-Points in the same network. With over 65 hours standby, the OT-110 has an intelligent power management.

Outside of the traditional restaurant environment, mobile order taking can be applied to an array of vertical markets such as sport events, music events, corporate hospitality, leisure clubs, night clubs, VIP lounges, stock taking, etc.

Special Features:

- 4.3" widescreen touch TFT-LCD
- Vibration alert
- 4-way direction sensor
- IP54 protection class
- Active WLAN roaming

Optional:

- 3-track MSR
- RFID 13.56MHz (MIFARE)
- Scanner 1D Symbol SE955
- Scanner 2D Honeywell

Order Terminal OT-110

Technical data

| Item | OT-110 | |
|----------------------|---|-----------|
| CPU | Samsung S3C 6410 667 MHz | |
| Memory | Mobile DDR 128MB, NAND flash 256MB | |
| LCD | 4.3" touch TFT-LCD widescreen (resolution 272 x 480) | |
| Connection Interface | WiFi 802.11 b/g/n Built-in class 2 bluetooth 2.1+EDR Mini USB 2.0 (client) / 1.1 (host) | |
| Operating System | Windows CE 6.0 | |
| Audio | Speaker, internal microphone, earphone jack, microphone jack | |
| Storage | Micro SD card (SDHC support) | |
| Special Features | Alert via vibration 4-way direction sensor Ambient light sensor | |
| Battery | Li-ion 2200 mAh (with gauge) | |
| Ruggedness | IP54, 1.2 meter drop test | |
| Dimensions | 133 mm (H) x 82 mm (W) x 19 mm (D) | |
| Weight | Approx. 220g with battery | |
| Environment | Operating | Storage |
| | Temperature 0~40 °C | -20~60 °C |
| Certifications | EMC & Safety: CE, FCC, BSMI, LVD RF: FCC ID, R&TTE, NCC | |
| Accessories | Included: hand strap, stylus cord, high quality stylus, AC adaptor, battery | |
| Options | 3-track MSR Barcode scanner 1D / 2D RFID 13.56 MHz (MIFARE) | |



Add-on RFID module



Add-on MSR module



Print orders directly to MP-300 mobile printer via Bluetooth



Cradle with spare battery charging slot



Packed with comprehensive accessories