



CARE . TRUST . RESPONSIBILITY

RECEIPT PRINTER RP-100-300II

QUIET, HIGH-SPEED RECEIPT PRINTING



RP-100-300 II: Quiet, High-Speed Receipt Printing

For retail and hospitality businesses that need a dependable and fast receipt printer, the RP-100-300 II is an ideal choice. Its compact form and quiet operation help it fit well in any setting.

The Partner Tech RP-100-300 II is a high-performance, direct thermal line 3-inch receipt printer that offers reliability, flexibility, and speed for a variety of applications.

Fast, Sharp Receipts

One of the strengths of the RP-100-300 II is its top printing speed 300mm per second, reducing transaction times and increasing customer satisfaction. And at a resolution of 203 dpi, receipts are crisp and easy to read.

Get the Look You Want

The RP-100-300 II allows you to customize the appearance of your receipts: line spacing is adjustable, and characters can be bold, underlined, or enlarged. The printer also supports different density bitmap and graphics printing, so you can add logos to enhance receipts, coupons, or vouchers.

Add Barcodes Too

The RP-100-300 II is capable of printing in several two-dimensional barcode modes, so you can further customize your receipts with barcodes for such uses as loyalty programs or customer satisfaction surveys.

SPECIAL FEATURES

- 300mm/sec high speed printing
- 2D barcode printing
- Integrated buzzer
- Star or ESC/POS emulation
- Wall mount support
- Multiple interfaces (serial, Ethernet, and USB)

RP-100-300II

Item	RP-100-300II						
Printing Method	Direct thermal						
Printing Speed	300mm/sec. text printing 150mm/sec. graphic printing						
Dot Density	203dpi (selectable by DIP-switch)						
Dot Pitch	0.141mm						
Paper	Type: thermal paper, black mark Width: 80 ± 0.5mm Print width: 72mm max. Roll ø: 80mm Roll core inner ø: 12mm ± 0.5mm						
Sensor	Paper end, cover open, black mark						
I/O Interface	Multi I/O Interface: Serial (DB9), USB (B type) and Ethernet Cash drawer (support 2 drawers)						
Memory	Flash: 256KB						
Auto Cutter Type	Guillotine (partial cut, tear-off)						
Reliability	Print head: 150km Cutter: 1,000,000 cuts MCBF: 60,000,000 lines MTBF: 360,000 hours						
Power Supply	100~240V / AC 50/60Hz / DC 12V/3A						
Environment	<table border="0"> <tr> <td>Temperature:</td> <td>Operating: 41°F ~ 113°F</td> <td>Storage: 14°F ~ 122°F</td> </tr> <tr> <td>Humidity:</td> <td>10% ~ 80%</td> <td>10% ~ 90%</td> </tr> </table>	Temperature:	Operating: 41°F ~ 113°F	Storage: 14°F ~ 122°F	Humidity:	10% ~ 80%	10% ~ 90%
Temperature:	Operating: 41°F ~ 113°F	Storage: 14°F ~ 122°F					
Humidity:	10% ~ 80%	10% ~ 90%					
Driver	Windows (XP, 7, 8.1,10) Linux (Ubuntu 12.04, 14.04) OPOS (Windows 32/64bit)						
Dimensions	5.47in (W) x 7.09in (D) x 5.04in (H)						
Color	Black/White						

*Specification is subject to change without prior notice



PARTNER TECH USA INC.
15320 Barranca Parkway Suite 150.
Irvine, CA 92618
TEL: +1-949-598-1888
sales@partnertechcorp.com

