



CARE . TRUST . RESPONSIBILITY

PT-6212ES, PT-6215ES AND PT-6515BZ PCT

ALL YOU NEED TO BE FLEXIBLE AND INDEPENDENT



The „All-in-One“ POS line PT-6212ES, 6215ES and PT-6515BZ PCT offers a wide range of compact solution for all kind of business.

Due to its compact design, the Partner Tech “All-in-One” Series fits perfectly into environments, where counter space saving and flexibility is demanded. Without extra modules, cables etc. it is easy to install and can be used in many different fields like retail, kiosk, convenience stores, fashion shops or hospitality locations.

SPECIAL FEATURES

- Intel® Celeron J1900 (2.00GHz-2.42GHz, quad core)
- Fanless cooling technology
- Resistive or Projected Capacitive Touch (PT-6515BZ PCT)
- Integrated 80mm thermal printer
- Integrated 3-track MSR
- Modular design for easy maintenance

OPTIONAL

- Mini PCI-e, e.g. to support WLAN module
- Customer display (2x20 VFD or 7“)
- RFID/NFC reader

PT-6212ES, PT-6215ES and PT-6515BZ PCT

Item	PT-6212ES	PT6215ES	PT-6515BZ PCT
CPU	Intel® Celeron™ J1900 (2.00GHz up to 2.42GHz), quad core, 2MB L2 Cache, fanless		
LCD	12" TFT-LCD resolution 1024 x 768 brightness 350cd/m ² LED backlight	15" TFT-LCD resolution 1024 x 768 brightness 350cd/m ² LED backlight	Bezelfree 15" TFT-LCD resolution 1024 x 768 brightness 350cd/m ² LED backlight
Touch	5-wire resistive ELO touch with USB interface		Projected Capacitive Touch (Multi Touch) with USB interface
RAM	DDR3 SO-DIMM, 2 slots up to 8GB		
Storage	1 x 2.5" SATA HDD or SSD (option)		
LAN	1 x RJ-45 10/100/1000 BASE-T Gigabit Ethernet		
I/O Interface	4 x COM (DC+0/5/12V: COM 1-2 BIOS selection, COM 3-4 by jumper) 3 x USB 2.0 1 x USB 3.0 1 x PS/2 1 x RJ-45 Ethernet 1 x RJ-11 Cash drawer control (for 2 cash drawers) 1 x VGA 1 x LPT (PT-6515BZ PCT only) 1 x Mini PCI-e (internal)		
Speaker	2 x 3W speaker (internal)		
Operating System	Windows 7, POSReady 7, Windows 8.1, Windows 10, Linux (ubuntu)		
Power Supply	AC100~240V/DC+12V, 15A, 180W power adaptor		
Dimensions	12.91in (W) x 11.39in (D) x 9.72in (H)	13.58in (W) x 12.64in (D) x 10.08in (H)	14.49in (W) x 11.44in (D) x 10.2in (H)
Environment	Temperature: Humidity:	Operating: 32°F ~ 104°F 15% ~ 80%	Storage: -4°F ~ +140°F 15% ~ 80%
Integrated Peripheral	PT-6212ES/PT-6215ES - 80mm back paper out printer, 2*20 customer display, 3-tracks MSR PT-6515 - 80mm front or back paper out printer, 3-tracks MSR		
Options	7" or 11.6" monitor on pole, NFC/RFID reader, WLAN module 2x20 VFD or CD-70 as customer display (PT-6515BZ PCT)		
Color	black		

*Specification is subject to change without prior notice



PARTNER TECH USA INC.
15320 Barranca Parkway Suite 150.
Irvine, CA 92618
TEL: +1-949-598-1888
sales@partnertechcorp.com