

AIO-XV Series

15" All-in-one Touchscreen System

Processor	Intel Celeron 400MHz or higher, Pentium III (FC-PGA) 500MHz or higher
BIOS	Phoenix/Award
VGA	4MB, upto 32MB
Memory	32MB, upto 512MB, 144-pins DIMM
Hard Drive	Internal 2.5", 2GB or higher
Network	Intel 82559 Pro 10/100BaseT with remote boot and wired-for-management capability
Audio	SoundBlaster compatible
Display LCD	15" TFT Active matrix, 1024x768
Touch Sensor	Resistive, SAW, Capacitive
Connectivity	2 serials, DB9 male (RS232) 1 serial, RJ45 female (RS232/485/422) 1 parallel 2 USB ports 1 network 1 PS/2 keyboard Speaker Out, Mic In
Expansion	1 PCI slot 1 socket for Flash Disk Digital I/O (8 output, 4 input channels)
Housing	Rugged ABS with spill-resistant
Mounting	Base with adjustable angles or Wall-mounted
Power Supply	External adapter, 100-240V, 78Watts
Environment	Relative Humidity : 10% to 95% non-condensing Operating Temperature : 32°F to 104°F Operating Shock : 5G
Dimension (WxHxD)	15.8 x 13.9 x 4.6 inches / 400 x 352 x 117 mm
Weight (approx.)	16 lbs / 7.3 kgs (Base-stand adds 11 lbs / 5 kgs)
O/S	Windows9x, Win2000, XP Prof, CE.NET, Linux
Listings	FCC, EMI, CE Marked, UL
Add-ons	Credit card reader, 2 or 3 tracks Multimedia speaker, 2W Internal modem Wireless (RF) network adapter, 802.11b



Product by



Pioneer POS, Inc.

www.stealthtouch.com

8 8 8 - 4 6 8 - 9 7 5 7