



# PR5022 High-Bright XGA DLP® Projector

FEATURES	BENEFITS
3500 ANSI Lumens	High bright 3500 ANSI lumens XGA DLP® projector is bright enough for conference room installation
DVI-D digital input	Easy set up and sync with digital signals with HDCP decryption (High bandwidth Digital Content Protection)
Top-loading lamp	Saves you time and money – no need to get service technician to swap the lamp., It's easy-to-replace the lamp from any position – even while ceiling mounted
Monitor-out	Monitor loop-through outputs the PC image to a monitor at the same time as the screen for easy reference during presentations
Separate Audio and video inputs	Full connectivity including separate, standard connectors for easy set up including separate audio inputs for computer and video
RS-232	For control of integrated projection systems
Two brightness modes	Economy and standard brightness modes let you adjust to any environment and extend the lamp life
Up to 3000 hours lamp life	Exceptionally long life lamp – up to 3000 hours reduces your total cost of ownership (TCO)
Full-featured remote control	Full-featured remote control with laser pointer and page up/down control for seamless presentations
The Planar PR5022 ships bundled with everything you need	We include the deluxe carry and storage case and all the accessories or cables you need to start your presentations (laser pointer remote, power cord, USB cable, computer cable, AV cable and audio cable)
Built-in speaker	5W TrueMedia™ SPL built-in speaker and audio-output jack for external speakers, controlled with the remote for better sound reproduction and seamless multi-media presentations
Front and rear IR pickups	More responsive remote control allows the presenter to move throughout the room
Five-segment color wheel	Richer colors with a 5-segment color wheel vs. competitors 4-segment color wheel
Anti-theft security features	Kensington® security lock slot and projector password protection lockout help you secure your investment
Customer First™ Warranty	Backed by Planar's industry-leading Customer First™ Warranty with free two-day advance replacement for three years including free shipping both directions you ensure a lower total cost of ownership
DLP® Technology	Higher contrast, smaller projector, longer life.

**Brilliant. Boardroom Performance.** Performance, affordability, brightness and resolution make this high-bright DLP® projector an ideal choice for mid-to-large size conference rooms, boardrooms, classrooms and training rooms. The Planar PR5022 DLP® projector also makes conference room installations affordable with enough brightness to get the job done. It delivers the professional features you need: digital input, RS-232 control, a full-featured remote control with laser pointer and 3500 lumens. It also offers a full connectivity suite, including separate audio and video inputs for computer and video, time-saving top-loading lamp for quick replacement while ceiling mounted, a powerful 5W TrueMedia™ SPL speaker system, monitor loop-through, up to 3000 hour lamp life all at a great price. Bottom line, it's everything you want in a projector.



### Corporate Headquarters

PLANAR SYSTEMS, INC.  
 1195 NW Compton Dr  
 Beaverton, OR 97006-1992 USA  
 Toll-Free +1.866.PLANAR.0 (752.6270)  
 +1.503.748.1100  
 Fax: +1.503.748.1493  
 Email: resellersupport@planar.com  
 Web: www.planar.com

**Customer [ 1<sup>st</sup> ]™**  
 2 Day replacement, 3 Year warranty



© 2007, Planar Systems, Inc. Planar is a registered trademark of Planar Systems, Inc. DLP® and the DLP logo are registered trademarks of Texas Instruments. Technical information in this document subject to change without notice.

		<b>PR5022 High-Bright XGA DLP® Projector</b>
Part Number		997-4277-00
Display Technology		Single Chip DLP® by Texas Instruments
Resolution	native/max	XGA 1024 (H) x 768(V) /SXGA+ 1400 x 1050
Brightness (max)		3500 ANSI Lumens
Weight	net/shipping	7.8 lbs /17 lbs (3.538 kg/7.7 kg)
Contrast Ratio		2200:1
Projection Method		Front/Rear, Desktop/Ceiling
Projection Image/ Screen Size		23.4"~300" (diagonal)
Throw Ratio (D/W)		1.8~2.1
Optical Offset		124%
Digital Keystone Correction		+/- 15°
Minimum Projection Distance		~1m
Lamp Type		230-260W
Lamp Life		2000 hrs standard, 3000 economy
Projection Lens		All glass zoom lens with manual focus
Zoom Ratio		1.15 :1
Aspect Ratio		4 :3 (native) ; 16 :9
Supported Video Standards		NTSC/NTSC 4.43, PAL B/G/H/I/M/N 60, SECAM
SD/HD Video Signal Compatibility		SDTV (480i, 576i), EDTV (480p, 576p),HDTV (720p, 1080i)
Computer Compatibility		VGA, SVGA, XGA, SXGA, SXGA+, Macintosh
Input Sources		DVI-D, Analog, Video (S-Video and Composite RCA), Audio (Stereo, mini-jack and 2 RCA), USB (A to B), RS-232 (9 pin D-sub male)
Output Terminals		Monitor Analog, Audio (stereo, mini-jack)
Built-in Audio		5W TrueMedia™ SPL (Sound Pressure Level) Speaker
External Control		1R Remote, Projector Keypad, RS-232
Input Current		AC 100-240V, 50/60 Hz
Power Consumption	Max(Standby)	330W (standard) 230W (eco) (<5W) built-in power supply
Dimensions	(WxHxD)	11.8 x 9.6 x 3.46 inches, 300 x 244 x 88 mm
Shipping Dimensions	(WxHxD)	16 x 18 x 11 inches, 406 x 457 x 279 mm
Agency approvals		UL, cUL, CB, CE, CCC, ICES-003, FCC-B, RoHS, WEEE
Audible Noise Level		33dba (eco)
Operating Temperature		5°C - 40°C At Sea Level
Projector Warranty		3-Year, Customer First™ 2-Day Advance Replacement
Lamp Warranty		180 days