

Specification	KS-7515	KS-7517
Processor	Intel B81x CPU / 1.6 GHz / 2M cache Intel B950 CPU / 2.1 GHz / 2M cache	
System Memory	DDR3 1066 MHz, SO-DIMM socket x 2, max 8 GB, default 2 GB	
Storage Device	2.5" SATA HDD x 2 or SSD Kit (Optional)	
Power Supply	12V DC power adaptor, 80W (Optional 120W when equipping with 2nd 15" LCD LM-8015 / 8025 / 8035 / 8045 / 8055 / TM-8045) (Black Only)	12V DC power adaptor, 120W (Optional 150W when equipping with 2nd 15" LCD LM-8015 / 8025 / 8035 / 8045 / 8055 / TM-8045) (Black Only)
Audio	2W speaker x 2, line out	
OS support	Win 7 / Windows XP Pro / POSReady 7 / POSReady 2009	
Color	Black / White	
<b>Display</b>		
LCD	15" TFT LCD, 1024 x 768 resolution	17" TFT LCD, 1280 x 1024 resolution
Touch Function	Resistive, 5-wire, USB Interface / IR touch, USB Interface Bezel-free, Resistive touch, USB Interface Bezel-free, PC touch, USB Interface	Resistive, 5-wire, USB Interface / IR touch, USB Interface
Brightness Control	By push button	
Tilt Adjustment	From 15° to 70°	
<b>Connectivity</b>		
LAN Port	10 / 100 / 1000 Mb	
Parallel Port	Optional	
Serial Port	DB9 x 3, RJ-45 x 1 (Optional RJ45 to DB9 cable) with 5V / 12V support on COM1 / COM2 / COM3 / COM4	
UPS Port	Yes, battery (Optional)	
Standard USB Port	7 ( 6 on the I/O plate, 1 on the left side)	
Proprietary USB Port	1 for side mount options	
Powered USB	1 X 24V via 5.5th gen base (Upgrade to 150W power adaptor when equipped with Powered USB) (Black Only)	
VGA Port	D-SUB 15 pins, with 12V power for Posiflex LCD monitor	
CR Port	1, control 2 CR	
<b>Physical Dimension</b>		
Dimension (W x D x H in mm)	378 x 312 x 340	410 x 312 x 385
Weight (N. W. in kg)	9.25	11.7
<b>Environment</b>		
Operation Condition	0°C - 40°C, 20%RH - 90%RH (Equipped with HDD) ; 0°C - 50°C, 20%RH - 90%RH (Equipped with SSD)	
Storage Condition	(-20°C) - 70°C, 10%RH - 90%RH	
<b>Options</b>		
SSD	8 GB minimum	
2nd HDD	2.5" SATA HDD	
UPS Battery	2300 mAh/12V	
WiFi	802.11 b / g / n, USB interface	
2nd LCD Display	15" LM-8015 / 8025 / 8035 / 8045 / 8055 / TM-8045 , 12" LM-6101B / LM-2312 , 10" LM-2310 (Black Only)	
MSR	See security device	
Security Device (SD)	SD-460/SD-460Z : 3 tracks MSR (Optional JIS-II) and/or fingerprint sensor (Black / White) SD-660W : 3 tracks MSR (Optional JIS-II) and/or iButton (Black Only) SD-860W : 3 tracks MSR (Optional JIS-II) and/or RFID and/or WiFi (Black / White)	
PD-306 / PD-306U	2 x 20 LCD, default 200 mm pole (Black Only)	
PD-309 / PD-309U	2 x 20 LCD, default 200 mm pole (Black Only)	
PD-310 / PD-310U	2 x 20 LCD, rear top mount (Black / White)	
PD-2602 / PD-2602U	2 x 20 VFD, default 200 mm pole (Black Only)	
PD-2604 / PD-2604U	2 x 20 VFD, rear top mount (Black / White)	
PD-2605 / PD-2605U	2 x 20 VFD, default 200 mm pole (Black Only)	
PD-76X2	240 x 64 dot graphics LCD, 200 mm pole (Black Only)	
Certifications		

# KS-7500 Series

## Affordable Premium Performance



Design and Manufacturing In Taiwan by Posiflex Technology Inc.

2012 KS75Q4C1

\*\* The product information and specifications are subject to change without prior notice.

## KS-7500 Series

You want a high-end POS terminal with great performance, but premium performance usually costs premium price. Despair no more!

Introducing the newest member of the Posiflex high end family – KS-7500 Series!

Like the Posiflex flagship KS-7700 Series, KS-7500 Series takes advantage of the Intel Sandy Bridge platform, but with the more economical yet powerful Intel B81X and B950 CPU. It also features a new curvier look that adds a little spice to otherwise elegant looking KS Series exterior. Coupling with Posiflex's patented Fanfree design, it assures faster transaction, quieter operation, maximum uptime and minimum maintenance. And most importantly, lower total cost of ownership!

KS-7500 Series offers premium performance without breaking your bank account, making it the best valued high end solution in the market.



### Key Features

- ▶ Equipped with up to Intel Pentium B950 2.1GHz CPU (Optional) and DDR3 memory
- ▶ Resistive, IR, Bezel-free Resistive, or Bezel-free PC touch screen (Bezel-free option for KS-7515 only)
- ▶ 17" LCD 1280 x 1024 (KS-7517) or 15" LCD 1024 x 768 resolution (KS-7515)
- ▶ UPS (Embedded on main board developed by Posiflex) support to avoid sudden loss of power during transaction
- ▶ FanFree design boasting quiet and anti-dust features
- ▶ Patented aluminum die casting design for efficient cooling
- ▶ Push-open cover to protect power switch from accidental shutdown
- ▶ Bottom cable guide design and cover for safety and neat outlook
- ▶ Firm and slim base stand
- ▶ Shiny black or white front bezel for stunning look (Optional)

