


Mobile POS Terminal





Posiflex mobile terminal series, MT-2000/2010, is designed to meet your specific business demand and environment with great mobility. Solidly made with 2 colors, double injection plastic & rubber molding case, MT series is both shock and water resistant to withstand the impact of accidental drop of device and the moist of harsh operation environment. Integrated with data entry, barcode scanning, receipt printing connection, and wireless data transmission technology.





- · Embedded windows CE 5.0 · 3.5"LCD with LED backlit display (240 x 320 resolution)
- · Touch Screen Resistive Type
- · 21-key numeric or 36-key alpha/numeric keypad interface options
- · Battery (Li-ion) provides hours of portable power, supplying 7.4V and 2400mAh
- · Fully charge battery from any level without performance reduction
- · Bluetooth and WIFI capability for wireless data transmission (option)
- · Unobtrusive vibration notification feature for mobile printing link
- · Mechanically and electronically rated to meet 1.5 meter free drop test (any surface)
- · "IP65 compliant" for dust and low pressure jets of water from all directions
- · Attachable integrated barcode scanner, MSR and smart card reader (option)
- · Versatile "Pistol Grip" with trigger for intensive scanning applications (option)
- · Multi-purpose cradle allows recharging of multiple batteries and visual confirmation of LAN and active sync connectivity (option)
- · Discreet storage area for stylus









Posiflex Mobile POS Terminal

MT-2000 Series





SPECIFICATION	MT-2000	MT-2010
CPU	XScale 312 Mhz up	
RAM	On board 128 MB	
Flash	On board 64 MB for OS	
Display	3.5" TFT LCD 240(W) x 320(H) with backlight	
Audio	Built-in 0.5W 8 ohm speaker, Built-in microphone X 1, Earphone Jack X 1	
SD Card	Built-in one SD socket for memory card	
Key Pad	Support 36 key pad matrix	Support 21 key pad matrix
Bar Code Scanner Module	Optional bar code scanner	
Bluetooth	Built-in class2 Bluetooth	
MSR Module	Optional MSR reader	
Smart Card Reader Module	Optional smart card reader	
WiFi	Built-in 802.11b/g WiFi	
Motor	Built-in vibration motor	
Battery	Li-Ion battery pack 7.4V 2400mAH	
Adaptor	Input: AC 110V-220V, 50-60Hz, Output: DC 12V 1.25A 15W	
PDA LED Indicator	WiFi Link Status indicator, Battery Status indicator	
Cradle	Optional 1.ActiveSync for USB port 2.10m /100m Ethernet 3.Supports 2 Li-Ion battery pack charge 4.Includes 12V/3.5A 42W adaptor 5.Two sets of Battery Status LED indicator 6.Cradle In Status LED indicator or ActiveSync Status indicator	
Pistol grip	Optional	
Operating System	WinCE 5.0	
Language	English, Chinese (Traditional), Chinese (Simplified)	
Safety Certifications	FCC, CE, RoHS	

^{**} The product information and specifications are subject to change without prior notice.



DS-100 Optional Cradle for the terminal and 2 additional batteries recharge, LAN port, USB port and indicators.



MD-200 Separately purchased MSR / Smart Card Reader option .



MP-300 Portable mobile 2" wireless thermal printer.



PG-100 Easy operate pistol grip.











