

Specifications

		SMC-210F(P) / 211F(P)	SMC-212F(P)
Picture Tube		53cm(21"), 0.74mm Stripe type, In line gun, 90°Deflection	53cm(21"), 0.74mm Stripe type, In line gun, 90°Deflection
Video	Input	2 BNC, 1 Vp-p	4 BNC, 1 Vp-p
	Output	2 BNC, 75 ohm	1 BNC, 75 ohm
Y/C in		S-VHS jack, 1Vp-p(Y), 0,286Vp-p(C), 1CH (SMC-211F)	S-VHS jack, 1Vp-p(Y), 0,286Vp-p(C), 1CH
Audio	Input	2 RCA, Line level 500mV, 47Kohm(Hi-Impeadance)	4 RCA, Line level 500mV, 47Kohm(Hi-Impeadance)
	Output	2 RCA	1 RCA
Control front		Volume Up/Down, Contrast, Bright, Color, Tint, Sharp, Input select	Volume Up/Down, Auto, Contrast, Bright, Color, Tint, Sharp, Input select
Connection rear		Video A, B(2CH Composite), VCR(1CH) Audio A, B, C(3CH)	Camera 1,2,3,4 (4CH Composite), VCR(1CH) Audio A, B, C(3CH)
Stabilization	Horizontal	Pull in range ±500Hz	Pull in range ±500Hz
		Holding range ±600Hz	Holding range ±600Hz
	Vertical	Pull in range ±4Hz	Pull in range ±4Hz
		Holding range ±4Hz	Holding range ±4Hz
	Sub carrier	Pull in range ±400Hz	Pull in range ±400Hz
		Holding range ±500Hz	Holding range ±500Hz
Convergence		0.5mm Max (Center)	0.5mm Max (Center)
Operating Temperature		-10 ~ +50°C	-10 ~ +50°C
Operating Humidity		10% ~90%	10% ~90%
Power Source		120VAC, 60Hz 230VAC, 50Hz (Rating voltage) 90 TO 260VAC(Voltage range)	120VAC, 60Hz 230VAC, 50Hz (Rating voltage) 90 TO 260VAC(Voltage range)
Power Consumption		Approx. 70W	Approx. 70W
Dimension(W x H x D)		490 x 444 x 482 (mm)	490 x 444 x 482 (mm)
Weight		Approx. 25Kg(with packing)	Approx. 25Kg(with packing)
Packing		620 x 585 x 570	620 x 585 x 570

* "P" indicates PAL model & "N" or no specific alphabet after the model name indicates NTSC model