



EC150 Touch Monitor



Highlights:

- Sleek and Stylish design
- Resistive Touch
- Smart Cable Management
- Detachable Stand / Supports VESA Mounting
- Spill Proof & Anti-Dust
- Dual Input VGA or DVI
- Dual Interface Touch - USB or Serial
- LED LCD
- Converts to a rear 15" customer display for the Breeze, Breeze Performance, Breeze 18.5, Pulse and Universal Printer Base

Peripheral Options:

- 3 Track USB MSR
- 2x20 VFD Rear Customer Display
- Fingerprint Reader

The EC 150 Touch LED LCD Monitor is a reliable LED touch monitor with a sleek and clean look. The EC150 boasts a dual interface resistive touch screen and offers options such as 3 Track USB MSR, Integrated 2 x20 VFD rear customer display and Digital personal URU. All of this is supported with a cable management system that lends itself to a organized and clutter free environment and makes the EC150 a high quality touch monitor that delivers a great value to the customer.



EC 150 Touch Monitor



Display	
Display size	15"
Optimal resolution	1024 x 768
Panel brightness	250 cd/m2 (typical)
Contrast ratio	600:1

Characteristics	
Response time	8ms (typical)
Tilt angle	0° - 70°
Viewing angle	160°

Input	
Input video signal	VGA & DVI
Touch function	USB or RS232

Power	
Power consumption	20W operation / 3W standby
Input frequency	Horizontal 31.5 - 60.2Khz; vertical 56.3 - 75Hz
Power supply	DC 12V +/- 10%

External I/O	
Serial ports	2 (1 x DB9 RS-232, 1x RJ45 fro 2x20 Rear customer display)
USB	2 x USB out, 1 x USB in (B type)
Video	1 x VGA (D-SUB 15pin), 1 x DVI-D
Controls	5 x OSD buttons, status LED

Environment	
Operating temperature	0°F - 40°F
Storage temperature	10°F - 50°F
Operating humidity	20% - 80% RH non-condensing
Storage humidity	10% - 90% RH non condensing

Dimension	
Dimension	14.4(W) x 13.3(H) x 7.9(D)
Weight	10.3lbs (net)

Optional	
3 Track USB MSR	
2 x 20 VFD Rear Customer Display	
Fingerprint Reader	

