

CD4230T

**42" SLIM BEZEL
COMMERCIAL DISPLAY
WITH TOUCH SCREEN**

Interactive digital signage.

ViewSonic's 42" CD4230T Commercial Display features touch screen control powered by 3M's MicroTouch™ DST Touch System. The elegant slim bezel design and dynamic touch panel technology is ideal for use in mall kiosks, corporate directories, product selectors, hotel lobbies, training rooms and point of information applications. The high brightness, high contrast ratio and wide viewing angles clearly communicate your message regardless of ambient light. The fast 8ms response time delivers blur-free scrolling text or video. VGA and RS-232 inputs/outputs allow you to daisy chain multiple displays into your network and still control each display individually. Other inputs include HDMI, S-video, component, composite and PC RGB. The CD4230T with 3M touch screen technology sets a new standard for interactive digital signage displays.



Shown with optional stand.

- > Features 3M's MicroTouch™ DST Touch System
- > 1080i 8ms panel for vibrant video and crisp images
- > High brightness and contrast ratio
- > RS-232 daisy-chain capable
- > VGA and DVI inputs/outputs for flexible connectivity and control
- > Remote and panel control lock out
- > Installation options include stand or VESA® wall mount
- > Integrated ON/OFF scheduling

HDMI™
HIGH-DEFINITION MULTIMEDIA INTERFACE

ViewSonic®
See the difference® 

CD4230T 42" SLIM BEZEL COMMERCIAL DISPLAY WITH TOUCH SCREEN



Shown with optional stand.

LCD	Type	42" color TFT active matrix, wide LCD	
	Display Area	36.6" horizontal x 20.6" vertical; 42" diagonal	
	Optimum Resolution	1366x768	
	Contrast Ratio	2500:1 (typ)	
	Viewing Angles	178° horizontal, 178° vertical	
	Response Time	8ms	
	Light Source	Long life, 50,000 hrs. (typ)	
	Brightness	500 cd/m2 (typ)	
	Aspect Ratio	16:9	
	Panel Surface	Anti-glare, hard coating (3H)	
	INPUT	Video Input	HDMI, DVI, component, VGA
		Video Output	VGA, component, DVI
	Control Input/Output	RS-232	
AUDIO OUTPUT	Speakers		
INPUT SIGNAL	TV/Video Comp.	480i, 480p, 720p, 1080i, 1080p	
CONNECTOR	Analog	15-pin mini D-sub (VGA)	
	Digital	HDMI, DVI	
	Power	3-pin plug	
POWER	Voltage	AC 100–240V (universal), 50–60Hz	
	Consumption	246W (typ)	
CONTROLS	Panel	Power, Exit, +, -, Menu/Enter	
	Picture	Picture mode, contrast, brightness, color temperature, temperature adjust, sharpness	
	VGA Setting	Auto adjustment, clock, phase, sharpness, H. position, V. position	
	OSD Setting	Languages, OSD H. position, OSD V. position, OSD timer	
	Input	VGA, DVI, HDMI, YPbPr	
	Audio	Volume, mute	
	Special	Aspect ratio, over scan, power save, image retention, auto adjustment, monitor ID, reset	
	Diagnostic	Thermal, back light, ambient, 5V detect, 12 detect	
	OPERATING CONDITIONS	Temperature (landscape)	32–104°F (0–40°C)
		Temperature (portrait)	41–95°F (5–35°C)
Humidity		20–80% (non-condensing)	
DIMENSIONS (W x H x D)	Physical with stand (optional)	37.9" x 23.6" x 6.2" (961mm x 598mm x 152mm)	
	Physical without stand	37.9" x 21.8" x 4.3" (961mm x 554mm x 104mm)	
WEIGHT	Net with stand (optional)	56.7 lb. (25.7 kg)	
	Net without stand	51.8 lb. (23.5 kg)	
	Gross without stand	61.7 lb. (28.0 kg)	
VESA® MOUNT		400mm x 200mm	
REGULATIONS		UL/FCC-B	
RECYCLE/DISPOSAL		The lamp in this product contains mercury. Please dispose of in accordance with local, state or federal laws.	
PACKAGE CONTENTS		LCD display, power cable, VGA cable, remote control with batteries, Quick Start Guide	
WARRANTY		Three-year limited warranty on parts, labor and backlight	

Complete Your Digital Signage Solution

Add a network media player and digital signage software.

Media Players

- NMP-550 (RISC-based)
- NMP-700 (X86-based)

Software

- Friendlyway Composer Software
- Best Wave **DisplayIt!** Software
- ViewSonic® Siganage Manager Express



ViewSonic Corporation's QMS & EMS have been registered to ISO 9001 & ISO 14001, respectively, by TUV NORD.

Sales: (888) 881-8781 • SalesInfo@ViewSonic.com • ViewSonic.com

Specifications subject to change without notice. Selection, offers and programs may vary by country; see your ViewSonic representative for complete details. Corporate names, trademarks stated herein are the property of their respective companies. Copyright © 2010 ViewSonic Corporation. All rights reserved. [14857-00B-02/10] CD4230T-1

ViewSonic®
See the difference®

For more product information, visit us on the web at ViewSonic.com