


EP5555

55" DUAL SCREEN DIGITAL SIGN BOARD

Twice the Impact – Dual-Sided ePoster

In-store digital signage is easy with ViewSonic's new dual screen ePoster display solution. Vivid retail messaging is easy by connecting your PC or adding your network media player to the industry standard input connections: HDMI, VGA, YPbPr, USB or composite video (A/V). Each screen can be driven separately with its own content. ViewSonic's ePoster display can easily be connected to a corporate network by adding a network media player. Security is achieved through the locking back cover. Compatible ViewSonic media players are available in both X86 and RISC (Linux) configurations.



- > Dual screen 55" full HD ePoster featuring 1920x1080 resolution and tempered glass faceplate for screen protection
- > All-in-One design provides easy customer deployment with no required construction
- > Dual Internal RISC media player with memory card for playing JPEG images and digital video files
- > Built-in AC power outlet and mounting cradle for adding your own media players
- > Automated power on/off provides easy scheduling of operation
- > 5W (x2) internal audio for playing digital audio files
- > Applications:
RETAIL ADVERTISING
TRANSPORTATION
HOSPITALITY
EDUCATION

EP5555 55" DUAL SCREEN DIGITAL SIGN BOARD



DUAL DISPLAY	Diagonal	55" (139.7 cm)
	Resolution	1920x1080 pixel resolution
	Color	Over 16.7M color (depending on video card used)
	Brightness	450 cd/m ² (typ)
	Contrast Ratio	5000:1 (typ)
	Response Time	6.0ms (typ gray-to-gray)
CONNECTIVITY	View Angle	Up and down 178°, left and right 178° (typ) @ CR>10
	I/O Ports	HDMI, VGA, YPbPr, USB (x2), A/V, RJ45 Pigtail
INTERNAL	Storage	4GB
	Dual Media Players Support	Video: MPEG 1/2/3, H.264, Xvid 1.00-AVI, MP4 Photo: JPEG Audio: WMA, MP3, M4A (AA CC)
		Clock and timer
AUDIO	Speakers	5W (x2)
POWER	Supply	3.2-1.38 A @ 100-240VAC, 50/60Hz
	Consumption	900W (max)
	Save	Off < 1W
OPERATING CONDITIONS	Temperature	32-104° F (0-40° C)
	Humidity	20-90% (non-condensing)
STORAGE	Temperature	-4-140° F (-20-60° C)
ENVIRONMENT	Humidity	10-90% (non-condensing)
DIMENSIONS (WxHxD)	Physical	32.68" x 76.77" x 18.31" (830 x 1950 x 465 mm)
	WEIGHT	Net 303.6 lbs. (138 kg) Gross 330 lbs. (150 kg)
REGULATIONS		FCC, ICES 003, CE
MTBF		50,000 hrs.
PACKAGE CONTENTS		ePoster, power cord, remote control with batteries, key, Quick Start Guide, User Manual and Software on CD
WARRANTY		1-year with extended options available



Sales: (888) 881-8781 • SalesInfo@ViewSonic.com • ViewSonic.com

Specifications and availability are subject to change without notice. Selection, offers and programs may vary by country; see your ViewSonic representative for complete details. Corporate names, trademarks stated herein are the property of their respective companies. Copyright © 2013 ViewSonic Corporation. All rights reserved. [16691-008-04/13]

ViewSonic®
See the difference®

For more product information, visit us on the web at ViewSonic.com