

Get the best for large venue presentations.

The ViewSonic® PJL9371 is an advanced high brightness LCD projector which delivers 4000 lumens with a 2000:1 contrast ratio at 1024x768 XGA native resolution to shine in virtually any lighting situation. The top load lamp and bottom filter with slide design provide for easy maintenance. There are 7 default picture modes (Normal, Cinema, Dynamic, Blackboard, Greenboard, Whiteboard and Daylight modes) to choose from depending on the projected source. RS-232 connectivity enables remote control, while the extensive input options and integrated 16W speakers provide for effective presentations or classroom lessons.

PJL9371

HIGH BRIGHTNESS LARGE FORMAT PROJECTOR

WITH 3LCD TECHNOLOGY



AFFORDABLE PRESENTATIONS THAT SHINE

- > **Bright in virtually any setting**
Packs 4,000 lumens with 2000:1 contrast ratio.
- > **Superior 16-watt stereo sound**
Two powerful 8-watt speakers give your presentation great sound.
- > **Eco-mode for green savings**
Automatically dims projector lamp, lowers power consumption which extends lamp life and lowers noise.
- > **The perfect image in any setting**
Digital keystone correction, and optical zoom ensure the perfect image in any venue.
- > **Easy maintenance**
Easy access to the lamp and filter covers even when the projector is mounted.
- > **Enhanced security features**
PIN lock feature prevents unauthorized use. Kensington® security lock and a security bar allow you to secure the projector to deter theft.
- > **The best warranty in the business**
Covered by a three-year parts and labor limited warranty, first-year Express Exchange® service and one-year limited lamp warranty.



VIEWSONIC
PRODUCTS, PROGRAMS,
AND SERVICES

ViewSonic®
See the difference® 

PJL9371

HIGH BRIGHTNESS LARGE FORMAT PROJECTOR WITH 3 LCD TECHNOLOGY



| | | |
|-------------------------------|-------------------------|---|
| PROJECTOR | Type | 0.63" Poly-Si TFT with micro-lens |
| | Pixel Format | 1024x768 XGA |
| | Lens | Manual zoom, manual focus |
| | Zoom Factor | 1.2 |
| | Keystone | Auto-vertical $\pm 30^\circ$ |
| DISPLAY | Size | 30"-300" (diagonally) |
| | Throw Distance | 35"-358" |
| | Throw Ratio | 1.5~1.8:1 |
| | Lamp | 260W, 5,000 hours* |
| | Brightness | 4,000 ANSI lumens |
| | Contrast Ratio | 2000:1 |
| | Aspect Ratio | 4:3 (native), 16:9 |
| AUDIO | Speakers | 2x8-watt |
| INPUT SIGNAL | Computer and Video | RGB analog, NTSC M, NTSC 4.45, PAL, SECAM, HDTV (480i, 480p, 575i, 720p, 1080i) |
| | Frequency | F _H : 31-100kHz; F _V : 56-120Hz |
| COMPATIBILITY | PC | Analog: from VGA up to UXGA (compressed) |
| | Mac [®] | Analog: up to SXGA (may require a Mac adapter) |
| CONNECTOR | RGB (input) | Analog RGB: DB-15 (x2) |
| | RGB (output) | DB-15 |
| | Composite Video (input) | RCA jack |
| | S-Video (input) | Mini-Din 4-pin |
| | Component Video (input) | RCA jack (x1 set) |
| | Audio (input) | 3.5mm stereo mini-jack (x2) for RGB, RCA L/R jack |
| | Audio (output) | 3.5mm stereo mini-jack |
| | Control | RS232 9-pin D-sub |
| POWER | Voltage | 90-264 VAC, 50/60Hz (universal) |
| | Consumption | 390W (typ) |
| CONTROLS | Basic | Standby/on, Input, menu |
| OPERATING CONDITIONS | Temperature | 41-95°F (5-35°C) |
| | Humidity | 10-85% (non-condensing) |
| NOISE LEVEL | Normal | 36 dB (typ) |
| | Whisper Mode | 29 dB (typ) |
| DIMENSIONS (W x H x D) | Physical (mm) | 400mm x 98mm x 318mm |
| | Physical (in.) | 9.5" x 3.9" x 12.5" |
| WEIGHT | Net | 9.5 lb. (4.3 kg) |
| | Gross | 17.4 lb. (7.9 kg) |
| REGULATIONS | | UL 60950, C-UL, FCC-B, TUV/GS, CB, CE, NOM, ROHS |
| OTHER | | Progressive scan, PIN lock, anti-theft security bar, daylight mode, 16-watt speakers, Kensington lock slot, active iris, eShot, My Screen, my Text, My Button, adjustable fan speed, remote with laser pointer, close caption |
| PACKAGE CONTENTS | | Projector, power cords, VGA cable, remote control, lens cap, ViewSonic Wizard CD, Quick Start Guide |
| WARRANTY | | Three-year limited warranty on parts and labor, first-year Express Exchange [®] Service. One-year limited warranty on lamp** |

Optional Accessories

- Replacement lampRLC-053
- Extended Express Exchange[®]PRJ-EE-10-03
- Universal ceiling mount kitWMK-005
- Wireless G Presentation Gateway ...WPG-350



ViewSonic Corporation's QMS & EMS have been registered to ISO 9001 & ISO 14001, respectively, by TUV NORD.

Sales: (888) 881-8781 • SalesInfo@ViewSonic.com • ViewSonic.com

*Running whisper-mode exclusively can extend lamp life. **Visit ViewSonic.com for full details. †Adapter may be required. Analog adapter available from ViewSonic. Specifications subject to change without notice. Selection, offers and programs vary by country. See your ViewSonic representative for complete details. Corporate names, trademarks stated herein are the property of their respective companies. Copyright © 2009 ViewSonic Corporation. All rights reserved. [14549-00B-09/09] PJL9371-1

ViewSonic[®]
See the difference[®] 

For more product information, visit us on the web at ViewSonic.com