Pro8200

1080P DLP® PROJECTOR

PROFESSIONAL GRADE HOME THEATER

Big Entertainment, right at home.

The ViewSonic® Pro8200 delivers a true HD home theater entertainment experience to even the most discriminating home theater enthusiast. The NATIVE 16:9 WIDESCREEN ASPECT RATIO is ideal for HDTV and movies as well as gaming. The Pro8200 combines state-of-the art DLP® and BrilliantColor™ technology with 2,000 lumens and 4000:1 contrast ratio to deliver a stunning visual experience to any home theater. The innovative seven segment color wheel provides vivid, rich colors. With multiple connectivity, including dual HDMI inputs with HDCP, connects any DVD player, game console and more for complete home entertainment. Get ready for beautifully clear home theater entertainment.

SHINE BRIGHT, ANYWHERE

> **Full 1080p HD resolution**
Enjoy the finest quality in high-definition movies, video and TV.

> **Bright in virtually any setting with 2,000 lumens**
Crisp 2,000 lumen output makes this the perfect choice for family room or home theater.

> **Pixelworks high performance PW980 video processor**
With full 10-bit color processing, detail enhancement technology and motion adaptive de-interlacer for crisper, sharper images.

> **BrilliantColor™ technology**
Latest BrilliantColor technology delivers stunning all-digital clarity with life-like color, sharp graphics and outstanding video. The advanced 7-segment color wheel enhances the yellow color performance that is key to accurate and vivid color reproduction.

> **Ultimate display source flexibility**
Two HDMI 1.3 inputs with HDCP compliance and component video input provide full connectivity in a customized home theater installation.

> **Stay connected**
Supports multiple video timing formats from SD (NTSC, PAL & SECAM) to HD 1080p.

> **Control capabilities**
Features full RS232 control for seamless integration into your automation system.

> **Closed captioning**
Integrated closed captioning decoder for the hearing impaired.

> **Go green and save**
Use the Eco-mode to achieve lower power consumption, reduce overall noise and extend lamp life.

MORE THAN 2,500 AWARDS

VIEWSONIC PRODUCTS, PROGRAMS, AND SERVICES

ViewSonic®
See the difference®

Pro8200

1080P DLP® PROJECTOR – PROFESSIONAL GRADE HOME THEATER

Optional Accessories

> Replacement Lamp	RLC-061
> Universal Ceiling Mount Kit	WMK-005
> Wireless G Presentation Gateway	WPG-360
> Extended Express Exchange®	PRJ-EE-08-03

Projection Distance		4:3 Aspect			
		Wide		Tele	
M	Feet	M	Inches	M	Inches
1.5	4.92	1.22	47.8	0.81	31.8
1.8	5.90	1.49	57.4	0.97	38.1
2	6.56	1.62	63.7	1.08	42.4
3	9.84	2.44	95.8	1.61	63.7
5	16.40	4.05	159.5	2.69	106.0
10	32.80	8.11	319.0	5.39	212.1

ViewSonic Corporation's QMS & EMS have been registered to ISO 9001 & ISO 14001, respectively, by TUV NORD.

Section	Field	Value
DISPLAY	Type	0.66" Digital Micromirror Device (DLP™)
	Resolution	1920x1080 (1080p)
	Lens	1.5× Manual optical zoom / Manual optical focus
	Keystone	Vertical digital keystone correction: +/– 20 degrees
	Size	30"–300" / 0.76m–7.6m
	Throw Distance	0.9m–10m / 3ft–32.8ft
	Throw Ratio	1.4 – 2.14:1
	Lamp	230 watt
	Lamp Life (Normal / Eco-mode)	4000 / 6000* hours
	Brightness	2000 Lumens
	Contrast Ratio	4000:1 (dynamic)
	Aspect Ratio	16:9 (native), 4:3, 16:10, Auto
	Color Gamut	70% NTSC 1931 CIE
INPUT SIGNAL	Computer and Video	NTSC M (3.58 MHz), 4.43MHz, PAL (B, D, G, H, I, M, N, 60), SECAM (B, D, G, K, K1, L), SD 480i and 576i, ED 480p and 576p, HD 720p, 1080i and 1080p
	Frequency	Fh: 30–100KHz, Fv: 50–85Hz
COMPATIBILITY	PC	VGA to 1080p
	Mac®	Up to 1080p
CONNECTOR	RGB Input	15-pin mini D-sub (x2)
	RGB Output	15-pin mini D-sub
	Digital Input	HDMI 1.3 (x2)
	Component	RCA (x3)
	Composite Input	RCA jack
	S-video Input	4-pin mini-DIN
	Audio Input	3.5mm mini jack (x2), RCA (L/R) x1
	Audio Output	3.5mm mini jack
	Mic Input	3.5mm mini jack
	Control	RS-232 (DB-9)
	Screen Trigger	3.5mm (12V/1A)
	USB	Type A for firmware update
AUDIO	Speaker	10W (x2)
POWER	Voltage	100~240VAC (Auto Switching), 50/60Hz (universal)
	Consumption	310W (max) / <1W (stand-by mode)
CONTROLS	Basic	Power, keystone/arrow keys, left/blank, menu/exit, right/panel key lock, enter, source
	OSD	**Picture:** Color Mode, Brightness, Contrast, Video Setting, Color Setting, User Color, Gamma **Video/Audio:** Frequency, Tracking, H Position, V Position, Overscan, Noise Reduction, Audio Setting, Microphone Volume, Speaker Volume, Mute **Setting:** Auto Keystone, Keystone, Aspect Ratio, Projection, Auto Source, Signal Type, Eco-mode, Filter Mode, High Altitude, Quick Power ON, Quick Cooling, DC 12V Trigger **Information:** Input Source, Resolution, H Frequency, V Frequency, Filter Hours, Filter Hours Reset, Equivalent Lamp Hours, Equivalent Lamp Hours Reset, Factory Default **Option:** Blank Screen, Password, OSD Setting, Closed Caption, Others, Display Type, Swap, Function
OPERATING CONDITIONS	Temperature	32°F–104°F (0°C–40°C)
	Humidity	10%–90% (non-condensing)
	Altitude	0~6,000 ft (1,800m), operational up to 10,000 ft (3048m)
NOISE LEVEL	Normal / Eco-mode	31dB / 27dB
DIMENSIONS (W x H x D)	Physical	13.1 × 4.3 × 10.4 (in) / 332.7× 110 × 264.2 (mm)
	Packaging	16.3 × 14.8 × 7.5 (in) / 414 ×375.9 × 190.5 (mm)
WEIGHT	Net	8.5 lb (3.86 kg)
	Gross	11.8 lb (5.36 kg)
REGULATIONS		CB, RoHS, SVHC, WEEE, UL/cUL, FCC-B, ICES-004, TUV-S (Argentina), NOM, PSB, C-tick, KC, CE, GOST-R, Hygienic, UKrSEPRO, CCC
PACKAGE CONTENTS		ViewSonic projector, power cable, VGA cable, HDMI cable, remote control/laser with batteries, lens cap, Quick Start Guide, ViewSonic Wizard DVD (with User Guide)
WARRANTY		3-year limited warranty on parts, 1-year limited warranty on lamp, 1st year Express Exchange® service.

Sales: (888) 881-8781 . SalesInfo@ViewSonic.com . ViewSonic.com

ViewSonic®
See the difference®