

22" Full HD "Edge White" LED Display

High-Definition Television for Hospitality Environments

VT2216-L



The ViewSonic® VT2216-L is a 22" (21.5" viewable) professional monitor with "edge white" LED technology, and a built-in ATSC/NTSC/QAM HDTV tuner ideal for hotel, retail, restaurant, and lounge TV systems. Featuring 1920 x 1080 resolution, 1000:1 contrast ratio and 250-nit brightness, the VT2216-L delivers high-quality image performance. Integrated HDMI, D-Sub and YPbPr video inputs allow for versatile connectivity for high-definition devices. Users can also set up specific product calibration with internal programming features. Dual integrated 10W speakers and SPDIF functionality also make this LED TV a complete multimedia entertainment package.

Built-in HDTV Tuner

The ViewSonic VT2216-L commercial TV has a built-in ATSC/NTSC/QAM HDTV tuner that receives both analog and high-definition TV signals.



USB Multimedia Playback & Cloning

With the handy PC-less USB playback feature, photos and music can be immediately played and shared by plugging a USB drive into the display. In addition, the VT2216-L includes USB cloning for easy duplication in multi-screen environments.

Hospitality Mode for Automated Multi-screen Control

The VT2216-L is great for multi-screen setups in hotels, restaurants, sports bars, or retail outlets that require automated control and customizable presets. With a USB-programmable hospitality setting, each television will have the same customized channel default, audio level, front-panel lockout, and auto power-up settings.

Energy-saving LED Backlight with Long Lifespan

The VT2216-L utilizes an energy-saving LED backlight that consumes 35% less power than conventional CCFL backlight displays, and has an extended lifespan of up to 30,000 hours*.

22" Full HD "Edge White" LED Display

VT2216-L

10W Stereo Speakers with Digital Sound and External Speaker Out

The VT2216-L display has integrated 10-watt stereo speakers with digital sound to enhance on-screen multimedia performance with crystal-clear sound effects. Users can also add external audio via the digital SPDIF audio-out port.

Versatile Input Selection for Flexible Connectivity

With the VT2216-L's versatile selection of inputs, you can easily connect and use a variety of digital equipment for use in hotel rooms and public areas. This includes an HDMI port to connect to high-definition content sources, as well as D-sub ports and composite inputs.



Applications

- Public spaces requiring Full HD video and graphic content within a mid-size screen
- Hotels, restaurants, sport bars, and retail display shelves

Optional Accessory

Wall Mount.....WM-U1

Specifications

PANEL	Type	21.5" color TFT active matrix, wide LCD with WLED backlight
	Display Area	18.8" horizontal x 10.6" vertical; 21.5" diagonal
	Optimum Resolution	1920 x 1080
	Contrast Ratio	1000:1 (typ)
	Viewing Angles	170° horizontal, 160° vertical
	Response Time	5ms
	Light Source	Long life, 30,000 hrs. (typ)
	Brightness	250 cd/m ²
	Aspect Ratio	16:9
	Panel Surface	Anti-glare, hard coating (3H)
INPUT	Video Input	HDMI, Component, VGA, RF (TV) / QAM
	USB 2.0	JPEG, MP3
AUDIO OUTPUT	Speakers	Internal 10-watt (x2)
INPUT SIGNAL	TV/Video Comp	480i, 480p, 720p, 1080i, 1080p
CONNECTOR	Analog	15-pin mini D-sub (VGA), RCA Audio In, PC Audio In, Headphone out
	Digital Power	HDMI, Component, Digital Audio out, USB 3-pin plug
CONTROLS	Picture	Picture Settings, Picture Mode, Screen Size, PC Settings, Color Temperature, Backlight, Advanced Picture Settings, Noise Reduction
	Sound	Sound Setting, Analog Sound, Digital Sound, Digital Audio Output, Equalizer Setting
	Channel	Channel List, Favorite List, Channel Settings, Signal Type, Auto Channel Search, DTV signal
	Parental	Lock Parent Control, V-CHIP, Change Password, Keypad Lock, Source Lock, System Lock
	Setup	Closed Caption, Menu Language, Clock, OSD Transparency, OSD Timer
	Others	Blue Back, No Signal Power Off, No Operation Power Off, User Monitor, Audio Only, TV ID (see user guide for complete OSD functionality)

POWER	Voltage Consumption	AC 100-240V (universal), 50-60Hz 25W (max)
OPERATING CONDITIONS	Temperature	32-104°F (0-40°C)
	Humidity	20-80% (non-condensing)
DIMENSIONS (W x H x D)	Physical with stand	17.1 x 12.0 x 6.3 in. / 435.2 x 305.1 x 160 mm
	Physical without stand	17.1 x 10.6 x 1.8 in. / 435.2 x 270.2 x 47.6 mm
	Packaging	23.3 x 17.6 x 5.0 in. / 592 x 446 x 127 mm
BEZEL DIMENSIONS	Left/Right	12.7 mm / 12.7 mm
	Top/Bottom	14.5 mm / 14.3 mm
WEIGHT	Net with stand	19.4 lbs / 8.8 kg
	Net without stand	17.6 lbs / 8.0 kg
	Gross	24.2 lbs / 11.0 kg
WALL MOUNT	VESA®	100 x 100 mm
REGULATIONS		FCC, UL, RoHS, ENERGY STAR®, Mexico-UL-CoC, Mexico Energy
RECYCLE/DISPOSAL		Please dispose of in accordance with local, state, or federal laws
WARRANTY		1-year limited warranty on parts and labor

What's in the box?

VT2216-L Display, power cord, remote control with batteries, Quick Start Guide, ViewSonic Wizard CD (with User Guide)



ViewSonic Corporation's QMS & EMS have been registered to ISO 9001 & ISO 14001, respectively, by TUV NORD.

*Energy savings may vary based on actual usage and other factors. Specifications and availability are subject to change without notice. Selection, offers and programs may vary by country; see your ViewSonic representative for complete details. HDMI, the HDMI Logo, and High-Definition Multimedia Interface are trademarks or registered trademarks of HDMI Licensing LLC in the United States and other countries. Corporate names, trademarks stated herein are the property of their respective companies. Copyright © 2014 ViewSonic Corporation. All rights reserved. [17115-008-03/14]